


QUICK REFERENCE
LAYOUT/QUOTE SAMPLE

SAMPLE TAKE-OFF DRAWING

Take-off provided for your drawing in 24 hours, turning informal drawings or full plans into customized LED solutions



QUICK REFERENCE LAYOUT/QUOTE SAMPLE

SAMPLE QUOTE

Nova Flex LED, Inc.
2789 Clearwater Road, Suite X
Saint Cloud, MN 56301
(800) 595-6302 www.novaflexled.com

Date	Quote No.
3/12/2019	Q-07335-1

Quoted To:

Company Name
Contact Name
Contact Email
Address
City State Zip
Phone

Ship To:

Location Name
Address
City, State Zip
Phone

Nova Flex Rep	Project / Job
Rachel Ford rachel@novaflexled.com (320) 839-8708	Boca Woods CC

Locker Room 1 Benches

# Runs	Item Code	Description	Qty.	U/M
6.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 79in LED	7	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 110.5in LED	10	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 122.25in LED	11	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
	NF-PS-96W-24V-0/10V	96 Watt 24 Volt 0/10V Dimming UL Listed Power Supply with JBox - 120-277V	2	each
	NF-CH-1612-2M	Surface 1612 Track - 2 Meter Section	11	each
	NF-CH-1612-C/SOFT-2M	Soft Cover for Surface 1612 Track- 2 Meter Section	11	each

Locker Room 2 Benches

# Runs	Item Code	Description	Qty.	U/M
6.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 118.25in LED	10	ft.
1.00	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
	NF-PS-96W-24V-0/10V	96 Watt 24 Volt 0/10V Dimming UL Listed Power Supply with JBox - 120-277V	2	each
	NF-CH-1612-2M	Surface 1612 Track - 2 Meter Section	13	each
	NF-CH-1612-C/SOFT-2M	Soft Cover for Surface 1612 Track- 2 Meter Section	13	each

This quote was generated in 0 Days 4 Hours 9 Minutes by Amy Sanders

QUICK REFERENCE LAYOUT/QUOTE SAMPLE


CONFIGURATION GUIDE

Group Name	# of runs	Item Code	Description	Qty.	U/M
Locker Room 1 Benches	6	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 79in LED	42	ft.
Locker Room 1 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 110.5in LED	10	ft.
Locker Room 1 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 122.25in LED	11	ft.
Locker Room 1 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
Locker Room 1 Benches		NF-PS-96W-24V-0/10V	96 Watt 24 Volt 0/10V Dimming UL Listed Power Supply with JBox - 120-277V	2	each
Locker Room 1 Benches		NF-CH-1612-2M	Surface 1612 Track - 2 Meter Section	11	each
Locker Room 1 Benches		NF-CH-1612-C/SOFT-2M	Soft Cover for Surface 1612 Track- 2 Meter Section	11	each
Locker Room 2 Benches	6	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	54	ft.
Locker Room 2 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
Locker Room 2 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 118.25in LED	10	ft.
Locker Room 2 Benches	1	NF-PRO-O-60-24V-2700K	Nova Flex Pro Series IP65 60 24 Volt 2700K 120in HW Lead + 106.5in LED	9	ft.
Locker Room 2 Benches		NF-PS-96W-24V-0/10V	96 Watt 24 Volt 0/10V Dimming UL Listed Power Supply with JBox - 120-277V	2	each
Locker Room 2 Benches		NF-CH-1612-2M	Surface 1612 Track - 2 Meter Section	13	each
Locker Room 2 Benches		NF-CH-1612-C/SOFT-2M	Soft Cover for Surface 1612 Track- 2 Meter Section	13	each

This order was customized by Nova Flex to save you an estimated install time of : 2hr and 3minutes

Installation guides can be found at www.novaflexled.com/resources/

We appreciate your business!



Product Labeled to Match Configuration Guide