



Scope of Works

Internal Renovation

Wet-seal's mission is to provide our clients with a waterproof system that:

- Protects the building the highest degree from water damage.
- Ensures peace of mind that the job has been carried out to comply with the Australian Waterproofing Code
- Is fully guaranteed and is the best practice waterproof system available.

Enviro-coat IS 511 System Description

Enviro-coat IS 511 is a latex, hybridised with polyurethane fully reinforced waterproof membrane system that has been specifically designed for internal work, where tiles are the finished product and protection of the membrane

Note: In some cases Wet-seal Enviro-coat is used as a sealer over the infill areas (e.g above the 300mm floor level and within the area outside of the reinforced internal corners on the shower wall, no reinforcement fabric is used).

Acceptability of Area to be Waterproofed

Provide Plans/Drawings /Photos of Renovation area

All measurements for quotation will be based on the plans/drawings or written instructions you have provided.

**Note: Verification on measurements/quotation will occur on site prior to commencement of works.
Photo of job to be emailed to Wet-seal Independent Franchisee when booking in!**

Provide photos of the area to be waterproofed to enable the Independent Wet-seal Franchisee to assess the potential work, prior to meeting onsite.

Any variations to this information are to be communicated in writing to the Independent Wet-seal Franchisee.

The structural flooring, substrate, wall sheets and cladding, must be installed in accordance with the Manufacturer's specifications (e.g. minimum wood float finish for concrete or sheeting glued/screwed correctly).



Scope of Works

Internal Renovation

Acceptability of Area to be Waterproofed - continued

The substrate must be clean, dry and smooth with no areas of ponding/divots (all contaminants removed or ground off including tiles or tile adhesive. If Bituminous product has been previously used then this **MUST** be removed prior to booking the job in).

Termination points/shower size, must be clearly marked or advised in writing.

Substrate conditions and moisture levels in the substrates are to be acceptable to enable the primer/membrane to be applied.

Old waste grates are required to be removed, to enable detailing into outlet.

You must provide a work site that meets with the relevant Work Health & Safety regulations. Safety of the Waterproofing Contractor must be considered at all times (e.g. scaffold or safety railing erected to provide a safe work area).

Visual Appearance

Enviro-coat IS 511 waterproofing membrane, is Wet-seal green in colour.

Whilst every effort has been taken in manufacturing quality control, some batch to batch colour variation may be present.



Scope of Works

Internal Renovation

Client's Duty Of Care - Cure Time & Membrane Protection

It is the client's responsibility to:

- Protect the Enviro-coat membrane system from damage until the installation of tiles or protective covering is complete.
- Allow adequate drying time for Enviro-coat IS 511 of 48 hours at 25°C, or longer at lower temperatures. Full cure will be achieved 4 days after application at 23°C/50% RH and longer if temperature is lower and/or relative humidity is higher.
- Enviro-coat IS 511 is not compatible with organic solvents or petroleum based products, including bitumen, paints, adhesives or coatings which may contain solvents or bitumen that may compromise their integrity.

Failure to comply with the above requirements will void warranty.

Tile Adhesive Compatibility

There is a list of compatible tile adhesives listed on the Wet-seal website.

Wet-seal, or Wet-seal's Independent Franchisee, however, do not accept any liability for the installation of the tiles or tile adhesives. The preparation and tiling must not compromise the Enviro-coat waterproofing system in any way. Tiles to be laid must be in accordance with AS/3958.1 and adhesives that meet the requirements of AS/4992.2 must be used.

Warranty

A Wet-seal Installation Certificate stating the specified warranty time and the area being warranted will be sent out to the client by Wet-seal's Independent Franchisee, once the installation system has been completed and the transaction finalised.

In the unlikely event of a defect, send an email to technical@wet-seal.ws with your name and contact details or call Wet-seal's Technical Department on 1800 025 081. Wet-seal will respond with an Information Request Form to be completed and returned.

In relation to the Wet-seal warranty, no rectification work can be carried out without written consent from Wet-seal as this will void warranty.



Scope of Works

Internal Renovation

Liability

If the Enviro-coat membrane is damaged at any time, by someone other than the Independent Franchisee of the Wet-seal Franchise System, the Warranty shall be voided.

No liability whatsoever is accepted for damage – accidental or otherwise – done to the Enviro-coat waterproofing membrane after the application of the membrane is completed.

Any damage repairs will be quoted separately and must be accepted in writing prior to the commencement of work.

Quotation Variance

The quoted waterproofing system is specific to the building structure plans provided to Wet-seal at the time of quotation. While many minor variances can be accommodated, changes to the overall available area may require the submission and written approval of an updated quotation.

Terms and conditions

The Scope of Works must also be referenced against Wet-seal's standard Terms and Conditions.

The Terms and conditions are available on Wet-seal's website: www.wet-seal.com.au