



ODOT Traffic Sign Design Manual

3rd Edition



Oregon Department of Transportation
Technical Services
Traffic-Roadway Section
Traffic Standards & Asset Management Unit
<http://www.oregon.gov/ODOT/HWY/TS/Pages/signing.aspx>

ODOT Traffic Sign Design Manual

Version 03-04 – June 2018

Heidi E. Shoblom, P.E.

ODOT Sign Engineer

Traffic Standards & Asset Management Unit

heidi.e.shoblom@odot.state.or.us

The material contained herein is for information purposes only and may be used to aid new employees and those unfamiliar with ODOT Traffic Engineering practices, in accessing and applying applicable standards, statutes, rules, and policies related to traffic sign design.

This manual was authored by Greg Stellmach, former ODOT Sign Engineer, and is maintained by the current ODOT Sign Engineer. Comments can be emailed to Heidi Shoblom, ODOT Sign Engineer.



Oregon Department of Transportation

Technical Services

Traffic-Roadway Section

Traffic Standards & Asset Management Unit

<http://www.oregon.gov/ODOT/HWY/TS/Pages/signing.aspx>



Oregon

John A. Kitzhaber, M.D., Governor

Department of Transportation

Traffic-Roadway Section, MS#5

Traffic Standards & Asset Management Unit

4040 Fairview Industrial Drive

Salem, Oregon 97302-1142

DATE: September 20, 2013
TO: Sign Designers
FROM: Heidi E. Shoblom, P.E.
State Sign Engineer
SUBJECT: 2013 Sign Design Manual

The purpose of this manual is to familiarize new sign designers with their responsibilities and to provide them with an organized collection of standards, guidelines, policies, and procedures to design a permanent signing plan for a project on the State Highway System. The concepts in the manual work for local roads as well as State highways, so a road authority for a city or county can use this document as well.

The amount of design work consulted out by ODOT has increased dramatically over the last decade. This manual is intended to provide instruction that will not only help in developing our ODOT design staff, but will also provide the information necessary for consultants or municipalities to produce PS&E documents for ODOT contracts.

All the information included in this manual is in compliance with the Manual on Uniform Traffic Control Devices (with Oregon Supplements), and the Sign Policy and Guidelines for the State Highway System.

This manual is not a stand-alone manual that contains everything you need to know to create a perfect sign design plan. There are links to many different web sites and publications in this manual that should be used when mentioned in the text. This information, in combination, will give you the background to put the whole design together.

This manual is not intended to replace any existing ODOT policy. It is intended to supplement existing ODOT policies, yet enhance the specific discipline of Permanent Signing Plans Design. This manual is to be used as a resource, a guide, a technical reference, and a teaching aide, as well. Please contact the Traffic-Roadway Section for clarification or interpretation of any policies and standards within this manual.

The procedures described in preparing sign plans provide one way of completing a set of contract plans. There are other acceptable ways of completing contract plans. When preparing contract work on a set of ODOT signing plans, it is important to check with the Region Sign Designer, prior to beginning design work, to coordinate design expectations for the project.

Contents

Contents iii

Figures vi

Tables vii

1 | Developing Plans 2

 Project Scope 2

 Treatment of Existing Signs and Supports 2

 Critical Sign Locations 4

 Sign Spacing 19

 Sign Specific Needs and Guidance 20

2 | Designing Signs 28

 Choosing Substrate and Sheeting Types 28

 Designing Regulatory and Warning Signs 32

 Designing Guide Signs 34

3 | Designing Supports 40

 Choosing a Support Type 40

 Wood Posts 40

 Steel Supports 40

 Other Supports 42

4 | Drafting Standards 46

 General 46

 Plan Sheets 50

 Sign Details 57

 Sign and Post Data Tables 64

 Sheet Numbers 76

 Archiving of Files 77

5 | Standards 78

 Standard Drawings and Standard Details 78

 Standard Specifications and Special Provisions 78

6 | Estimates 82

 List of Bid Items 82

 Providing Quantities 84

 Unit Costs and Regional Factors 86

Anticipated Items..... 86

7 | Design Follow-Up..... 90

 Construction Support..... 90

 Shop Drawings / Submittals 90

8 | Special Design Considerations 94

 Review Requirements for Interstate Signing..... 94

Appendix A | Signing Contacts 98

 Project Leader / Consultant Project Manager 98

 Roadway Designer..... 98

 Specification Writer..... 98

 Region Sign Designer..... 98

 Traffic-Roadway Section Staff..... 99

 District Sign Supervisor/Coordinator 99

 State Parks 99

 Oregon Travel Experience (OTE) 99

 Right-of-Way..... 99

 Sign Structures Designer 100

 Geotechnical Engineer..... 100

 Landscape Designer..... 100

 Other Traffic Designers 100

 Project Manager (and Inspector) 100

 Bicycle & Pedestrian Program Manager 101

 Construction Materials Inspection Lab..... 101

 Survey Crew 101

 Region Mobility Liaison..... 101

Appendix B | Sign Design Resources..... 102

 Existing Sign Inventory & Photos 102

 Digital Video Log..... 102

 Manual on Uniform Traffic Control Devices (MUTCD) 102

 Standard Highway Signs Manual 103

 Oregon Supplements to the MUTCD 103

 Sign Policy & Guidelines for the State Highway System 103

 ODOT Traffic Manual..... 103

Speed Zone Orders	104
No Parking Resolution.....	104
Contract Plans Development Guide.....	104
Standard Specifications and Special Provisions	105
Standard Drawings	105
As-Built Plans.....	105
Oregon Bicycle and Pedestrian Plan.....	105
OARs and ORSs	106
Qualified Products List.....	106
Traffic Control Devices Handbook	106
Interstate Highways Control Cities List	106
Appendix C Level of Development	107
Design Acceptance Package	107
Preliminary Plans.....	107
Advance Plans and Specifications	108
Plans-In-Hand Meeting.....	108
Final Plans and Specifications.....	108
Appendix D Sign Sizes	110
Appendix E Mileage Control Table.....	112
Appendix F Abbreviations	122

Figures

Figure 1 Standard Signing for Safety Corridors	5
Figure 2 Typical Speed Zone Signing	6
Figure 3 Standard Signing for Passing or Climbing Lanes	7
Figure 4 Standard Signing for Slow Moving Vehicle Turnouts	7
Figure 5 Transition Signing for Physical Separation of Lanes	8
Figure 6 Weigh Station Signing Off-Interstate (MUTCD Figure 2D-17, ref.).....	9
Figure 7 Weigh Station Signing Interstate with Weigh-In-Motion	10
Figure 8 Regulatory Signing at Exit Ramp (MUTCD Figure 2B-18, ref.).....	12
Figure 9 Typical Guide Signing at Exit Ramp	12
Figure 10 Typical Signing for Exit Ramp with Right Turn Lane.....	13
Figure 11 Low Mount Signing – Standard Ramp Terminal	13
Figure 12 Enhanced Wrong Way Signing – Folded Diamond Ramp Terminal	14
Figure 13 Low Mount Signing – Ramp Terminal with Concrete Island	14
Figure 14 Low Mount Sign Installations – Freeway Ramp Terminals.....	15
Figure 15 Typical Ramp Meter Signing Layout.....	16
Figure 16 Typical Ramp Meter Signing Layout (Overhead Ramp Meter Installation).....	17
Figure 17 Typical Ramp Meter Signing Layout (Ground Mounted Ramp Meter Installation).....	18
Figure 18 Sample Plan Sheet.....	51
Figure 19 Sample Plan Sheet.....	52
Figure 20 Sample Plan Sheet.....	53
Figure 21 Sample Plan Sheet.....	54
Figure 22 Sample Detail Sheet	59
Figure 23 Sample Detail Sheet	60
Figure 24 Sample Detail Sheet	61
Figure 25 Sample Sign and Post Data Table	71
Figure 26 Sample Sign and Post Data Table	72
Figure 27 Sample Sign and Post Data Table	73
Figure 28 Sample Sign and Post Data Table	74
Figure 29 Sample Sign and Post Data Table	75
Figure 30 Cost Estimating Spreadsheet.....	83

Tables

Table 1 | Minimum Suggested Spacing Between Signs19

Table 2 | Regulatory Sign Border Dimensions33

Table 3 | Word Spacing – Legends.....35

Table 4 | Type “D” Arrow Sizes.....36

Table 5 | ODOT Regulatory and Warning Sign Sizes (inches)110

Table 6 | Control Points Established as City Centers112

Table 7 | Common Oregon Abbreviations.....122

(This page intentionally left blank.)



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 1

Developing Plans

1 | Developing Plans

Project Scope

The first information needed is the scope of the work to be accomplished. There are many types of highway construction projects, and the type of work to be performed will have a big effect on the scope of the work for the permanent signing. A preservation overlay, for example, will not directly impact existing signs in the same manner as a modernization project that includes major widening, alignment changes, and changes in grade, yet signing should not be ignored in the preservation project. Even when existing signing seems to be unaffected, a designer must still evaluate whether it meets all minimum standards set for signing on our highway system. More specific details about the various standards for designing signs and sign supports appear in Chapter 2 and Chapter 3 of this manual.

For most projects, the physical limits (stations, mile points) for the signing plans will coincide with those of the roadway plans. Some projects, however, may not include roadway work and still others may be limited to signing work only. In these cases, the designer should contact the Project Leader or Consultant Project Manager for information such as project limits, or scope of signing work. In some instances, the signing limits will need to extend beyond those of the roadway plans. For example, the project paving limits could end in the middle of a school zone, in which case the designer should include all of the signing for that school zone in the sign plans. A project may only involve realignment of ramps at an interchange, but it may actually necessitate changes in guide signs a mile in advance of that interchange. A small widening project to create a left turn lane will require striping and signing changes for ¼ mile in advance of each end of the left turn lane. These are just a few of the scenarios in which the signing limits would exceed the roadway limits.

Another consideration for the scoping efforts is whether any project design features will impact vertical clearance in any way such as the addition of any new overhead sign supports. Any time a new overhead traffic structure is added or an additional one is modified that alters the vertical clearance contact the Region Mobility Liaison. The Region Mobility Liaison will provide the appropriate coordination with the Region, and ODOT Motor Carrier Transportation Division.

Each project is unique, so the scope of the signing work to be performed can vary widely from one project to the next. Identifying the full scope of the work to be performed early on will make the design process go more smoothly.

Treatment of Existing Signs and Supports

When gathering information to create your sign plan, you need to determine which signs need replacing. On some modernization projects, you will replace everything. On some preservation projects, you will only replace some of the signs. This depends on the scope of work, how it affects existing sign installations, and the condition of those signs.

The sign designer must replace the signs that do not meet the minimum requirements of the MUTCD or State Sign Policy. Since the MUTCD and Sign Policy are updated frequently, you will need to keep informed of current standards. You can accomplish this by paying close attention to the resource manuals listed in Appendix B.

Design Expectations

Review the sign inventory for non-conforming sign installations. Minimum sign sizes for the State Highway System can be found in the MUTCD and this manual (see Appendix D). The appropriate size of sign depends on speed and type or classification of highway. There are also minimum legend sizes for guide signs that need to be followed. They are presented in Chapter 2 (Designing Guide Signs). If signs do not meet the minimum size standards shown, they must be replaced with the larger required size, which will usually necessitate replacement of the support as well.

Service Life of Signs

The service life of a sign on the State Highway System is usually about 10 to 17 years unless it is damaged. If signs on the inventory are approaching the end of their life span, consider replacing them as part of the project. It is not fiscally responsible to reinstall a sign that you know will fail in a few years.

The sign inventory usually includes condition ratings and photos for each sign. These items help determine which signs are physically in need of replacement. Signs rated as fair or poor should be replaced. Anything rated as new or good should be maintained as long as it complies with MUTCD and Sign Policy standards. Signs that are broken, dented, cracked, delaminating, or contain scratched sheeting or bullet holes need to be replaced. Once the cell pattern of the sign sheeting has been damaged or compromised, its retro-reflective qualities can deteriorate and be ineffective in the dark or in conditions of limited visibility.

If there is any uncertainty as to the quality of an existing sign or signs, the District Sign Supervisor or Coordinator for that area can provide you with valuable input as to the age and condition of the signs.

Service Life of Sign Supports

Sign Bridges, Cantilevers, Structure Mounts, Etc.

The useful life of a sign support varies with the type of support. Large manufactured steel sign supports such as Sign Bridges, Cantilevers, Structure Mounts, Butterfly Supports, etc. have a service life of about 50 years. Usually, the steel will outlast the galvanizing on the steel. These supports are not breakaway and should be shielded from traffic. You should be able to reuse these supports unless you are changing the size of the signs you are replacing. If there is any change in sign size, the support should be structurally evaluated to see if the change will require replacement of the support. If the support is over 20 years old, a field inspection should be done on the support before reusing it. The useful life of the bolted connections and/or galvanizing should be checked before new signs are installed on it. If there are signs of deterioration, consider rebuilding or replacing the support.

Multi-Post Breakaway

The useful life of steel multi-post breakaway sign supports is about 30 years depending on the condition of the support. A field inspection should be made of the supports after 20 years and a decision made whether to reuse or replace the support. Any change in loading (even simply shifting an exit number panel to the right or left side) will necessitate a reevaluation of structural adequacy of the supports.

Triangular Base Breakaway

The useful life of Triangular Base Breakaway Steel supports is about 30 years. The designs of this support have undergone several changes throughout the years and only the newest version should be considered for reuse. A quick check of the base plate will tell you if the latest version is in use. There should be a 5' square concrete pad present and the bolt slots on the base plate should be cut out at 90 degree angles. If these features are not present, then the support does not meet current standards and cannot be reused.

If you have any steel Single Post Slip base sign supports on your project, they will need to be replaced with a Triangular Base Breakaway sign support.

Other Steel

The reuse of other steel supports such as Signal Pole Mounts, Bridge Rail Mounts, etc. should be based on the condition of the existing support. They should be field inspected for loss of galvanizing, fatigue cracking, bolted connections, etc. If there is any doubt whether the support will last another 10 years or more - replace it.

Wood Posts, Perforated Steel Square Tube Posts, Etc.

Most small sign supports such as wood posts, perforated steel square tube posts, etc., should be replaced along with the sign as the support will probably need replacing long before a new sign will need replacement. Remember – round steel pipes are not allowed on the State Highway System because they are not considered a breakaway device; replace any round steel pipe even if it is in good condition.

You will need to rely on the sign inventory you are given to determine if the sign support is new enough that you can leave it in place or remove and reinstall it if required. If it is a small sign support and there is any doubt, just replace it.

Critical Sign Locations

Conventional Highways

The priority for sign placement is

1. Regulatory,
2. Warning, and
3. Guide signs.

In general, you should first consider the location of regulatory signs, followed next by the location of warning signs, and then the location of guide signs.

Several regulatory signs have critical locations. For example, the MUTCD is very specific about placing speed zone signs as close as possible to where the speed changes (MUTCD, Section 2B.13). The same logic applies to No-Passing Zones, School Zones, No Parking Areas, Disabled Parking, Loading Zones, etc. Placement of STOP and YIELD signs are also critical placements.

Warning signs have the next highest priority for location placement. These include Stop or Signal Ahead Symbol signs, curve warning signs, chevrons, DEAD END, NO OUTLET, Object Markers, etc.

After the regulatory and warning sign locations have been established, the guide sign locations can be considered. These include placing street name signs on all intersecting roadways, installing route shield assemblies (if required), destination and distance signs, City Hall, Library, Airport, Train Station, permissive parking and park & ride signs, etc.

There are also specific situations that require specific placement, sequencing, or combinations of regulatory, warning and/or guide signs. Typical locations of signs for various circumstances are shown on Figure 1 through Figure 7. [Figure 6](#) Not all of the signs in the Figures will be appropriate for the project you are working on, so you must select the signs that meet the particular needs of your project.




Figure 1 | Standard Signing for Safety Corridors




Figure 2 | Typical Speed Zone Signing




Figure 3 | Standard Signing for Passing or Climbing Lanes




Figure 4 | Standard Signing for Slow Moving Vehicle Turnouts






Figure 5 | Transition Signing for Physical Separation of Lanes



**Figure 6 | Weigh Station Signing
Off-Interstate
(MUTCD Figure 2D-17, ref.)**



**Figure 7 | Weigh Station Signing
Interstate with Weigh-In-Motion**

Freeways and Expressways

For freeways and expressways, several types of signs have critical locations for placement. Most of the critical locations relate to interchanges as they are the beginning point for measurements. Figure 8 through Figure 10 show the locations mandated for Ramp Terminal signing. On freeways and expressways, a minimum spacing of 800 feet between all large guide signs should be maintained (Reference: “ITE Traffic Control Devices Handbook, 2001, Sign Spreading, Page 52).

Use Figure 8 through Figure 10 to determine the locations for the DO NOT ENTER, ONE WAY, WRONG WAY, STOP, and Stop or Signal Ahead Symbol signs. The MUTCD allows signs on Ramps every 100’ following the EXIT SPEED sign. Review the other existing signs and arrange them in a sequence that gives the driver enough notice that they can get into the appropriate lane to make their turn at the ramp terminal. Remember the priority for signs is: Regulatory, Warning, and then Guide signs. Use the back of the posts of the DO NOT ENTER and WRONG WAY signs for signs facing the opposite direction.

Figure 11 through Figure 14 provide additional guidance regarding low mounted installations for Wrong Way Entrance signing on the Interstate. Prevention of wrong-way traffic movement is a concern whenever an entire roadway is dedicated to one-way traffic, especially on high speed facilities like the Interstate where instances of wrong way driving often result in very damaging or fatal crashes. MUTCD Section 2E.53 provides guidance in the placement of signs to discourage wrong way driving. A combination of ONE-WAY, DO NOT ENTER, and WRONG-WAY signs is recommended. It is also recommended for low or no light rural areas to add a red retroreflective strip to the DO NOT ENTER sign posts. MUTCD Section 2A.21 provides guidance on the use of retroreflective strips on sign posts. The MUTCD also allows for lane use arrows and markings. MUTCD Section 2B.41 includes new language that would allow for the use of a lower mounting height for signs in locations where an engineering study indicates it would address the issue of wrong way movements.

In order to implement the use of low mounted sign installations to prevent wrong way entrances at freeway exits, ODOT has adopted a standard for low mounted installations (Figure 14) that should be used for all interchanges. Guidance and examples on where to place the low mounted signs can be found in Figure 11 through Figure 13. For locations where it is not attainable to construct low mounted signing it should be noted why low mounted signs are not being used. Because wrong way entrance signs are typically installed at a 45 degree angle to approaching traffic and because of the limited performance of high intensity sign sheeting for night time retroreflectivity when viewed at angles other than 90 degrees to approaching traffic, all installations for wrong way entrance signing shall use wide angle prismatic sheeting (ASTM Type IX or better).

Sign designers are responsible for doing a field inspection of the proposed location to determine if there are circumstances that would impede the ability of drivers to view low mounted installations (e.g. Barrier, fencing, snow embankment, etc.). If the designer determines the signs will not be clearly visible at the lower mounting height, the signs shall be installed at the standard mounting height.

Figure 15 through Figure 17 show typical ramp meter sign layouts. The STOP HERE ON RED and FORM 2 LANES WHEN METERED signs are paid for under the applicable sign and post bid items. All other signs are detailed on the “Ramp Meter Plan” and paid for under the lump sum Ramp Meter bid item.




Figure 8 | Regulatory Signing at Exit Ramp
(MUTCD Figure 2B-18, ref.)




Figure 9 | Typical Guide Signing at Exit Ramp




Figure 12 | Enhanced Wrong Way Signing - Folded Diamond Ramp Terminal




Figure 13 | Low Mount Signing - Ramp Terminal with Concrete Island




Figure 14 | Low Mount Sign Installations – Freeway Ramp Terminals




Figure 15 | Typical Ramp Meter Signing Layout




Figure 16 | Typical Ramp Meter Signing Layout (Overhead Ramp Meter Installation)




Figure 17 | Typical Ramp Meter Signing Layout (Ground Mounted Ramp Meter Installation)

Sign Spacing

Conventional Highways

Now is a good time to look at what you have on the plan sheets and look at the spacing between signs both on the State Highway and the intersecting roads. Remember some of the Regulatory signs cannot be moved from where they are placed. Warning signs should be placed using the “Guidelines for Advance Placement of Warning Signs” listed in the MUTCD (Table 2C-4). Note these are guidelines, not mandatory placement distances.

It is important that the warning sign placement gives the driver enough time to determine and take corrective action before they get to the item being warned about. This does not mean that you put the sign in at the distance shown on the chart just because it is on the chart. Visibility and applicability of the sign is just as important. Warning sign legends with smaller letter size (less than 6”) or more than four words might justify using a longer distance.

This leaves other signs subject to moving in order to obtain the proper spacing between the signs to make them readable for the driver. This is also a good time to think about combining some of the signs on the same support to reduce the number of sign installations on the roadway. Do not combine different types of signs on the same post if you can avoid it. Regulatory and Warning signs should be installed on their own posts.

If possible, try to maintain the spacing shown in Table 1.

Table 1 | Minimum Suggested Spacing Between Signs

Speed (mph)	Distance Between Signs (feet)
25	100
30	125
35	150
40	200
45	250
50	300
55, 2-lane sections	350
55, multi-lane sections	500

Freeways and Expressways

Starting at the Exit Direction Sign at the off-ramp, pencil in locations at 800’ spacing between locations back on line. Existing signs will probably include Logo Signs in addition to Major Guide signs. These signs should be at 800’ minimum spacing. If Logo Signs are included, there is a sequence they are to be in approaching the interchange. The GAS sign is closest to the interchange, preceded by FOOD, LODGING, CAMPING, and ATTRACTION. There are only four logos allowed preceding an interchange, so if all five types of logos are present, one of the signs will have to be a combination of two different services. Any service covered by Specific Service (Logo) signing at a particular exit, is not to be included on General Service signing for that same exit.

Pencil in the major guide signs on the sign plan starting at the Exit Direction sign. Going back away from the interchange, they would most likely be: Gas Logo, Food Logo, Supplemental Guide Sign, Lodging Logo, Camping Logo, and Advance Guide Sign. Check to see if there is space available to install a 2 Mile Advance Directional sign if warranted. Usually, any interchange other than a minor one would warrant a 2 Mile Advance Directional sign according to the MUTCD.

Sign Specific Needs and Guidance

After taking stock of the existing signs, consider new signing needs. These needs vary depending on the type of project and the type of facility upon which it is located.

Curve Warning

Curve warning signs should not normally be used when the safe speed on the curve exceeds the posted speed. Curve signs are optional when the safe speed on the curve is the same as the posted speed. Curve warning signs are recommended when the safe speed on the curve is at least 5 MPH less than the posted speed on the roadway. Curve warning signs with an advisory speed plaque are required when the safe speed on the curve is at least 5 MPH less than the posted speed on the roadway.

The only sure way to check the safe speed on curves is with a ball bank indicator. If you are paving the roadway with this project, the paving may change the super-elevation on the road changing the safe speed. You can estimate the safe speed on a curve using the Comfort Speed Chart located in the Highway Design Manual, Page 3-19. The Region Traffic personnel should ball-bank the curves after the project is paved to determine if the speed riders (as designed) are correct.

The W1-1 or W1-3 turn warning signs are to be used when the Advisory Speed is 30 MPH or less. The W1-2 or W1-4 curve warning signs are to be used when the Advisory Speed is more than 30 MPH.

The Large Arrow sign (W1-6) or chevron markers (W1-8) are required as a supplement to the curve or turn warning signs when the safe speed on the curve is at least 10 MPH less than the posted speed. If there are existing Large Arrow signs or chevron markers on the project, they should be replaced unless there is a change in horizontal alignment. Existing signs of this type are an indication that there have been problems in the past with run-off-the-road type of accidents in this area. Placement of these signs or markers should be in conformance with the locations listed in the MUTCD (Sections 2C.09 and 2C.12).

Exit Direction / Advance Guide

The legend on the Exit Direction and the Advance Guide sign are required to be the same message (MUTCD Section 2E.30). There is a limit of two destinations per guide sign. If there are more than two destinations for the interchange, use a supplemental guide sign. Previous designs for these signs may have a message such as “NEXT RIGHT” or “NEXT EXIT”. The MUTCD now requires the Exit Number on the sign face or as an Exit Number sign placed over the guide sign (MUTCD Section 2E.31).

Intersection Signing

Typical intersection signing for cross-roads, T-intersections, and separated roadways is shown in the MUTCD.

Ramp Terminal

Review all Ramp Terminal signs and check for appropriate legends. Check the cross road for Jct. Signs, Route Shield Assemblies (may be incorporated in the guide signs), lane use control signs, speed signs, guide signs, etc. Check the on-ramps for lane drops and place the merge or add lane warning sign. Use Figure 8 through Figure 10 for guidance on ramp terminal sign placement.

Road Names under Warning Signs

When road names are placed under warning signs in this fashion, the road name is to be a yellow background with black legend for the warning sign rider. The road name sign should not exceed the width of the main warning sign. Use guide signs to provide advance street name notice at locations where no intersection or signal ahead warning signs are needed.

Route Signing

All State Highways have an official state route assigned to them, but not all of the State Highways have the state routes signed. Route shield assemblies are required in certain circumstances, such as intersections of two state highways, and the beginning of routes, etc. In the past, Route Shield Assemblies were considered optional in many circumstances. The MUTCD makes route signing at the beginning of State Highways mandatory. Many people navigate by using the Route shields so you should include them whenever a change in direction is required.

The use of Route shield assemblies as trail blazers and confirmation signs is also critical to some drivers. Route shields can be placed inside the Guide Signs, directions for doing that will be discussed later in Chapter 2 (Designing Guide Signs).

Review the existing guide signs to ensure the existing legend is still appropriate for the project. The legend size may need enlarging to meet current MUTCD standards; this will be discussed later in Chapter 2. Pencil in the locations and proposed text for all the guide signs. Advance guide signs on conventional highways are encouraged where Right of Way permits their use.

School Speed Zones

Review the Speed Zone Order (See Appendix B “Speed Zone Orders”) for any school zone exceptions. The School Speed Limit 20 zones are actually exceptions to the Speed Zone Order because the school speed is different than the normal posted speed. The limits shown for the school speed exception are the exact locations for placing the SCHOOL SPEED LIMIT 20 sign for traffic flowing that direction. Directly across the road from the SCHOOL SPEED LIMIT 20 signs (for traffic flowing the other direction), place an END SCHOOL SPEED LIMIT sign, or use an END SCHOOL ZONE sign for zones posted with FINES HIGHER signs. Various school zone scenarios and their associated signing are presented in ODOT’s Sign Policy & Guidelines (Chapter 7).

The laws regarding signing for school zones were changed by the State Legislature in 2003 and 2005. One of the changes was removing school speed zones from under ORS 811.105 as a “basic rule violation” so all school speed zones are included under ORS 811.111 as “violating a speed limit”. In order to reflect the new ORS language, sign designers shall use either the SHS R2-1 SPEED LIMIT 20 sign design as part of the school speed limit assembly, the S5-1 SCHOOL/SPEED LIMIT 20/WHEN FLASHING sign, or the OS5-5 SCHOOL/SPEED LIMIT 20 design from the Sign Policy and Guidelines when designing plans for locations with speed limit signing in school zones.

The OR2-1 sign design from the Sign Policy and Guidelines will no longer be considered an acceptable sign option for speed limit signing in school zones on State Highways. Existing SPEED 20 signs within school zones should be changed to SPEED LIMIT 20 when they are due for normal maintenance replacement or as part of construction projects.

Sign the school zone with the required School Advance Warning Assembly (S1-1). Refer to the Sign Policy and Guidelines, Chapter 7, for their location. Oregon has taken exception to the location of the signing in the MUTCD. The MUTCD recommends placement of the sign with respect to the school grounds or school crossing, but the Oregon supplements require the placement based on the location of the School Speed Limit Assembly (Oregon Supplements to MUTCD, Section 7B.15). For the School Crosswalk Warning Assembly (S1-1) the use of the downward pointing arrow (W16-7p) is required (MUTCD, Section 7B.12). The School Crosswalk Warning Assembly (S1-1) shall not be installed on approaches controlled by a STOP sign (MUTCD, Section 7B.12).

Slow Moving Vehicle Turnouts

Slow moving vehicle turnouts are not commonly installed in Oregon; however, you may have to replace existing signing as part of a project. See Figure 4 for the typical layout.

Specific Service (OTE Signs)

In addition to General Motorist Service signs installed by ODOT, there are other types of blue signs installed by the Oregon Travel Experience (OTE). Logos are available for Gas, Food, Camping, Lodging, and Tourist Attractions. Tourist Oriented Directional signs (TODS) are for any business that gets the majority of their income from people who live outside the local area.

OTE signs are placed on ODOT Right of Way but actually belong to the OTE. These signs are usually listed as “maintain and protect” as part of a project if possible. If the signs are impacted at all, notify Oregon Travel Experience that a project will impact their signs. You can reach OTE at 503-378-4508 or 1-800-574-9397. If the widening of the road makes moving the Logo or TODS necessary, normally they can be removed and reinstalled on the existing supports.

OTE may request new supports or the change in slope may require a new support. OTE needs to review your Preliminary, Advance, and Final Plans. The Logo and TODS signs need to be maintained during construction and the work zone traffic designer should be reminded to provide for them if necessary.

There are occasional brown TOD signs for historic districts, museums, or historic properties. The brown signs are limited to three destination groups: Historical, Cultural, or Recreational. These signs can be word messages or symbol signs or a combination of both words and symbols. Brown background signs would include Historic Districts, Historic Properties, Historic Highways, Museums, Parks, Recreational Areas, Fairgrounds, etc.

Speed Zones

Review the Speed Zone Order(s) (See Appendix B “Speed Zone Orders”) which cover your particular section of highway, pencil in the limits of the speed zone and place the appropriate speed sign at all changes in speed. If there are major intersections between breaks in the speed zone, you should allow for one speed sign each direction as close as possible to the intersection. This allows the driver to determine the appropriate speed upon entering the roadway. You may notice the locations of the signs to be installed are not the same as the existing speed signs. This is not unusual as many speed zones have been incorrectly signed.

The location of the SPEED XX or SPEED LIMIT XX signs should be located at the points of change from one speed limit to another (Section 2B.13 MUTCD) according to the Speed Zone Order. SPEED LIMIT XX signs are to be used for all applications on the interstate, in school zones or within city limits. The SPEED XX signs are to be used for all applications other than these. If the location in the Speed Zone Order is not practical, an adjustment of up to 100 feet is permissible. If the location is not suitable for appropriate signing, the Region Traffic Section should be contacted to discuss the possibility of having the Speed Zone Order re-evaluated.

See Figure 2 for example of typical speed zone signing.

State Supplied Signs

Many projects will include signs with unique graphic designs such as Scenic Byway or Tour Route signs, State Parks Shields (D-434) (supplied by state parks), and others not traditionally fabricated by private sign companies. Whenever these signs are needed, it may make sense for them to be designated state-supplied so they do not enter into the bid. If this is the desire, then the subject signs would be noted in the plans as “state supplied”. Money is then put into the contract for these signs to be purchased later, during construction, from the ODOT Sign Shop, State Parks or other appropriate source as an anticipated item. Anticipated items will be discussed in greater detail in Chapter 6 (Anticipated Items).

Stop Signs

Locate all the STOP sign installations on the plan sheets. Almost all of the state highways are considered to be through highways. This means the highway has priority over intersecting roads except in those locations where the intersecting roadway has a larger volume or a safety issue dealing with alignment has been identified. You can assume (unless the existing signs show otherwise) all roads leading into the State Highway should have a STOP sign (of course, this does not apply to signalized intersections).

Any STOP sign application on the State Highway that stops traffic traveling on the State Highway requires approval from the State Traffic Engineer (ODOT Traffic Manual, Section 5.1.1.1). Decisions for STOP sign applications on cross streets that are not State Highways are done by the Region Traffic Manager/Engineer (ODOT Traffic Manual, Section 5.1.1.2).

Private approaches may sometimes be signed on State Highway Right of Way due to visibility problems. There is a Policy on allowing these signs (see page 5-10 in the [Sign Policy and Guidelines](#)). Private businesses are not allowed to place STOP signs and other traffic control devices on State Highway Right of Way.

The standard STOP sign size listed is 36” for any road 30mph or greater. This would also be the size of the STOP signs on any cross street that intersects on a road 30 mph or greater. Even if the cross street is 25 mph or lower, the STOP sign should be a 36” sign because of the impact to the traffic on the faster highway.

Stop Ahead / Signal Ahead

Check the alignment of the roads entering the State Highway for sufficient safe stopping sight distance. Place Stop Ahead symbol signs if the stopping sight distance is lacking. If a new signal is being installed as part of the project, a Signal Ahead symbol sign should be considered both on the main line and cross streets. If the new signal is in close proximity to other signals, a Signal Ahead Symbol sign may not be necessary.

Street Name

Install street name signs for highway and side streets if the highway has a name. If the highway does not have a name, install route shield assemblies at all the major road connections. Place street name signs on both sides of the post above the STOP sign. At T-intersections, place street name signs (for the highway name) on both sides of the STOP sign post above the side street name signs. At cross street intersections, the street name signs for the highway only need to be on the highway side of the STOP sign post.

Street name signs mounted on traffic signal mast arms shall be shown and detailed on the Signing Plans, but only referenced on the Signal Plans. Since the signs are shown in the Signing Plans, they need to be covered under the bid item for the specific sign type. These signs shall not be paid for as part of the lump sum for signal installation bid item.

Weigh Station

Typical signing layouts for weigh stations off-interstate and those on the interstate with weigh-in-motion are shown in Figure 6 and Figure 7, respectively.

(This page intentionally left blank.)



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 2

Designing Signs

2 | Designing Signs

Choosing Substrate and Sheeting Types

A typical road sign consists of three components: substrate, sign sheeting, and sign legend. This chapter discusses the common construction and materials involved in the construction of road signs.

Sign Substrates

ODOT uses sheet aluminum as our first choice of sign substrate material. However there are situations where sheet aluminum is not the best choice for sign substrate. The other two materials ODOT may use for permanent sign substrate are extruded aluminum and High Density Overlay (HDO) plywood. All three of the signs substrate materials are recyclable.

There are numerous types of substrate for road signs that have been used over the years and new products are being introduced every year. This chapter will deal with the current substrates being used in Oregon. The overall dimensions of a sign will often help determine the appropriate substrate material for fabrication.

Sheet Aluminum

Sheet aluminum is ODOT's first choice of sign substrate anywhere. It has a smooth flat surface and comes in a variety of precut sizes to match most standard sized signs. The thickness of the aluminum is increased as the size increases to maintain the strength of the sign. Sheet aluminum can also be purchased in sheets just like plywood. The Oregon Standard Specifications lists the allowable thickness for the size of sign and also lists the acceptable types of aluminum sheeting (ODOT Specification 02910.10). Using something other than the specified type of aluminum sheeting may result in failed substrate.

Sheet aluminum substrate should not be specified in high wind areas or snow plow areas since the aluminum does not resist bending well. In rural areas with a history of gunshot vandalism, HDO plywood substrate should be considered because unlike aluminum, the plywood can often sustain gunshot damage and still remain readable.

Signs designed using sheet aluminum should be designed in width and height that increase in 3" increments (the same as plywood signs). The maximum size of sheet aluminum signs is 4' x 5', due to its tendency to deform or sustain wind damage when used for signs larger than this. Many other states have limited normal sheet aluminum sign use to this dimension for the same reason. Sheet Aluminum overlays on Extruded Panel signs are not limited in size since the Extruded Aluminum panels support the sheet aluminum. Mast arm mounted street name signs are not limited in size since the signal mast arm helps to support the sheet aluminum.

In some locations of the state, designers must include painting the backs of aluminum signs to blend in with the environment. When required to do this, there is a Special Provision in Section 00940 that should be used for this purpose and it automatically calls up Sections 00593 and 00594 that have the coating specifications. Different locations may call for different colors of paint. Most of these places will also require you to paint the metal sign supports as well.

Extruded Aluminum Panels

Extruded aluminum panels are composed of pre-formed structural shapes bolted together to create the sign substrate. The shape is shown on Oregon Standard Drawing Number TM675 in the upper left corner. The extrusions come in 6" and 12" tall panels up to 34' in length. Each extrusion is covered with sign sheeting prior to bolting the panels together to form the sign. Normally, the border, text, route shields, etc. are placed on a thin aluminum background and then pop-riveted to the preformed sign background. Signs designed using aluminum extrusions should be designed in width and height that increase in 6" increments. Due to size restrictions for plywood and sheet aluminum, extruded aluminum panels must be used for all signs larger than 4' x 8'. The nature of their fabrication requires their fastening to the support by means of post clips rather than bolts. Many of the steel signs supports (Chapter 3) such as triangular base breakaway posts, multi-post breakaway supports, exit number sign mounts and signal pole mounts are designed specifically for fastening by clips. Where such supports are used, extruded panel signs (regardless of size) should be specified.

Occasionally, a legend can be applied directly to the extruded panel if the legend does not span from one extrusion to the other. Direct applied legend when applied to two extrusions will accumulate dirt and other materials where the two extrusions meet causing a dirt pocket that will retain moisture; when this freezes, the sheeting can be damaged by the expanding mass-it also looks very unsightly.

High Density Overlay (HDO) Plywood

HDO plywood is the only plywood allowed for permanent signs on ODOT projects. HDO plywood has a very smooth surface similar to a Formica cabinet face. No primer is required between the face of plywood and the sign sheeting. HDO plywood does not have the surface blemishes found in the MDO plywood due to the thicker overlay applied when the plywood was made. HDO plywood is very rigid and is an excellent substrate for signs that must withstand a lot of wind pressure. This substrate should be used in Snow Zone areas because it holds up very well against the snow blower and snow plow damage. It should also be used in rural areas where there is a history of sign damage from gunshot vandalism, because the plywood can often sustain gunshot damage and remain readable.

This product is available in 4' x 8' sheets (maximum size allowed for plywood substrate signs) and is cut to the size needed for a particular sign. ODOT uses 3/4-inch HDO plywood. If the project you are designing is for someone other than ODOT, you might want to check on the thickness they use. Signs designed using HDO or MDO plywood should be designed in width and height that increase by 3" increments (e.g. 4'-6" x 3'-9").

Medium Density Overlay (MDO) Plywood

MDO plywood formerly was the standard for almost all the plywood signs in Oregon. Some time ago, there was a problem with the primer (required on the MDO plywood for adhesion to the sign sheeting) resulting in massive failures of sign faces throughout the state. ODOT was given no relief by the manufacturers for the signs that had to be replaced when the primer failed. As a result of this, MDO plywood is now allowed on ODOT contracts for temporary signing only.

MDO plywood does have surface blemishes (plugs) that sometimes distract from the smooth finish of the finished sign face. This plywood is very rigid and is an excellent substrate for signs that must withstand a lot of wind pressure. This product is available in 4' x 8' sheets and is cut to the size needed for a particular sign.

Other Substrates

ODOT has tried using plastic and fiberglass substrates on signs in the past without much success. Different substrates will likely be available in the future that will fulfill ODOT requirements for a dependable long lasting sign substrate.

If you are designing a project for a local government and they want to use another substrate, you will need to include a detail and specifications of what the substrate looks like and the materials specification for each type.

Sign Sheeting

There are numerous types of sign sheeting available and each type has its advantages and disadvantages, so it is very important to specify which type of sheeting to use on each sign you have designed.

ASTM Type III

This sheeting is also known as High Intensity. On State Highways, this is the minimum reflective sheeting allowed and also the most used sheeting. Almost all ground mounted signs will use Type III sheeting for backgrounds and almost all of the legends. Type III sheeting is also used for background sheeting on overhead guide signs. This sheeting is warranted for 10 years from the manufacturer.

ASTM Type IV

This sheeting is multi-layer sheeting, sometimes called prismatic sheeting. Performance of Type IV sheeting is similar to the performance of Type III sheeting.

ASTM Type VIII

This sheeting is similar to type IX, but has a narrower band of retroreflectivity. This type of sheeting has not been used in Oregon for permanent signing.

ASTM Type IX

This is a highly retroreflective sheeting, mainly used for overhead sign installations. This sheeting has a much wider angularity and is not quite as bright as the type VII used in the past. It can be used for ground mounted signs, but should be reserved for places where high-impact is needed. It is more commonly used for legend on overhead mounted signs, and can be used as background where more high-impact is needed. Viewing distance on this sheeting is up to 800 feet away. The warranty on this sheeting is 12 years. It also comes in fluorescent colors; yellow, yellow-green, and orange. In the fluorescent colors, a ten year warranty applies.

ASTM Type XI

This sheeting has not been approved for use on Oregon State Highways at this point.

Other ASTM Type Sheeting

ASTM Type I, ASTM Type II, ASTM Type V, ASTM Type VI, ASTM Type VII, and ASTM Type X are no longer used on the State Highway system in Oregon.

Non-Reflective Sheeting

Since the MUTCD requires all signs to be retroreflective and to be the same color at night as during the day, the use of non-reflective sheeting has become extinct except for black. Black sheeting comes in rolls or as a “tape” that is the common width of most borders. The use of black in Oregon is limited to legends for regulatory and warning signs.

Electronic Cuttable Film (EC Film)

This is a semi-transparent film placed over the underlying sign sheeting to change the color of the sign sheeting. It is an alternate to applying another layer of sheeting (usually for legend, but could be a background) in the manufacturing process. Usually, this is not an item you would specify when building a sign plan but it is something of which you should be aware. There is also a black non-reflective EC Film used in lieu of the standard black sheeting mentioned above.

The Sign and Post Data Table sheet provides the sign manufacturer precise information on the construction of the sign specified (See Chapter 4 “Sign and Post Data Tables”). This doesn’t mean there isn’t another way the sign can be built and still perform to ODOT standards. One option is the use of Electronic Cuttable Film (EC Film) not usually listed as a construction method but meets ODOT specifications and performs very well.

The EC Film is a semi-transparent film that allows light to reflect back through to create the colors required on the sign. It is very cost effective for unusual designs (such as the Tsunami Series, Oregon Trail, Lewis & Clark, etc.) since it replaces the silk screening method. For sign shops that do not silk screen, EC Film is a very practical method of building signs. EC Film is also resistant to vandals trying to remove letters from the legend as the film will come off in tiny pieces.

Sign Sheeting Identification

You can view or download a two page document illustrating the identification marks of several manufacturers of the different types of sheeting. This is valuable information for those of you who also will be called upon to identify the materials. It can be accessed at:

http://safety.fhwa.dot.gov/roadway_dept/night_visib/sign_visib/sheetguide/.

Sign Legend

Once the sign sheeting has been applied to the sign substrate, the legend can be applied to the sign face in three different fashions: direct applied, demountable legend, or silk-screening.

Direct Applied

Sign sheeting or black tape is cut into letters, borders or whatever else is called for as a legend. Most sheeting or border tape has a removable backing that can be removed and applied over the background sheeting to form the legend on the sign.

Demountable Legend

Sign sheeting specified for the legend is applied to a thin aluminum and then the letters are cut out with a die (or cut with a router). The legend is then laid out on the sign as specified and pop-riveted to the sign. The advantage of making signs this way is that the legend can be changed on the sign after it is made or erected. This method is required for extruded panel signs if any of the legend on the sign overlaps or crosses the joint between extrusions. This legend is often referred to as “Removable Legend” since the legend can be removed from the sign by drilling out the rivets.

Silk Screening

Smaller signs can have a legend applied by the silk-screening process similar to the way that t-shirts are screen printed. This process is used for many of the standard signs in an effort to keep manufacturing costs to a minimum.

Designing Regulatory and Warning Signs

There are rules for designing signs that come from several different sources including the MUTCD, some are industry standards. The Standard Highway Signs manual shows all of the sign designs for standard regulatory and warning signs shown in the MUTCD. If a standard sign is from the MUTCD, the sign design is already completed for you, but you still must determine the appropriate size to install.

The sizes of standard signs shown for regulatory and warning purposes in the MUTCD (see Tables 2B-1 and 2C-2) vary by highway classification, with larger sizes called for on the wider, higher speed classifications such as freeways and expressways. In many cases ODOT has determined to use larger minimum standard sizes than what is shown in these MUTCD tables. As a result we have created our own standard size chart for regulatory and warning signs, intended to supplement the MUTCD tables. ODOT’s chart is in Appendix D of this publication. Sign sizes for use on our state highway system are to be determined by using this chart. For those regulatory and warning signs not found in Appendix D, sizes are to be determined from use of the MUTCD charts.

Regulatory Signs

These are almost always vertical rectangles, white background with black legend (can also be red or green), always have a border and a margin, detailed in Table 2. Try to use standard sign blank sizes when possible, to make the signs easier to build.

Table 2 | Regulatory Sign Border Dimensions

Sign Dimension	Border	Inset	Radius
<24"	3/8"	3/8"	1-1/4"
24" to 30"	5/8"	3/8"	1-1/2"
30" Square	3/4"	1/2"	1-7/8"
30" to 48"	7/8"	5/8"	2-1/4"
≥48"	1-1/4"	3/4"	3"

Always use a legend size consistent with the speed of the highway. Refer to examples of regulatory signs in the Standard Highway Signs as a guide. Where practical, it is best to use at least a D font or wider for legend on regulatory signs.

Regulatory and warning sign sizes for Expressways & Freeways are larger than conventional highways. The Standard Highway Signs book shows layouts for the larger signs and if you need to create a new one you can refer to it for examples. It is always better to put up a sign that is too big compared to one that is too small.

Warning Signs

For warning signs, use the same border, margin, and radius sizes as for regulatory signs.

Permanent warning signs should always be yellow with black legend except for school related signs which must be Fluorescent Yellow-Green (see below). Use the standard blank sizes if possible.

Always use a legend size consistent with the speed of the highway. Refer to examples of warning signs in the Standard Highway Signs as a guide. Where practical, it is best to use at least a D font or wider for legends on warning signs. It is always better to put up a sign that is too big compared to one that is too small.

Minimum sign size for warning signs on the State Highway System is 36".

Lane Drops (EXIT ONLY)

For lane drop situations (EXIT ONLY), often a yellow overlay is placed on an overhead guide sign. The yellow overlay is typically a horizontal rectangle instead of a diamond. Other situations may also require a horizontal rectangle instead of a diamond.

Fluorescent Yellow-Green

ODOT policy is to reserve the use of fluorescent yellow-green sign sheeting for school zone signing on state highways including the "SCHOOL" portion of the School Speed Limit (S5-1) sign and any supplemental plaques used in association with these warning signs. Pedestrian and/or Bicycle warning signs should use the standard yellow color. Fluorescent yellow sign sheeting may be used for pedestrian and/or bicycle crossing signs if there is a need to call extra attention to a particular crossing.

The Region Traffic Engineer may allow the use of fluorescent yellow-green for pedestrian/bicycle warning signs on a state highway if the requesting jurisdiction can demonstrate an existing systematic approach to pedestrian signing which includes the fluorescent yellow-green sign background. However, other treatments must be considered before choosing fluorescent yellow-green sign sheeting (e.g. curb extensions, pedestrian refuge islands, Rapid Flash Beacons, etc.). The mixing of standard yellow and fluorescent yellow-green backgrounds for pedestrian/bicycle signs within a selected site area should be avoided.

Designing Guide Signs

Legend Sizes and Spacing

Lower-case letters following an initial upper-case letter are the standard primary legend style (destinations) to be used on guide signs. Other secondary legend (directional, guiding) is to consist entirely of upper-case letters. Legend sizes are typically referred to by the upper-case letter size. The lower-case value will always be 75% of the upper-case value. For example, 8" legend refers to 8" upper-case along with 6" lower-case, where needed.

The MUTCD allows the use of 4" legend for principal legend on guide signs where the posted speed of the highway is 25 MPH or less (MUTCD, Section 2D.06). On the State Highway System, the smallest legend for principal legend on guide signs is usually 5". The exceptions to this are Adopt-A-Hwy signs and riders, Historic Trail Riders, and other riders where the main message is a symbol sign (such as recreational symbol).

The use of 6" legend is required for principal legend on guide signs where the posted speed of the highway is over 25 MPH. The majority of guide signs on conventional highways use a 6-inch C legend. The use of D or wider fonts is a judgment call for the designer. Wider fonts make the signs easier to read but it also makes the sign wider. When a sign width exceeds the maximum permitted for a single post, wider fonts are sometimes used to increase the size of the guide sign to the minimum required for multiple posts.

The MUTCD recommends the use of 8" legend where the highway is a multi-lane, high-speed facility (MUTCD, Section 2D.43). Larger legend is also warranted for overhead sign locations such as signs mounted on a signal pole, signs viewed from a long distance, or critical signs.

The use of 10"C, 8"-6"EM, or larger can also be used on the multi-lane, high-speed highways. You should always make sure that the size of legend is consistent with the speeds and lane widths on the highway. It is always better to put up a sign that is too big compared to one that is too small.

The MUTCD recommends the use of 12" legend for overhead street name signs (Section 2D.43).

Due to the higher speeds and volumes associated with Expressways & Freeways, the legend on guide signs are larger than on conventional highways. The MUTCD has tables (Tables 2E-2 through 2E-5) outlining the minimum legend size used on these facilities. The tables apply to any highway (or portion of a highway) built to Expressway or Freeway standards.

When using Tables 2E-2 through 2E-5, determine the interchange classification (from MUTCD Section 2E.32) for the design. In most cases, it will be Major, Category B or an Intermediate. The numbers listed in the tables are for an EM font since that is the standard for guide signs on Expressway & Freeways (MUTCD, Section 2E.14).

The tables are broken up into sections so each part of the sign has a specified letter or numeral height, or specific dimensions. Use the correct column for the sign you are designing. The principal legend size of Category A and B signs under the Major category call for 20”-15” legend for ground mounted signs. The principal legend for Overhead signs is 16”-12” legend.

When designing guide signs, the width of the sign is determined by the legend plus the outside (lateral) spacing that normally includes the border. Outside spacing is required on any sign to make them more readable. The ideal lateral clearance is usually one letter height from the side of the sign to the end of the legend, but may be as little as one half the letter height (ODOT Standard Drawings TM223 and TM224). The average of the upper and lower case letters should be used for the vertical clearance from the legend to the top (or bottom) of the sign. The spacing between lines of legend (vertically) ideally would be about ¾ of the legend height. It usually varies between ½ and 1 letter height.

Typical layouts for guide signs can be seen on Oregon Standard Drawings TM223 and TM224, the Standard Highway Signs book, and in the Sign Policy and Guidelines.

Spacing between letters of the legend is a function of the font. Individual spacing also depend on what letters are being used. This information can be found in the Standard Alphabets for Highway Signs published by the FHWA. Most software packages have this information built into the program so you won’t need to concern yourself with figuring these distances unless you are doing the design by hand.

Spacing between words of the legend is a called out in the ODOT Specifications to be based on the font size (ODOT Specifications Section 00940.45), summarized in Table 3.

Table 3 | Word Spacing – Legends

Series Font	Word Spacing
“B”	0.531H
“C”	0.625H
“D”	0.836H
“E”	1.000H
“EM”	1.500H

Note: H = height of upper case letter.

Arrow Sizes and Design

Arrow types are discussed in Section 2D.08 of the MUTCD. The Type A arrow (tapered, long shaft) is used most commonly for exit direction guide signs, exit gore signs and some “Exit Only” signs. These arrows are typically pointing upward and to the right, usually at a 45 degree angle. The Type B arrow (tapered, short shaft) is not as commonly used, but has some application for overhead directional guide signs where sign space is limited and use of the Type A arrow may not be appropriate. The Down Arrow is used only for overhead application. It is commonly used for Pull Thru signing and for some “Exit Only” signs. Type D arrows (straight shaft, extendable) are used for directional guide signs on conventional highways and at freeway/expressway ramp terminals.

The size of Type D arrows on guide signs is set up to match the upper-case letter height for the primary sign legend (destination), shown in Table 4.

Table 4 | Type “D” Arrow Sizes

Upper-Case Legend Height	Arrow Size
4”	4”x6”
5”	5”x7”
6”	6”x9”
8”	8”x12”
10”	10”x16”

These arrows are shown on Oregon Standard Drawing TM233, along with the arrow styles (Types “A”, “B” and “Down”) used for larger legends.

The Type “D” arrows have a straight (non-tapered) shaft. Therefore, their length can be increased to “balance” the sign. Sometimes when you have the sign designed, the arrow will look too small. If the arrow is placed horizontally at the bottom of the sign, increase the arrow length to ½ the width of the sign to make it easier to read.

If you are using a single arrow at the side of a two line legend, you might want to make the arrow longer or increase the arrow to the next legend size to improve the readability of the sign.

Hook arrows (we tend to use a straight shaft version similar to Type D, instead of the Type C arrow shown in MUTCD) are used for advance sign placement where you want the driver to turn at the next intersection instead of the place where the sign is installed.

There is a hierarchy in the placement of arrows as they appear on a destination sign (Section 2D.37 MUTCD). Destinations that are straight ahead are listed at the top the top of the sign with the “up” arrow. Below that would be any destinations to the left with the arrow pointing left, followed by any destinations to the right with the arrow pointing right. All destinations in a given direction shall have one directional arrow.

Design Layout

Separate destinations with a horizontal divider line all the way across the sign, to show groups of destinations in a particular direction. Shorter horizontal lines on the guide sign face can be used to highlight a section of the legend, or separate lines of legend if needed for clarity.

The number of destinations on a guide sign should be based on the driver's ability to read the entire message and still safely concentrate on the task of driving. Large amounts of legend should be reserved for locations where the driver is stopped while reading the sign. If you have a lot of information for the driver, consider making two signs with less legend and spacing them apart so the driver has ample time to react to each one.

Advance guide signs on conventional highways are preferable, but not always possible due to right of way constraints. When designing these signs, include a positive guidance message such as: "NEXT RIGHT", "LEFT ½ MILE", etc. This gives the driver more information that they can use to make better decisions.

Route shield assemblies are often required since the MUTCD requires their use where the highway has a route number. All State Highways now have a route number assigned to them but not all of them have been signed yet. For single installations, the assemblies are placed on a single support. When placing the route shield assemblies in conjunction with guide signs, either place them on the guide sign face or attach the assemblies underneath the guide sign. The standard size for a route shield is 24" when used by itself; you can use smaller shields when you place them on the guide sign. The 18" version is the smallest and should only be used when you are in an urban area using 6" legend on the guide sign. Use a 24" shield when you use 8" legend.

Freeway and Expressway Design

Legends on all overhead guide signs shall be ASTM Type IX retroreflective sheeting. All "EXIT ONLY" panels on overhead guide signs shall be ASTM Type IX and utilize Fluorescent Yellow retroreflective sheeting, with Black, non-reflective legend.

Guide signs for interchanges may have no more than two destinations on the Advance Guide signs and Exit Direction signs, and the destinations have to match on these signs. One supplemental sign with a maximum of two destinations is allowed per interchange.

Exit number panels are to be mounted flush with the right side of the guide sign for right exits. Exit number panels for left exits are mounted flush with the left side of the guide sign. Standard exit panel sizes for Oregon are different than the standards shown in MUTCD Table 2E-1. Our standards can be found in Oregon Standard Drawing TM225. The Oregon version of these signs is considerably narrower than the MUTCD version, yet it still satisfies MUTCD guidelines for margin spacing (Sec. 2E.15) on the sides. The ODOT version eliminates excess "green" space that would otherwise make these panels unnecessarily large. Exit numbers on Supplemental signs can have the exit number as part of the legend, or as an Exit number panel.

Border width for guide signs depends on the legend size, not the sign size. Signs having a legend in upper and lower case letters with 10 2/3" or smaller upper case letters and signs having a 12" or smaller all capital lettered legend shall have a 1" border. Signs having a legend in upper case smaller than 6" shall have a 1/2" border. All signs with a legend larger than specified above shall have a 2" border. The exceptions to this would be any standard sign included in the FHWA Standard Highway Signs book.

The corner radii of a sign should be 1/8 of the smaller sign dimension rounded to the nearest of the following numbers: 1.5, 3, 6, 9, and 12. A 12 inch radius should not be exceeded.

There are sample sign designs shown on Oregon Standard Drawing TM224. Exit Gore sign standards are shown on Oregon Standard Drawing TM225 and are consistent with the standards shown in MUTCD Table 2E-1.



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 3

Designing Supports

3 | Designing Supports

Choosing a Support Type

There are numerous types of sign supports available that the designer specifies for each sign on the project. This chapter describes the various sign supports that are used on ODOT projects. The designer should always contact the District Sign Supervisor/Coordinator when deciding which post material to specify for the smaller sign supports.

Sign supports used on the State Highway System must have breakaway features when used inside the clear zone and should have breakaway features when located outside the clear zone. Sign supports without breakaway features are required to be shielded from traffic (when inside the clear zone) with a concrete barrier, guard rail, or some other device to keep errant vehicles from hitting the support.

The standard sign supports shown in the Oregon Standard Drawings are all breakaway supports when properly installed to the details outlined in the standard drawings.

Wood Posts

This is by far the most commonly used support on the State Highway System. ODOT allows only pressure-treated wood posts. Post sizes are computed using the formula shown on Oregon Standard Drawing TM670.

Multiple wood post installations require a distance between the wood posts to maintain the breakaway design. For 4"x4" wood posts, this distance is 3'-6". Since this configuration is not often used, you will need to specify the clearance between the posts in the "Remarks" column of the Sign and Post Data Table (See Chapter 4 "Sign and Post Data Tables"). Multiple wood post installations usually utilize 4"x6" or larger posts. These require 7'-0" clearance between posts to be considered breakaway. If the sign installation is behind barrier, the clearance between posts can be decreased. All wood posts 4"x6" and larger require holes to be drilled in the post so they will break off at the proper location. This information is shown on Oregon Standard Drawing TM670.

Steel Supports

Bridge Rail Mounts

On occasion, a designer will need to install a small sign mounted from the railing on a bridge. Limit the size of these signs to 30 square feet or less. Bridge Rail Mounts are a bid item; you will need to supply the estimated pounds of structural steel in the Special Provisions (See Chapter 6, "Providing Quantities"). Design of these supports is done by a structural designer with information supplied by the sign designer.

Butterfly Sign Support

These supports are engineered to support large signs overhead, in a confined area. These often support Interchange Sequence Signs. Design of these supports is done by a structural designer with information supplied by the sign designer. These supports are not breakaway and require shielding from traffic. New butterfly support design requires the sign designer to contact the Region Mobility Liaison during the project scoping phase to determine vertical clearance requirements.

Cantilever Sign Support

These supports are engineered to hold large signs projecting out over a lane of the roadway. You can view a sample on Oregon Standard Drawing TM622. Designs for these supports are done by a structural designer with information supplied by the sign designer. These supports are not breakaway and require shielding from traffic. New cantilever support design requires the sign designer to contact the Region Mobility Liaison during the project scoping phase to determine vertical clearance requirements.

Exit Number Sign Mounts

These are S3x5.7 members (with 2" x 2" structural tubes attached as sign spacers) used to attach exit number signs on top of large guide signs. You can view the supports on Oregon Standard Drawing TM220. Sometimes these supports can be used to hang auxiliary sign under the main guide signs as shown on TM220.

Multipost Breakaway Supports

These are steel supports for larger signs usually located on expressways or freeways. You can view the supports on Oregon Standard Drawing TM600 and TM601.

Sign Bridge

These are engineered supports for supporting large signs over traffic lanes. You can view this support on Oregon Standard Drawing TM614. Design of these supports is done by a structural designer with the information supplied by the sign designer. These supports are not breakaway and require shielding from traffic. New sign bridge design requires the sign designer to contact the Region Mobility Liaison during the scoping phase to determine vertical clearance requirements.

Signal Pole Mounts

This support is for mounting small to medium sized signs on signal, luminaire, or similar poles. You can view this support on Oregon Standard Drawing TM680. It can be used for signs up to 60 square feet. These supports attach to a signal pole, luminaire pole, or other steel pole that can support the increased load. The sign designer needs to coordinate their design for a signal pole mount with the signal designer.

Most signal pole mounts have an "H" frame for mounting the major guide sign. Most of these guide signs are extruded panel signs attached using the post clips shown on Oregon Standard Drawing TM675.

If you need to support a sign larger than 60 square feet you will need to use another type of support.

Guide signs mounted on traffic signal poles shall be shown and detailed on the Signing Plans, but only referenced on the Signal Plans. Since the signs are shown in the Signing Plans, they need to be covered under the bid item for the specific sign type. These signs shall not be paid for as part of the lump sum for signal installation bid item.

Note of caution: A lot of decorative poles will not support the added wind load of this support.

Structure Mounts

These are engineered steel brackets that are bolted to the sides of bridges to hold extruded aluminum signs. Design of these supports is done by a structural designer with information supplied by the sign designer. New structure mount design that alters the vertical clearance requires the sign designer to contact the Region Mobility Liaison during the project scoping phase to determine vertical clearance requirements.

Triangular Base Breakaway

This is an FHWA approved design for mounting signs up to 15' in width. The support is multi-directional, meaning that it can be hit from any direction and still performs as a breakaway support. Larger signs use an H-frame to help stabilize the sign. The design for a triangular base breakaway support is on Oregon Standard Drawing TM602.

Other Supports

Adjustable Sign Mounts

This is a bracket bolted or strapped to a signal pole, mast arm, luminaire pole, or similar support to hold up a sign. You can view the support on Oregon Standard Drawing TM465. There are similar sign supports of this type not shown on the drawing but are available from signal supply companies. This support is also called Adjustable Sign Bracket or Adjustable Sign Clamp.

Crosswalk Closure Barricade

These supports serve two purposes, they act as a shield to block the crosswalk and also provide a sign support for the required signing. You can view this support on Oregon Standard Drawing TM490.

Milepost Marker Posts

These are supports for mile markers, delineators, and object markers. The design for a milepost marker post is on Oregon Standard Drawing TM222.

Pipe Sign Support

These are the round steel pipes frequently seen in urban areas. These posts are not used on the State Highway Right of Way since they are not an approved breakaway post. There is an example of a pipe sign support on Oregon Standard Detail DET4235.

Route Marker Frame

This is actually a frame bolted to a sign support with other signs bolted to the frame. It is very useful for installing multiple route shield assemblies and can be used for other sign assemblies as well. The design for a route marker frame is on Oregon Standard Drawing TM678.

Secondary Sign Supports

These are supports for signs that are attached to larger extruded aluminum signs. You will need them to attach additional signs to the main guide signs. You can view the supports on Oregon Standard Drawing TM678.

On the Sign and Post Data Table, there are columns for Secondary Sign Supports that are used to specify how the secondary signs are attached below the main guide sign. Refer to Oregon Standard Drawing TM678 for the Secondary Supports and to Oregon Standard Drawings TM200 and TM678 for installation details.

Special Pipe Sign Support

This is a commercially available round steel support with a triangular slip base. It can be viewed on Oregon Standard Detail DET4237. This support is not used on the State Highway System.

Stainless Steel Clamps

These are clamps that support small signs mounted on signal, luminaire, and similar poles. You can view this support on Oregon Standard Drawing TM677.

Perforated Steel Square Tube (PSST) Sign Supports

These supports are sometimes known by their commercial name “Telespar posts” that is just one of the manufacturers listed on the QPL for these types of posts. You can view these types of posts on Oregon Standard Drawings TM681, TM687, & TM688.


Mast Arm Street Name Sign Mounts

These supports consist of a group of extruded beams which are riveted to the back side of a sheet aluminum sign substrate. Each beam, in turn, is mounted to the signal mast arm by use of a strap and buckle. These supports are shown in greater detail on Oregon Standard Drawing TM679.

(This page intentionally left blank.)

LEGEND

-  Install new sign (N)
 -  Install new sign (N) on new (M) sign support
 -  Maintain and protect existing sign (N) and support
 -  Remove and save existing sign (N)
 -  Remove and save existing sign (N) and remove (M) sign support
 -  Remove and save existing sign (N) and (M) sign support
 -  Reinstall existing sign (N)
 -  Reinstall existing sign (N) on new (M) sign support
 -  Reinstall existing sign (N) and (M) sign support
 -  Remove existing sign (N) and (M) sign support
 -  Remove existing sign (N)
 -  Work to be performed by others
 -  Modify existing sign (N) as shown on plans
- N = Sign Number
 M = Material
- Material options:
- W = Wood Post
 - S = Steel Breakaway Support (TBB or MPB)
 - P = Round Pipe Support
 - PC = Galvanized Pole Clamp
 - SM = Structure Mount
 - SP = Signal Pole Mount
 - C = Cantilever
 - SB = Sign Bridge
 - MP = Milepost Marker Post
 - SSC = Stainless Steel Clamp
 - BR = Bridge Rail Mount
 - ST = Perforated Steel Square Tube
 - MA = Mast Arm Street Name Sign



NOTE:
 The locations of sign installations shown are approx. with exact locations to be determined in the field.

NOTE:
 Signs not shown are to be installed unless otherwise indicated by the engineer.

ODOT Traffic Sign Design Manual

3rd Edition

Chapter 4 Drafting Standards

4 | Drafting Standards

General

CADD Files

You will not be able to start putting together your signing plans without first obtaining the necessary electronic data from the Roadway Designer. These CADD files that you will need include existing features files, alignment files, new construction files, right-of-way files, etc. Once you have gathered all of these, you should have what you need to begin your own design files. Compromise

Design Format

The vast majority of design work produced for ODOT contracts is done in 11" x 17" format using surveyed alignments. On some preservation jobs of minor complexity an 8½" x 11" format may be selected by the roadway designer. When this happens, the signing plans will need to be developed for that same format. This manual focuses on the production of plans in 11" x 17" format.

In some cases, a surveyed alignment either does not exist for a particular project or may not be available to the sign designer for producing their plans. When this is the case, the designer should create their own "alignment" using straight-line format. The designer drafts straight segments of roadway, with an assumed center-line, to serve as the alignment for the sign plans. The designer then adds center-line stationing or mile point references consistent with those used by the roadway designer.

The designer should always contact the roadway designer or Project Leader before starting design work to coordinate the proper format. It is difficult to change formats later on when the design is mostly finished.

Consolidation of Base File

The first step is to create a "base" file to set up your plan sheets. This file should be set up to include all of the features necessary to show on your plan sheets and leave out the unnecessary ones. Begin by merging all of the necessary files (existing features file, right-of-way file, alignments, new roadway file, striping design file) together into a single two-dimensional file. This newly created base file will later be used as a reference to your design file.

As you progress through your design, keep in mind that the Roadway Designer is also progressing through their design. Along the way, there will often be changes made to alignments or other geometric features. Because of this, it is advisable to update your base file, as needed, by referencing in the most current files for alignments and new construction. An open line of communication with the Roadway Designer will be your best tool for determining when to do this. They can let you know when they are making changes that will significantly affect your base file. Anytime your plans are printed and distributed for review they should show alignments and other features consistent with the Roadway plans. This can only be accomplished by keeping an up-to-date base file.

For some projects, minor in scope and complexity, there either will be no Roadway plans or they may only consist of typical sections. In this case, you will not have the usual information available to you necessary to create a base file for your design. There are two other options available to you. The first involves “borrowing” alignment from as-builts of previous projects at that location. The second involves using the straight-line format described in the previous section on “Design Format”.

File Clean-Up

After creating the base file, the sign designer’s next goal is to clean out extraneous information. This is accomplished through a combination of turning off levels and deleting unwanted elements. There is some information that you won’t want in your plans but will still want to keep as a resource, such as utilities, easements, curve data and existing signing data. Take care not to delete these items, because you will need to refer back to them on occasion. The items that you will want to show on your plans include:

- center-line,
- stationing and station marks,
- lane lines,
- edge of pavement,
- curbs,
- sidewalks,
- barriers,
- bridges,
- street names,
- North arrows, etc.

Also include lane-use control arrows at intersections to show allowed turning movements. It will prove useful to incorporate actual striping features into your plans; if possible, since the lane lines and markings in the roadway design files won’t always match those shown in the actual striping plans.

Items such as landscape features, buildings, and drainage features will clutter up your plans and should not be shown for this reason. In some cases, a lane line may conflict with the center line. In this case, the lane line should be deleted so that the center line stands out more clearly.

Once extraneous information is removed, some line codes and weights may need changing for consistency with ODOT drafting standards. For instance, the center-line in the roadway file is usually a heavy solid line. ODOT drafting standards require a line weight of zero with a line style of seven. The stationing tick marks also have a line weight of zero, but would remain a solid line style. One other possible change involves the line style used for new curbs and barriers. Often these are shown with a dashed line style in the roadway files, but ODOT standards call for them to be solid.

Do not show existing striping and other pavement markings on your plan sheets unless they are being maintained as is. Do not show both the new and the existing edge of pavement lines on your plans when they are in nearly the same location, as is the case in a project with only minor widening. In this case reduce the clutter by not showing the old edge of pavement. In cases where the new and the old edge of pavement differ considerably, as in projects with significant realignment, show both. This can be helpful in eliminating confusion as to why existing signs sometimes are shown in the middle of the new alignment or far beyond the new edge of pavement.

You will also need to replace all of the symbols for existing signs with the sign symbols that are included in the ODOT pull-down menu. This is necessary because the sign symbols from the original existing features file used to create your base file are very small and hard to see. The symbols in the pull-down menu are built to a scale such that they will stand out much better on your plan sheets and it will be much easier to show orientation of sign faces with these symbols.

Creating and Naming a Design File

Once you are comfortable with the way your base file looks, it is time to start building your design file. Your design will be put together in a separate file with your base file referenced to it as needed to develop your plan sheets. Begin by opening a new two-dimensional design file in MicroStation. The naming convention for signing files uses the five digit key number followed by the letters “tr” for traffic and the suffix “.sn1”. As an example, for a project with the key number 05925, the sign design file would be named 05925tr.sn1. If you have need for more than a single design file, then the suffix would increase with each additional file (.sn2, .sn3, etc.).

This file will contain all of the design notes and bubbles, borders, title block, and any of the text needed for the contract plan sheets.

Sheet Borders

Once you have created and named your design file, open it up. Set up all of your plan sheets in this file and reference pieces of your base file to individual plan sheets to cover the entire length of the project. Consultants may have a different method to set up sheet borders and plot sheets than ODOT uses. Although the approach may be different, the goal is still the same. You want your file set up in a manner that has organized rows or columns of identical sheet borders placed and identified in such a manner as to allow for quick and easy prints. ODOT uses a tool called Print Organizer, within the MicroStation V8i environment, that allows for customization of how your sheets are organized and printed, both on paper and digital. By creating “print set” definitions, a collection of any or all sheets in a design file can be identified for printing (paper or digital) in a selected order, without requiring individual fencing of sheets. For this manual, we will focus on setting up a design file by using Print Organizer.

Begin by placing sheet borders for 11” x 17” sheets at a 1200 scale (1” = 100’) in your file. The number of borders you place doesn’t matter so much at this point, because you can add more or delete some later, as needed. You will eventually need enough borders to take care of all Signing Plan sheets, Sign Detail sheets, and Sign and Post Data Tables.

There are a number of features common to all sheets in your design file. Once you have created your sheet borders, place these common features inside of your first sheet border. Copy these features to all sheet borders, so that you don’t have to create them anew for each sheet. Among the features common to all or most sheets are: title block (with professional stamp), sheet header, LEGEND notes and general notes (plan sheets only), and PRELIMINARY (or ADVANCE) COPY “stamp”. These items can be found among the “General” or “Signing” workflows that are a part of the overall “Traffic” workflow. For consultants, the ODOT workspace will include templates for these under the task tab. Consultants can download the ODOT workspace here:

<http://www.oregon.gov/ODOT/EAST/Pages/ODOT-Workspace.aspx>

Whatever LEGEND or general notes are used can usually fit in the area directly above the title block and below the sheet header. After placing this information inside of the first sheet border it can be fenced and copied inside of all other sheet borders. The title block will be the same on all sheets. Sheet headers and general notes will be used on all plan sheets and details sheets although the contents will differ somewhat for each of the two types. Sign and Post Data Table sheets all have the same spreadsheet type of layout to them. This also is a standard cell which can be accessed from within the “Signing” workflow. The cell can be placed inside of each sheet border that will serve as a data table. ODOT has also provided blank data table sheets for consultant use within the same file mentioned above.

Plan Sheets

After customizing your sheet borders and copying from sheet to sheet all of the common information, you are now ready to begin laying out your plan sheets. There's more than one way to accomplish this task, but this manual will focus on one specific method, which involves referencing portions of the base file into individual plan sheet borders in the design file.

All of the existing traffic signs should be included on the signing plan sheets. This includes signs to be maintained and protected, signs to be removed, and signs to be replaced. When all of the signs are included on the plan sheets, the plans can be reviewed with a clear picture of all the signs located within the project limits. This will also be beneficial when the plans are filed as "as-built" records for that section of highway.




Figure 18 | Sample Plan Sheet




Figure 19 | Sample Plan Sheet




Figure 20 | Sample Plan Sheet




Figure 21 | Sample Plan Sheet

Clip Boundary and Referencing of Files

On most 11" x 17" plan sheets your usable design space will be an area of about 10" x 10". Within this space you should be able to comfortably fit two different stretches of highway alignment of lengths anywhere from 800 to 1000 feet. Begin by creating a box (rectangle) of approximately 4" tall by 9" (400' x 900') wide. Create it on a level which does not need to be turned on for your final prints. The boxes can be made with construction lines and turned off for printing. Place this box over adjoining pieces of alignment in your base file, from beginning to end of the project, such that the entire alignment is covered with minimal overlap. Each box should be rotated, if necessary, such that its length runs more or less parallel with the center line of the alignment.

If you have an interchange or a cross road which has a considerable amount of work on it, you may need to limit that particular sheet to only one section of alignment, instead of the two. If this is the case, you may want to use a 9" x 9" (900' x 900') box to mark that particular section of alignment. Once you have these boxes placed end-to-end covering the entire alignment, you may want to reposition them as needed to insure that all important features, including station numbers are encompassed within them. Also make sure that within each box there is a North arrow to define orientation of the alignment. Make sure that text for highway names and any crossroads are present within each box.

Once you've arrived at this point, the idea is to individually fence around each box and copy their contents as references to the sheet borders within the design file. The fence contents may need rotating on the page as they are referenced to make the boxes run horizontal. Some sheets will have room for two boxes, one above the other. Other sheets will only have room for a single box if it is the 9" x 9" (900' x 900') variety. The sheets need to be filled systematically, so that the overall alignment stationing increases left to right and top to bottom from first sheet to last as if reading a book.

To begin the referencing, put a fence tight around the outside of the first box at the beginning of the project alignment. Now attach this as a reference to your design file inside of the sheet border for the first plan sheet. One way is to name the reference according to the sheet number and whether it takes up the top or bottom portion of the sheet. Remember, most sheets will have two separate portions referenced to them, one on the top and the other on the bottom. Make sure that you have specified "clip boundary" and that your fence setting is on "clip" when you "move" the referenced material into its position within the design sheet border. Rotate this referenced material, as needed, so that the alignment is horizontal on your plan sheet and make note of the degree of rotation used.

Repeat this procedure for each of the remaining boxes in order of increasing stationing until you have filled in each of the plan sheets with the necessary alignments. If referenced properly, the boxes themselves will also show up on the plan sheets. The unique level which these boxes should have been created on can be turned off before making any prints so that they will not show up on your actual printed plan sheets.

As mentioned earlier, for some projects an actual surveyed alignment is not available to the sign designer, and a straight-line format is necessary. In this case, instead of referencing pieces of alignment from a base file into the design file, the designer creates horizontal pieces of alignment directly onto each plan sheet and drafts a center-line using milepoints or stationing to match that which is shown on the sign inventory they were provided. No particular scale is necessary, but it should use as few sheets as possible without making the sign symbols so crowded together that the information is difficult to read. If there are long sections of highway with no signs present, the designer may consider leaving these sections out.

Mapping Existing Signs

After referencing the base sheet alignment to the plan sheets, begin plotting the existing sign locations onto each sheet. Most or all of the existing sign locations should appear on your alignment from the original existing features file. The original sign symbols should all be replaced with the symbols from the pull-down menu. Next, compare the locations listed in the sign inventory with the locations shown on the plan sheets. You may find that some of the locations in the inventory are missing from the plan sheets or vice-versa. You may also find that some of the symbols are not shown in the exact location as listed in the inventory or that some of the symbols are not oriented with the signs facing the same direction shown in the inventory. If you run into conflicts such as these, it is best to resolve them by looking at the digital video log or by making a trip on-site for projects. Add or move any sign symbols as needed according to what you are able to determine is the most accurate representation of what signing is currently in particular locations.

At this point, you might make paper prints of all the plan sheets and begin making note (in ink) of what each existing installation consists of. Another alternative is to place the cell symbols for the signs within your plan sheets on a construction level. Draw a line from each sign face to a blank area on the page where you can sketch a rough version of what that particular sign(s) looks like or use a brief word message like “speed 35”-whichever is easiest for you. Do this for all the signs in the project. You will want to differentiate existing signing from proposed new signing. When you later begin marking in locations for proposed new signing, you will want to use pencil, because you may make numerous changes before settling on a particular plan. This is the reason for using ink to designate the existing signing.

You should not need to make any written indications about the types of supports. There are different symbols available in the ODOT pull-down menu, and from other sources, for each of the different types of commonly used supports: wood posts, steel posts, pipe installations, signal pole mounts, cantilevers, etc. Use the representative symbol for the appropriate type of support used. Also, use symbols which accurately depict the number of posts present in the installation, as well as showing sign faces on all sides of the support where present. Whether it is an existing installation which might be removed and discarded or new signing and supports to be installed, it is important to provide an accurate picture of what is currently out there and what is desired, to eliminate any confusion later on when the plans are read by a contractor or inspector.

Use of Legend Notes

Once you've completed a rough layout of all signing, existing and proposed, on your plan sheets, indicate the action to be taken for each installation shown. In the ODOT pull-down menu is a complete set of all commonly used LEGEND (bubble) notes. These notes are in the form of hexagons, with enclosed letters and numbers, used to indicate action(s) to be taken with regards to each sign and/or support. Within each bubble, the number (N) represents the sign number in question. The letter (M) in the bottom half of the bubble represents the type of support: wood, steel, cantilever, pole-clamp, etc. The other letters in the bubble (RX, EX RS, RI, etc.) represent the action(s) to be taken to the sign and/or support. Each plan sheet should include a list of the LEGEND notes used on that particular sheet. At the bottom of the list are definitions for each coded message and for the various possible support types. The most common possibilities are included in the ODOT pull-down menu.

Sign installations may have signs facing only in one direction or facing in two or more different directions. In using bubble notes, use a separate string of notes for each sign face. Begin by drafting a leader line outward from one of the sign faces. At the end of this leader line, place the string of bubble notes needed to sufficiently describe the work to be performed for each sign on that face. The bubbles should be in order, moving outward, so that they are representative of how the work would actually be accomplished. Begin with bubbles that show existing signs being removed followed by bubbles that show new signs being installed. Repeat this process for each sign face in the entire installation. Although an installation may have signs facing in multiple directions, there is only one common support for that installation. Once the removal and/or replacement of the support has been detailed with one of the bubble strings, there is no need to repeat it on any of the other strings for that installation.

Sign Details

In order to adequately explain the signing work to be accomplished on a project, you need to provide the contractor with a detailed description of the signs, both existing and new. This task is partially accomplished by developing Sign Detail sheets that include the likeness of each sign. Not only is this necessary for performing the work under contract, but these sheets will prove beneficial later on as a set of as-built records for that area.

Format of Detail Sheets

There is an example of a Sign Detail sheet at the end of this Section that you can refer to for the layout of this sheet. Start the sign drawing at the upper left corner and then proceed down the sheet in rows until the sheet is full. The signs within any particular row are left-justified with respect to each other, and the sign numbers are centered below each respective sign. Allow an adequate amount of space between signs within each column and between each of the columns so that the sheets do not appear cluttered and are easy to read. Sign numbering is obtained by going back to your penciled-in plan sheet.

One way to number your project is to start with the first sign at the beginning of the alignment on your first plan sheet and call it number one. The corresponding design should be placed in the upper left corner of the Sign Detail sheet and labeled Sign No. 1. Working ahead on line, the next sign would be numbered 2 and so forth. All the signs on the Sign Detail sheet are numbered in this fashion.

This is the easiest way to number your project, but it doesn't always produce the best-looking Sign Detail sheets. You will end up with some small signs mixed in with some very large signs, and will not make very efficient use of the space on your sheets.

Another way to number your sheets and make better, more efficient use of the space on your Sign Detail sheets is to begin at the start of the alignment and proceed ahead on line numbering the smaller regulatory, warning and other standard signs first. Once these signs have been covered for the entire project, repeat the process for the smaller guide signs and other small signs requiring custom designs. Last of all, repeat the process for the larger guide signs and other large signs requiring custom designs. By using this second method, the signs on your Sign Detail sheets line up more uniformly and use the space more efficiently. This method places signs requiring custom designs at the end of the Sign Detail sheets.

Signs that supplement each other should share the same sign number. Examples include a warning sign with an accompanying speed or distance rider, a guide sign with secondary route assemblies or recreational symbols mounted below it, or a guide sign with an exit number sign mounted above it. In each of these cases, the entire collection of signs would be shown together in one location on the Sign Detail sheet and given a single sign number. To differentiate between the primary sign and the supplemental signs, each of the supplemental signs would be further designated by a specific suffix. So, if the entire collection was known as sign number 1, then the supplemental signs accompanying the primary sign would be labeled as 1a, 1b, 1c, etc. In this manner, the entire collection of signs that supplement each other on that particular sign face can be referred to as sign number 1 in the bubble notes on the plan sheet. At the same time, each individual sign in that collection has its own unique designation that can be referred to later on in the Sign and Post Data Tables, when more specific details are required.

Once a particular sign has been located and numbered on the Sign Detail sheets do not show it again. For example, if sign number 1 is a STOP sign, then refer to every other STOP sign on the project as sign number 1. Any signs that will be removed altogether, or otherwise not replaced with new signs, will be drafted with dashed (broken) borders on the Sign Detail sheets. Draft others that will require new signs with solid borders.

SIGN DETAILS

NOTE:
Signs shown with broken borders are existing signs.

OREGON DEPARTMENT OF TRANSPORTATION TRAFFIC - HIGHWAY SECTION	
REGION AND OR CONSULTANT LOGO	
PROJECT NAME FROM TITLE SHEET NAME OF HIGHWAY NAME OF COUNTY	
DESIGNED BY: Name DRAWN BY: Name EC: 210 MP: 10.21.1.59	
PERMANENT SIGNING	
REGISTERED PROFESSIONAL ENGINEER OREGON XGI X XXXXX MARCH X, XXXX X Expires June	
I.S. No. _____ I.S.C. No. S-XXXX	

1:1200 - 5

THIS IS THE FILENAME LOCATION ***** DD-MMM-YYYY HHMM USERNAME

Figure 22 | Sample Detail Sheet




Figure 23 | Sample Detail Sheet

THIS IS THE FILENAME LOCATION ***** DD-MMM-YYYY HHMM USERNAME 1:1200 - 6




Figure 24 | Sample Detail Sheet

Regulatory and Warning Signs

When building your Sign Details sheets, you will find that most of the more common regulatory and warning signs are already depicted in cell libraries or cache files, for your convenience. The GuidSIGN Sign Design program, used for designing custom signs, also contains a library of cells for the most common regulatory and warning signs shown in the MUTCD. It also includes many styles of route shields and a number of standard recreational and motorist services symbols. Any of these cells which apply to your particular project can be copied to your Sign Detail sheets. You'll want to take advantage of this and other cell libraries that you have access to so that you don't have to spend a lot of time drafting these standard signs over and over again. A good source for these standard signs is a cache file on the ODOT web-site (See "Plan Sheets" section of this chapter for website). The file is referred to as "Standard Sign Details in MicroStation". This cache file contains a number of signs which do not appear in the MUTCD because they are unique to Oregon.

Regardless of what source you obtain your sign depictions from, it is important that they closely resemble the actual signs needed on your project, so that there is no question on the part of the contractor as to what signs they need to install. These depictions should be drafted at a scale large enough to be easily recognized, but small enough that you can get a reasonable number of them on a sheet. With these smaller standard signs, you could show 25 to 40 signs on a single sheet. They should also be scaled with respect to each other such that signs which are the same size actually appear the same size on the sheet. If one sign is twice the size of another, draft it such that it is twice the size on the sheet. If you cannot find an exact depiction of a particular standard sign, then you can usually find a sign which is very similar and modify its legend to make the sign that you need. Once you have done this, you may want to consider creating your own cell of this sign for future use.

Guide Signs

Most guide signs are unique to a particular location. There are standard layouts for signs such as exit gore signs and exit number signs, but even though the overall dimensions for these signs are set, the spacing of the legend will vary with the exit number. Because of this, a unique design layout should be worked up for each guide sign. Using your sign design software, produce likenesses of each guide sign for placement onto your Sign Detail sheets. Use the sign design software in a design file other than your project design file. That way, if the software malfunctions for some reason, it won't destroy any of the information being developed on your plan sheets. As each sign is designed it can be copied into the project design file using the clipboard feature. Copy the necessary dimensioning text along with each sign. Ideally, each guide sign should include dimensioning text showing the overall height to the left of the sign, overall width above the sign, and letter sizes and fonts as well as arrow and shield sizes to the right of the sign. Do not show any dimensions below the signs, if possible. Begin with the smaller guide signs such as street name signs and work your way up to the larger signs as you build your sheets. The signs will fit more uniformly on the sheets and you'll use the space more efficiently by doing this. Refer back to Chapter 2 "Designing Guide Signs" for information on the actual design of the sign.

As you copy the signs onto your Sign Detail sheets, be sure to scale them appropriately so that they are proportionately sized with respect to the regulatory and warning signs that you have already placed on the Sign Detail sheets. Place the text for the sign dimensions such that its size is consistent from sign to sign. Use a text size that is easy to read, but otherwise does not take up a lot of room or interfere with the actual depiction of the sign.

Show all signs on a particular face that are installed together as a single sign number. Use suffixes for each sign other than the primary sign within each sign number. As an example, if you have a primary guide sign that contains two route shields, has an exit number sign mounted above it, and has an “exit only” panel at the bottom of it, you would refer to the entire collection as sign number 1. The exit number sign might be referred to as 1a, the “exit only” panel as 1b, and the route shields as 1c and 1d. By doing this you can refer to the entire installation as sign number 1 on the plan sheet(s), but still be able to identify each sign separately when more detail is required in the Sign and Post Data Tables, which we will discuss later in this chapter.

In most cases a guide sign will be one of three colors: green, blue or brown. The color depends on the type of destination(s) that you are directing people to. There will be some cases where a guide sign will need to be partly green and partly brown or blue. In other cases, a guide sign will include a yellow “EXIT ONLY” message at the bottom. For either of these scenarios, it is best to label with the suffixes “a” and “b” to differentiate between the two colors on the same sign. Later, in the Sign and Post Data Table you will need to give more specific details as to the type of sheeting and the dimensions involved for each color, so the use of these suffixes will allow you to detail each of the two colored portions separately.

Sign Design Software

There are several programs available to design and draft the signs not available in the signing cell library. ODOT uses “GuidSIGN” sold by Transoft Solutions, 604-244-8387, Fax 604-244-1770. “SignCAD” is another very similar system that will design and draft the sign for you. It is sold by Sign Cad Systems, Inc., 952-544-9559, Fax 952-544-9561, or on the web at www.signcad.com. The advantage of using software to design the signs is the speed of the design plus the drafting is to scale so what you see on the design is an exact replica of what the finished sign will look like.

If using software to design signs for a project, you will need to print the design for each sign out individually for the shop drawings required with your sign plan. The sign designer will be asked to send these drawings to the Construction Project Manager’s office and they will provide them to the Contractor for the Project. The Sign Manufacturer uses the drawings to build the signs according to their design. Make sure that the sign numbers on the drawings match those shown on the Sign Details sheets. Also, make sure that the information on the drawings regarding sizes, sheeting types and colors, etc. matches the information entered into the Sign and Post Data Tables (see next section).

Sign and Post Data Tables

There is a completed form of a Sign and Post Data Table at the end of this section that you can refer for the layout of this sheet. We will go through this form column by column, explaining what type of data needs to be entered in each case. Some examples will be provided along the way, and the completed data table at the end of the chapter should also be examined while reading through the instructions for each column. You should read through this entire Chapter prior to filling out a Sign and Post Data Table for the first time.

Before beginning to fill in the data tables, tally up the number of each individual sign needed to complete the work shown in the plans. Count entries only where a new sign and/or support are to be installed or where an existing sign and/or support are to be removed, saved and reinstalled or somehow modified. Do not count signs and supports removed and not replaced or signs and supports maintained and protected in their existing location. Once you have your tally completed, you can begin filling in the first data table. You may want to leave a few empty lines after each sign number if you anticipate the need for additional signs in the future.

Sign Number & Sign Location

Start with sign no. 1 and make your entries in numerical order. If you have three installations tallied for sign no. 1, then you will fill in data in three different rows. In this case you would only need to enter the number “1” for the first row. It would be understood that the other following rows were also number 1 unless otherwise numbered. If your sign no. 1 has a secondary sign (1a) along with it, then you will be filling in data in six different rows. The entries in the sign number column would read “1, 1a, 1, 1a, 1, 1a” as you work your way down. Entries are only needed in the sign location column for the rows next to number 1 (not 1a), because the location of 1 and 1a would be the same in each case. For the sign location column, it is preferred that the entry consist of an alignment name, engineering station and a designation of “lt.” for left of center-line or “rt.” for right of center-line, when looking ahead on line. If the installation is in the median, then use the designation “ctr.” If engineering stationing is not available, as is the case in some preservation overlay projects, then enter mile points, to the nearest one-hundredth of a mile, into the sign location column. A directional suffix (EB, WB, NB, SB) should accompany them to indicate which side of the highway the installation is on.

After completing each of the rows for sign no. 1, skip a row and begin making entries for signs numbered 2, then 3 and so on until all numbers have been covered. It is best to leave a blank row after finishing the entries for a particular number. This provides a little separation and makes the data tables easier to read.

Sign Dimensions

These entries are simply the width and height for each sign. For all custom designed signs enter these values in terms of feet and inches as determined by the custom sign design software used in their design. For all standard signs (regulatory signs, warning signs, shields, arrow boards, rec. symbols, milepost markers, etc.) show the dimensions in inches only. Dimensions for most of the more common regulatory and warning signs are included in Appendix D. Dimensions for other standard signs can be found in FHWA's Standard Highway Signs, our Sign Policy and Guidelines, and our Standard Drawings (TM200 series). If you are detailing a sign which already exists in the field, then bracket each dimension with parenthesis to differentiate it from the new signs. It is not always necessary to show dimensions for existing signs, but it will prove useful if that existing sign needs a new support. Sign sizes are needed for the contractor or project inspector to be able to field verify sizes of new supports.

Sign Type

Sign Types were removed with the 2018 Oregon Standard Specifications for Construction.

Substrate

ODOT accepts only three types of substrate material for permanent signing on the state highway system: sheet aluminum, plywood and extruded aluminum panels. Place a checkmark in the appropriate column for each row to designate the desired substrate material for each specific sign. As a general rule-of-thumb, ODOT only uses extruded aluminum panels for signs that are too large to be made of plywood. This would be anything larger than what can be fabricated out of a 4' x 8' sheet of plywood. Some signs that would otherwise be small enough to go on plywood should instead use extruded aluminum panels if they have structural steel supports. These supports are designed for signs mounted to them with post clips instead of being thru-bolted.

Extruded aluminum panel signs are designed in 6-inch increments for overall height and width, whereas plywood and sheet aluminum signs are designed in 3-inch increments. Plywood can be used as a substrate for signs up to 4' x 8' in size. Sheet aluminum can be used for ground-mounted signs up to 4' x 5' in size, and is also used as an overlay material riveted to extruded aluminum panels (route shields and EXIT ONLY panels on large guide signs).

Because of its relatively light weight, sheet aluminum is also used for virtually all street name and lane use control signs mounted on signal pole mast arms. Plywood is sturdy and therefore is resistant to bending or warping around the support in high wind conditions or in snow-blowing operations. Because of this, plywood may make for a better substrate material than sheet aluminum for signs wider than 3 feet which would be the most susceptible to bending or warping in severe conditions.

Background Color

Abbreviations for each of the colors are listed in footnote number 1 at the bottom of each Sign and Post Data Table. The written descriptions for each sign type, as shown in our Special Provision for Section 02910, will specify whether the background sheeting is ASTM Type III/Type IV or ASTM Type IX. The color abbreviation is to be entered into whichever column is appropriate for that sign type.

Legend Color

There are three columns where information can be entered for the legend color. The legend color can either be listed under the “ASTM Type III or Type IV” column, the “ASTM Type IX” column, or the “Non-Reflective” column. You should choose only one of these columns for the sign legend and enter the appropriate legend color.

Whenever your legend color is black, enter the abbreviation “BK” into the “Non-Reflective” column. Black legend is always non-reflective. No other colors will be entered in the “Non-Reflective” column.

For all other legend colors, use the same abbreviations referred to previously in footnote number 1. Enter the abbreviation for your sign color into whichever column is appropriate (“ASTM Type III or Type IV” or “ASTM Type IX”). The written descriptions for each sign type from the specifications will help you decide which column is appropriate.

Legend Type

Enter a checkmark into one of the two columns. If your sign is to be made of plywood or sheet aluminum, then your legend type is direct applied and will always be considered “permanent”. If your sign is to be made of extruded aluminum panels, then your legend is riveted on and will always be considered “removable”.

Sign Number

This column is a repeat of the very first column. Copy the first column directly over to this column. It makes the table easier to read if you have the sign numbers repeated in this location near the center of the sheet. There is one additional feature that should be incorporated into this column, which does not appear in the first column. This feature is individual designation for each separate post on a steel multi-post breakaway installation. Provide extra rows to accommodate the total number of posts in your installation. This allows you to enter design details for each steel breakaway post in its own specific row. This is necessary because each post might have its own unique length and offset distance to specify.

As an example, for a steel multi-post installation (assume sign number 1) using three posts you would allow for three rows to detail each individual post. In the first column the first row would have the number “1” entered, but the next two rows would be left blank. The corresponding sign number column in the middle of the sheet would have the following entries: 1L, 1C, and 1R, respectively in those same three rows to represent the left, center and right posts. This will allow each of the three posts to be detailed individually as you work your way to the right of the page across other columns. The information specific to the sign would only need to be entered in the first row. There is no need to repeat it in the other two rows. It is not necessary to detail posts separately for multiple wood post installations. For those installations, the posts can all be detailed in a single row.

Type of Support

These 15-20 columns include all of the primary and secondary support types common to permanent signing on ODOT’s highway system. Enter a check mark in the appropriate column or columns for each sign. In most cases you will check no more than a single column for any given row. In a few cases you may need to check more than a single column. For example, a triangular base breakaway support may or may not have an “H” frame associated with it. If so, then you will need to insert a check in both of these columns. Many installations will have a primary support and some secondary supports, as well. In such cases, make sure that you enter your check marks for each column in the appropriate row corresponding to the actual sign it supports.

As an example, a primary guide sign (number 1) may have two steel multi-post breakaway supports (1L, 1R), and it may have a secondary exit number sign above it (number 1a) supported by an exit number sign support and another secondary sign (number 1b) mounted below it using a C4x5.4 channel support. In this case, rows 1L and 1R (for sign number 1) would each have a check entered in the multi-post breakaway column, the row for sign number 1a would have a check entered in the exit number sign support column, and the row for sign number 1b would have a check entered in the C4x5.4 column under secondary sign supports.

Some sign numbers and their corresponding rows will have no check marks entered in the support columns. This is because each support, whether primary or secondary, is only to be detailed once in the data table. This eliminates confusion when calculating actual material quantities needed.

For example, if a single wood post supports a STOP sign (number 1) and street name signs for two different streets (numbers 2 and 3), then the wood post column would only be checked in the row for sign number 1. The other signs (2 and 3) would not have any check marks in their rows for support types. They would, however, contain notes in the REMARKS column (to be discussed later) indicating that their support is detailed with sign number 1.

Detail each support only once, but make cross references so that it is obvious how each individual sign is supported.

Post Size and Length

These columns are only filled in for the following types of supports: wood posts, perforated steel square tube sign supports, triangular base breakaway sign supports, multi-post breakaway sign supports, exit number sign supports and milepost marker posts. Lengths for secondary sign supports are also required in the data table, but there is a separate column for this purpose next to the other columns which are specific to secondary sign supports.

In the post size column, enter information specific to the cross-sectional size of the support. In the post length column, enter the length of the support, usually in feet and inches. Further explanation is provided in the following paragraphs. The actual design of supports and determination of appropriate sizes and lengths is discussed in a later chapter on support design.

Post sizes for wood posts and perforated steel square tube sign supports have nominal cross-sectional size in inches. ODOT uses wood post sizes of 4"x4", 4"x6", 6"x6" and 6"x8". Perforated steel square tube sign supports come in the following cross-sectional sizes: 2", 2.25" and 2.5".

Post lengths for wood posts are calculated in even two foot increments which is consistent with how they are sold on the market (14', 16', 18', etc.). The lengths shown represent the total length of post from the bottom of the embedment (4' to 7' below the surface) to the top of the three inch reveal above the sign(s) supported.

Calculate post lengths for perforated steel square tube sign supports to the nearest inch and show them in terms of feet and inches. The lengths shown represent the total length of the main square tube post from the bottom of the embedment (18" below the surface) to the top of the sign(s) supported.

Milepost marker posts all have a specific size detailed in Standard Drawing TM222. The designer can either enter the specific size under this column or enter "SEE TM222" in this column to specify post size for milepost marker posts.

Post lengths to be shown for milepost marker posts can be found on the previously mentioned chart on Standard Drawing TM222. These values vary with the size of the milepost marker supported. Enter the appropriate measurement (in feet and inches) from the chart.

Post sizes for triangular base breakaway and multi-post breakaway supports, as well as exit number sign supports, have industry recognized structural member names. All exit number sign supports are short flange members of a specific size (S 3x5.7). Use them in pairs and indicate the need for two of them in your entry. All multi-post breakaway sign supports are wide flange members which come in a range of sizes shown on Standard Drawing TM601 (W 6x9, W 6x12, W 6x15, etc.). All triangular base breakaway sign supports are tubular steel members made of three-sixteenths inch thick steel. The available sizes are shown on Standard Drawing TM602 (range from TS 3x3 thru TS 8x8).

Enter lengths for multi-post breakaway and triangular base breakaway sign supports in units of feet and inches, in each case to the nearest inch. Unlike some of the other supports the length indicated does not include the portion of the support below the surface in the concrete footing. Lengths shown for the multi-post supports represent the entire post beginning at the top of the base plates and working up to the top of the post at or just above the top of the primary sign. Lengths shown for the triangular base supports represent the entire post beginning at the top of the base plates and working up to the top of the post. The top of the post will not always coincide with the top of the sign(s). If a triangular base breakaway support has an “H” frame, then the length is only calculated up to where the post ends at the “H” frame. This coincides with a distance half way up the back of the sign. If the support does not have an “H” frame, then the top of the post coincides with the top of the sign and the length shown should reflect that.

Exit number sign supports are used in pairs and will almost always be 7' in length. This is the length required for a standard application of this support which involves supporting a 30 inch tall exit number sign above a primary guide sign, with the supports also running a length of nearly 4 feet 6 inches down the back of the primary sign. These supports, however, are also used for signs other than exit number signs, so the length needed could vary. It is also possible that the primary sign may be shorter than 4 feet 6 inches, requiring the exit number sign supports to be shortened so as not to extend below the primary sign. Enter the appropriate length in feet and inches.

Footing Location and Minimum Depth

These columns are only for ground-mounted installations that specifically require concrete footings. That limits it to multi-post breakaway sign supports, triangular base breakaway sign supports and perforated steel square tube sign supports.

The location column should show an offset value, in feet and inches, representing the distance from a particular point of reference to the center of the desired footing location. This point of reference is the edge of pavement, edge of travel lane (fog line), face of guardrail or concrete barrier, face of curb, or back of sidewalk, whichever is most appropriate. Include a note in the remarks column to specify which point of reference to measure from. This specified distance will allow the contractor to accurately stake the location of the footing to insure that it gets installed where it needs to be.

The minimum depth column includes a measurement in feet and inches representing the total minimum depth required for the concrete footing. For perforated steel square tube sign supports, the minimum footing depth is always 3 feet. For multi-post and triangular base breakaway supports, the minimum footing depths vary with the size of the support. These depth values can be found in the same charts referred to earlier in Standard Drawings TM601 and TM602.

Remarks

This last column is reserved for any remarks needed to further explain the installation of the particular sign and/or support detailed within that row. Sometimes further explanation is needed in this column to supplement the location or offset of a sign or footing. Installations that contain several signs, especially when they do not all face the same direction, may need remarks added in this last column to explain the orientation of a particular sign or to explain that the support for that sign has already been detailed for one of the other signs. Sometimes a sign may need to be supplied by ODOT or another agency such as State Parks. When this is the case, a remark should be added stating this. Use this column to refer to other drawing numbers (plan sheets) that relate to some of your signs. Examples include referencing design drawings for signal poles, cantilevers, sign bridges or other supports which relate to specific signs.

SIGN AND POST DATA TABLE															REFER TO OREGON STANDARD DRAWING		REMARKS			
SIGN NO.	SIGN LOCATION	SIGN DIMENSIONS	SIGN HEIGHT	BORDER WIDTH	RADIUS	ARROW INFO	SIGN TYPE (PER SEC. 2010 STD. SPECIFICATIONS)	SUBSTRATE	COLOR 1/			LEGEND TYPE	SIGN NO.	TYPE OF SUPPORT	POST SIZE (BASED ON ESTIMATED LENGTH)	POST LENGTH (MUST BE FIELD VERIFIED)	LOCATION	FOOTING MIN. DEPTH	REFER TO OREGON STANDARD DRAWING	REMARKS
									ASTM TYPE I OR II	ASTM TYPE III OR IV	ASTM TYPE IX									
16	CL 30+60 RL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	16	WOOD POST	4"-6"	18'		TM602			
16a	CL 30+60 RL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	16	WOOD POST	4"-6"	18'		TM602			
16b	CL 121+50 LL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	16	WOOD POST	4"-6"	18'		TM602			
16c	CL 121+50 LL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	16	WOOD POST	4"-6"	18'		TM602			
17	CL 47+25 LL 36"	36"	36"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	17	WOOD POST	4"-6"	20'		TM602			
19	CL 96+50 RL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	19	WOOD POST	4"-6"	18'		TM602			
19a	CL 96+50 RL 24"	24"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	19	WOOD POST	4"-6"	18'		TM602			
22	CL 93+90 LL 36"	36"	30"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	22	WOOD POST	4"-6"	18'		TM602			
25	CL 103+00 RL 36"	36"	36"				"Y1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	25	WOOD POST	4"-6"	18'		TM602			
26	CL 96+25 RL 36"	36"	36"				"Y1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	26	WOOD POST	4"-6"	18'		TM602			
27	CL 39+00 LL 66"	30"	30"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	27	WOOD POST	4"-6"	18'		TM602			
28	EL 24+10 RL 21"	15"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	28	WOOD POST	4"-6"	18'		TM602			
28a	EL 24+10 RL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	28	WOOD POST	4"-6"	18'		TM602			
29	CL 100+75 LL 24"	12"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	29	WOOD POST	4"-6"	20'		TM602			
29a	CL 100+75 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	29	WOOD POST	4"-6"	20'		TM602			
29b	CL 100+75 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	29	WOOD POST	4"-6"	20'		TM602			
29c	CL 100+75 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	29	WOOD POST	4"-6"	20'		TM602			
30	CL 96+50 LL 24"	12"	12"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	30	WOOD POST	4"-6"	18'		TM602			
30a	CL 96+50 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	30	WOOD POST	4"-6"	18'		TM602			
30b	CL 96+50 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	30	WOOD POST	4"-6"	18'		TM602			
30c	CL 96+50 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	30	WOOD POST	4"-6"	18'		TM602			
30d	CL 96+50 LL 24"	24"	24"				"W1"	PLYWOOD	ASTM TYPE I OR II	ASTM TYPE IX	PERMANENT	30	WOOD POST	4"-6"	18'		TM602			

Figure 26 | Sample Sign and Post Data Table

OREGON DEPARTMENT OF TRANSPORTATION
TRAFFIC - HIGHWAY SECTION


REGION AND OR CONSULTANT LOGO

PROJECT NAME
FROM TITLE SHEET
NAME OF HIGHWAY
NAME OF COUNTY

DESIGNED BY: Name
DRAWN BY: Name
CHECKED BY: Name
SCALE: 1/8" = 1'-0"

PERMANENT SIGNING

DATE: _____ I.D. NO. _____ I.D.S. NO. 5-21109



1) BK-BLACK
BL-BLUE
BR-BROWN
FY-FLUORESCENT YELLOW
G-GREEN
O-ORANGE
R-RED
RB-RED-BLUE
SW-SILVER-WHITE
W-WHITE
Y-YELLOW
YG-YELLOW-GREEN

2) NOTE: L.C.R ARE LOCATIONS OF POSTS
FACING THE SIGN.
L-LEFT POST
C-CENTER POST
R-RIGHT POST

3) DISTANCE FROM EDGE OF TRAVEL LANE
FACE OF CURB, GUARDRAIL OR BARRIER
TO THE CENTERLINE OF FOOTING. FOR
ADDITIONAL INFORMATION SEE STANDARD
DRAWINGS TM601, TM602 AND TM603.

4) NOTE: THE LOCATIONS SHOWN ARE APPROXIMATE
EXCEPT FOR SPEED ZONES, SCHOOL ZONES, OBJECT
MARKERS AND MILEPOST MARKERS. EXACT LOCATIONS
ARE TO BE DETERMINED BY THE ENGINEER.

5) MINIMUM DEPTH OF FOOTING FOR
TRIANGULAR BASE BREAKAWAY AND
MULTI-POST BREAKAWAY INSTALLATIONS
IS FOR A 2" DIAMETER FOOTING. FOR
ADDITIONAL INFORMATION SEE STANDARD
DRAWINGS TM601 AND TM602.

THIS IS THE FILENAME LOCATION ***** DD-MMM-YYYY HHMM USERNAME I:1200 - 9

SIGN NO.	SIGN LOCATION	SIGN DIMENSIONS	BORDER WIDTH	RADIUS	APPROX INFO	SIGN TYPE (PER SEC. 2010 STD. SPECIFICATIONS)	SUBSTRATE	COLOR	LEGEND	LEGEND	SIGN NO.	SIGN TYPE	TYPE OF SUPPORT	POST		FOOTING	REFER TO OREGON STANDARD DRAWING	REMARKS
														WIDTH	HEIGHT			
31	CL 31+30 LI, 24"	24" x 12"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX	31	REMOVABLE	WOOD POST	6"-16"	22"	5/8"	TM600 & 801 TM602 TM635 TM675 TM676 & 208 TM677 & 679 TM678 TM681, 687 & 688 TM620 & 201 TM621 & 222	
31a	CL 31+30 LI, 24"	24" x 12"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX		PERMANENT	WOOD POST	6"-16"	22"	5/8"		
31b	CL 31+30 LI, 24"	24" x 12"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX		NON-REFLECTIVE	WOOD POST	6"-16"	22"	5/8"		
31c	CL 31+30 LI, 21"	21" x 15"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX		PERMANENT	WOOD POST	6"-16"	22"	5/8"		
31d	CL 31+30 LI, 24"	24" x 12"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX		NON-REFLECTIVE	WOOD POST	6"-16"	22"	5/8"		
31e	CL 31+30 LI, 30"	30" x 24"	1/2"	0"		"W1"	PLYWOOD	ASTM TYPE IX	ASTM TYPE IX	ASTM TYPE IX		PERMANENT	WOOD POST	6"-16"	22"	5/8"		
32	EB 21+90 RL					EXIST.	EXIST.				32							REINSTALL BELOW SIGN NO. 6
33	CL 41+40 RL					EXIST.	EXIST.											REINSTALL BELOW SIGN NO. 10
34	CL 47+25 LI, 45"	9"				"Y1"	Y											REINSTALL EXIST. SIGN & SUPPORT
35	CL 47+25 LI, 45"	9"				"Y1"	Y											REINSTALL EXIST. SIGN & SUPPORT
36	WB 22+00 LI					EXIST.	EXIST.											REINSTALL EXIST. SIGN & SUPPORT
37	CL 28+15 LI, 4'-0"	2'-0"	1/2"	0"		"G"	G	SW										REINSTALL EXIST. SIGN & SUPPORT

Figure 27 | Sample Sign and Post Data Table

1) OREGON DEPARTMENT OF TRANSPORTATION
TRAFFIC - ROADWAY SECTION

REGION AND OR CONSULTANT LOGO

PROJECT NAME
FROM TITLE SHEET
NAME OF HIGHWAY
NAME OF COUNTY

DESIGNED BY: Name
DRAWN BY: Name
CHECKED BY: Name
SCALE: 1/8"=1'-0"

PERMANENT SIGNING

1:1200 - 10

REGISTERED PROFESSIONAL ENGINEER
XXXXX

REGISTERED PROFESSIONAL ENGINEER
XXXXX

OREGON X61 XXXXX
MARCH X, XXXX
Expires June

- 4) NOTE: THE LOCATIONS SHOWN ARE APPROXIMATE EXCEPT FOR SPEED ZONES, SCHOOL ZONES, OBJECT MARKERS AND MILEPOST MARKERS. EXACT LOCATIONS ARE TO BE DETERMINED BY THE ENGINEER.
- 5) MINIMUM DEPTH OF FOOTING FOR TRIANGULAR BASE BREAKAWAY AND MULTI-POST BREAKAWAY INSTALLATIONS IS FOR A 2 DIAMETER FOOTING. FOR ADDITIONAL INFORMATION SEE STANDARD DRAWINGS TM601 AND TM602.

- 2) NOTE: L.C.R ARE LOCATIONS OF POSTS
FACING THE SIGN
L-LEFT POST
C-CENTER POST
R-RIGHT POST
- 3) DISTANCE FROM EDGE OF TRAVEL LANE FACE OF CURB, GUARDRAIL OR BARRIER TO THE CENTERLINE OF FOOTING. FOR ADDITIONAL INFORMATION SEE STANDARD DRAWINGS TM601, TM602 AND TM603.

- 1) BK-BLACK
BL-BLUE
BR-BROWN
FY-FLUORESCENT YELLOW
G-GREEN
O-ORANGE
P-RED
PB-RED-BLUE
SW-SILVER-WHITE
W-WHITE
Y-YELLOW
YG-YELLOW-GREEN

SIGN AND POST DATA TABLE

SIGN NO.	SIGN LOCATION	SIGN DIMENSIONS	SIGN WIDTH	SIGN HEIGHT	ARROW INFO	SIGN TYPE (PER SEC. 2910 STP. SPECIFICATIONS)	SUB. STR. (WOOD, SHEET ALUMINUM, EXTRUDED ALUMINUM)	COLOR 1	LEGEND	LEGEND	LEGEND	TYPE OF SUPPORT	POST		FOOTING		REFER TO OREGON STANDARD DRAWING	REMARKS
													SIZE (ESTIMATED LENGTH)	LENGTH (MUST BE FIELD VERIFIED)	LOCATION	MIN. DEPTH		
36	CL 29+30 LI	3'-0"	3'-0"	3'-0"	∅ 8" x 18"	B	WOOD	BL	SW	REMOVABLE	PERMANENT	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
40	CL 34+10 RI	8'-0"	3'-0"	3'-0"	"G"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
41	CL 40+00 RI	5'-0"	3'-0"	3'-0"	"G"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
42	CL 47+25 LI	4'-0"	1'-0"	1'-0"	"G"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
43	EN 107+10 RI				E1/S1		WOOD POST			NON-REFLECTIVE	PERMANENT	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
46	CL 43+00 RI	17'-0"	3'-0"	3'-0"	E1/S1		WOOD POST			NON-REFLECTIVE	PERMANENT	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
49	WP 129 WB	10'-0"	6'-0"	6'-0"	"G"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53	CL 41+50 LI	15'-0"	8'-0"	8'-0"	∅ 12" x 18"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53a		24"	12"	12"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53b		24"	24"	24"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53c		24"	24"	24"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53d		24"	24"	24"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
53e		24"	18"	18"	"C"	BR	STEEL SQUARE TUBE	BR	SW	SW	SW	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54	CL 29+50 LI	14'-0"	9'-6"	9'-6"	∅ 12" x 18"	G	STEEL SQUARE TUBE	G	SW	PERMANENT	PERMANENT	TRUNKULAR BASE BREAKAWAY	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54a		24"	12"	12"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54b		24"	24"	24"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54c		21"	15"	15"	"W1"	SW	STEEL SQUARE TUBE	SW	BK	BK	BK	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54d		24"	24"	24"	"C"	BR	STEEL SQUARE TUBE	BR	SW	SW	SW	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE
54e		24"	18"	18"	"C"	BR	STEEL SQUARE TUBE	BR	SW	SW	SW	WOOD POST	W 8x18	22'-0"	8'-0"	3'-6"	TM600 & 601	CLAMP TO SIGNAL POLE

Figure 28 | Sample Sign and Post Data Table

- 1) BK-BLACK
BL-BLUE
BR-BROWN
FY-FLUORESCENT YELLOW
G-GREEN
O-ORANGE
P-PED
RB-RED-BLUE
SW-SILVER-WHITE
W-WHITE
Y-YELLOW
YG-YELLOW-GREEN
- 2) NOTE: L.C.R ARE LOCATIONS OF POSTS
FACING THE SIGN.
L-LEFT POST
C-CENTER POST
R-RIGHT POST
- 3) DISTANCE FROM EDGE OF TRAVEL LANE, FACE OF CURB, GUARDRAIL OR BARRIER TO THE CENTERLINE OF FOOTING, FOR ADDITIONAL INFORMATION SEE STANDARD DRAWINGS TM601, TM602 AND TM603.
- 4) NOTE: THE LOCATIONS SHOWN ARE APPROXIMATE EXCEPT FOR SPEED ZONES, SCHOOL ZONES, OBJECT MARKERS AND MILEPOST MARKERS. EXACT LOCATIONS ARE TO BE DETERMINED BY THE ENGINEER.
- 5) MINIMUM DEPTH OF FOOTING FOR TRUNKULAR BASE BREAKAWAY AND MULTI-POST BREAKAWAY INSTALLATIONS IS FOR A 2" DIAMETER FOOTING. FOR ADDITIONAL INFORMATION SEE STANDARD DRAWINGS TM601 AND TM602.

OREGON DEPARTMENT OF TRANSPORTATION
TRAFFIC - ROADWAY SECTION


REGION AND OR CONSULTANT LOGO

PROJECT NAME
FROM TITLE SHEET
NAME OF HIGHWAY
NAME OF COUNTY

DESIGNED BY: NAME
CHECKED BY: NAME
DRAWN BY: NAME
SCALE: 1"=10'-0"
DATE: 11-15-10

PERMANENT SIGNING

1:1000 - 11



SIGN NO.	SIGN LOCATION	SIGN DIMENSIONS	BORDER WIDTH	RADIUS	APPROX INFO	SIGN TYPE	SUBSTRATE	COLOR	LEGEND	LEGEND	SIGN NO.	TYPE	TYPE OF SUPPORT	POST		FOOTING		REFER TO OREGON STANDARD DRAWING	REMARKS
														WIDTH	HEIGHT	LENGTH	LOCATION		
55	EB 27+85 RL 14'-0"	14'-0" x 8'-0"	1/2"	0	1/2-10-15	G	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	55L	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	* DIST. BEHIND BACK OF SIDEWALK * DIST. BEHIND BACK OF SIDEWALK
55a		24" x 12"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	55R	NON-REFLECTIVE	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55b		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55c		21" x 15"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55d		24" x 12"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55e		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55f		21" x 15"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55g		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
55h		24" x 18"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56	CA 91+85 LL 13'-0"	8'-0" x 8'-0"	1/2"	0	1/2-10-15	G	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	56L	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	* DIST. FROM EDGE OF TRAVEL LANE * DIST. FROM EDGE OF TRAVEL LANE
56a		24" x 12"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	56R	NON-REFLECTIVE	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56b		30" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56c		30" x 12"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56d		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56e		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56f		21" x 15"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56g		24" x 12"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
56h		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
57	CA 29+30 LL 24"	24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	57	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
57a		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
58	CA 29+30 LL 24"	24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	58	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
58a		24" x 24"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
59	CA 92+50 RL 36"	48" x 48"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	59	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
59a		48" x 48"	1/2"	0	"W1"	SW	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
60	WR 22+00 LL 6'-6"	3'-0" x 3'-0"	1/2"	0	"G"	G	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV	60	PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	
60a		3'-0" x 3'-0"	1/2"	0	"G"	G	PLYWOOD	ASTM TYPE III OR EXTRUDED ALUMINUM	ASTM TYPE IX	ASTM TYPE III OR IV		PERMANENT	WOOD POST	W 8x18	21'-0" x 4'-0"	8'-0"	8'-0"	TM602 & 601	

Figure 29 | Sample Sign and Post Data Table

1) BKG-BLACK
BL-BLUE
BR-BROWN
FY-FLUORESCENT YELLOW
G-GREEN
O-ORANGE
R-RED
RB-RED-BLUE
SW-SILVER-WHITE
W-WHITE
Y-YELLOW
YG-YELLOW-GREEN

2) NOTE: LCR ARE LOCATIONS OF POSTS
 FACING THE SIGN
 L-LEFT POST
 C-CENTER POST
 R-RIGHT POST

3) DISTANCE FROM EDGE OF TRAVEL LANE
 FACE OF CURB, GUARDRAIL OR BARRIER
 TO THE CENTERLINE OF FOOTING. FOR
 ADDITIONAL INFORMATION SEE STANDARD
 DRAWINGS TM601, TM602 AND TM603.

4) NOTE: THE LOCATIONS SHOWN ARE APPROXIMATE
 EXCEPT FOR SPEED ZONES, SCHOOL ZONES, OBJECT
 MARKERS AND MILEPOST MARKERS. EXACT LOCATIONS
 ARE TO BE DETERMINED BY THE ENGINEER.

5) MINIMUM DEPTH OF FOOTING FOR
 TRIANGULAR BASE BREAKAWAY AND
 MULTI-POST BREAKAWAY INSTALLATIONS
 IS FOR A 2" DIAMETER FOOTING. FOR
 ADDITIONAL INFORMATION SEE STANDARD
 DRAWINGS TM601 AND TM602.

OREGON DEPARTMENT OF TRANSPORTATION
 TRAFFIC - HIGHWAY SECTION

REGION AND OR CONSULTANT LOGO

PROJECT NAME
 FROM TITLE SHEET
 NAME OF HIGHWAY
 NAME OF COUNTY

DESIGNED BY: NAME
 DRAWN BY: NAME
 EC: PLO MP: PLO 2.11.15

PERMANENT SIGNING

REGISTERED PROFESSIONAL ENGINEER
 XXXXX
 OREGON XXXX
 MARCH X, XXXX
 EXP. 31 JUN 2022

PL: B. N. _____ I.S.L. OR. No. S-XXXX

Sheet Numbers

All sign plan sheets, sign detail sheets, and sign and post data table sheets require unique sheet numbers that are assigned by the Traffic-Roadway Section. These unique sheet numbers are used to archive all of the signing sheets on a project.

Sheet numbers should be requested as close as possible to the printing of final mylars. This is because the unique sheet numbers run consecutively, and once a set of numbers is assigned it is difficult to simply add or delete plan sheets from your project. If a sheet needs to be added or deleted after the sheet numbers have been assigned, often a completely new set of numbers will need to be assigned and the old numbers voided. Therefore, it is best to request sheet numbers when you are certain that the total number of plan sheets will not change. This usually occurs sometime between the advanced plans and printing of the final mylars.

Projects on freeways or expressways or in urban areas will frequently include overhead sign supports, requiring the production of structural design drawings. If these drawings are for stand-alone supports such as sign bridges, cantilevers or butterfly supports, then they are to be assigned Signing sheet numbers. If they are for supports that are attached to a bridge structure, such as structure mounts or bridge rail mounts, then the drawings are to be assigned Bridge drawing numbers from Bridge Section.

Ideally, structural drawings which are determined to need Signing sheet numbers should be bundled together with the Signing Plans when sheet numbers are requested. This will take some coordination and cooperation among the different designers to get it done right. The structural sheets that are related to the Signing Plans should be positioned immediately after the Sign & Post Data Tables so they can be assigned numbers that are consecutive with the Signing Plans. All sheets can then be sent in together at one time as part of a single request from a single party. If they come in separately there are no guarantees that the numbers assigned will be consecutive. This may seem like a small matter, but it makes a big difference years down the line when somebody searches our records for “as-built” information. It is much easier to find information on overhead support structures when the sheets are part of the same run of numbers as the signing sheets they relate to.

If it is not possible or practical to request these sheet numbers together as one group, then the related sheets should be cross-referenced to one another. For example, a note might be inserted in the REMARKS column of the Sign & Post Data Table referencing a particular drawing number for the sign structure that relates to the subject sign number from the Data Table.

To request sheet numbers for all the plan sheets on the project, call (503) 986-3601 to obtain your sheet numbers.



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 5

Standards

5 | Standards

Standard Drawings and Standard Details

The Standard Drawings which support permanent signing are located in the TM200 and TM600 series of drawings. These can be accessed through the following web-site link:

<http://www.oregon.gov/ODOT/Engineering/Pages/Drawings-Traffic.aspx>. Many of these Standard Drawings have already been discussed for content in the chapter 4 section on Sign and Post Data Tables. Others not previously mentioned include: TM211 & 212 (Interstate, U.S. and Oregon route shields); TM221 (Mile post marker signs); TM223 – 225 (Guide signs, conventional and freeway/expressway); and TM230 – 233 (Demountable legend).

All Standard Drawings which apply to the work described in your plans are to be listed as part of the final submittal of PS&E documents to the Spec Writer. These are to be listed as “Accompanied By Drawings” in the lower right corner of the title block on your first plan sheet, just above the sheet number. The Spec Writer will also include this information in their Index of Sheets which appears just after the Title Sheet. All sheets listed will be added at the end of the set of contract plans.

Standard Specifications and Special Provisions

Oregon Standard Specifications for Construction (2018) are located at the following web-site: http://www.oregon.gov/ODOT/Business/Pages/Standard_Specifications.aspx. Most of the specifications dealing with permanent signing are in Part 00900 – Permanent Traffic Control and Illumination Systems. There are, however, other portions of this book that relate to signing, as well. For each section of this book on standard specifications, there is a corresponding document that contains information that is updated or has been modified or deleted since the publication of the book in 2018. These documents, or Special Provisions, can be found at the following web-site location: <http://www.oregon.gov/ODOT/Business/Pages/Boilerplate-SP-2018.aspx>

Special Provisions, as shown at this web-site are referred to as “boiler-plate” Special Provisions. They are intended to supplement or supersede the corresponding information shown in the Standard Specifications.

Any Special Provision that covers an item or a type of work shown in the plans must be included in the contract documents for that project. Some of the boiler-plate Special Provisions do not actually contain any updated information, but simply make reference to the corresponding Standard Specification. These boiler-plate Special Provisions must still be included in the contract documents. In some cases, the boiler-plate Special Provisions may contain some information that does not apply to a particular project. In this case, delete that information from the boiler-plate Special Provision before it is submitted to the Spec Writer. Turn on “Track Changes” before editing boiler-plate special provisions, so the Spec Writer can see that you have deleted or changed something. If you wish to actually change or add to the content of the boiler-plate Special Provision, you need to first consult with the “technical resource” of the Specification. For permanent signing issues, that is the ODOT Sign Engineer, who can be reached at (503) 986-4013. If the issue is related to structural steel supports or their footings/foundations, then the technical owner is the ODOT Senior Traffic Structures Engineer, who can be reached at (503) 986-3069.

The boiler-plate Special Provisions most commonly used in conjunction with permanent signing plans are as follows: Section 840 for projects with milepost marker post installations; Section 905 for projects that have removals or reinstallations of existing signs and/or supports; Section 910 for projects that have new wood posts being installed; Section 920 for projects that include installation of sign support footings; Section 930 for projects that include installation of any of a variety of metal sign supports; and Section 940 for projects including fabrication and installation of new signs. Many of these Special Provisions refer to other related Special Provisions which must also be included in the final submittal to the Spec Writer. Among these are sections 440, 2110, 2190, 2530, 2910 and 2920. There are still other Special Provisions such as Section 941 (Sign Covers) which apply to items not frequently used on ODOT contracts.

The Section 160 Special Provision (Source of Materials) has a subsection (160.30) which deals with agency-furnished materials. Whenever your project includes the installation of certain specialty signs which are to be provided by ODOT or another agency, then a list of these signs is to be provided in this subsection along with an indication of where these signs will be delivered. These agency-supplied materials are usually signs that have a graphic or unique design, and would therefore be difficult for a sign supplier to reproduce. These are almost always signs which are part of the standard stock at the ODOT Sign Shop.

Of the permanent signing Special Provisions mentioned above only a few typically require any modification. In most cases the Special Provision is sufficient in its boiler-plate version. Notable exceptions are Sections 920 and 930 which contain subsections where the designer is required to list materials quantities for certain bid items. Other notable exceptions are present in Sections 930 and 940 which contain language specific to painting of metal sign supports and the backs of aluminum substrate signs. This is generally not done except for under special circumstances, as requested by other agencies or jurisdictions. Therefore, unless this work has been requested, it is necessary to delete these subsections from the Special Provisions to insure that the work is not performed.

All Special Provisions pertaining to your design are to be submitted, along with the plan sheets and an engineer's estimate showing a breakdown by bid item, to the Spec Writer. This is first done at the Advance PS&E stage of design. There may be some modification required after the review process, and the final Special Provisions package will be submitted at the Final PS&E stage. The Special Provisions are, of course, Word documents and should be submitted electronically. They are typically attached to and submitted with an Email message.



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 6

Estimates

6 | Estimates

List of Bid Items

As part of your submittals to the Spec Writer at both Advance and Final PS&E, include a detailed cost estimate broken down into individual bid items. The bid items should be listed in order by item code (section number from Standard Specs). For each item, indicate the official bid item name and associated unit of measure as shown in the Standard Specifications and Special Provisions. Other information needed for the estimate includes: item code, quantity, unit cost, and total cost for each bid item.

ODOT has a cost estimating Excel spreadsheet for permanent signing available for use on request. It can be obtained by calling (503) 986-3599. This spreadsheet already has the most commonly used bid items listed. Item codes and units of measure have also been provided. Values have been provided for unit costs, but should be updated or adjusted to regional price variations.

Quantities need to be input for all bid items that are not lump sum. The spreadsheet will automatically calculate a total cost for each of these items. For lump sum items, you will need to estimate a dollar amount for each item on your own and input these values in the unit cost column of the spreadsheet. The spreadsheet then will automatically copy this value into the total cost column. Once a total price has been calculated for each item, the spreadsheet calculates a subtotal for all bid items. If you have any anticipated items (State Supplied Signs), there is a row down below the subtotal where you can enter a lump sum cost into the unit cost column. The spreadsheet will copy this value to the total cost column and will add this value to the previously mentioned subtotal to provide you with a total for the entire spreadsheet.

A sample of the cost estimating Excel spreadsheet is included in this chapter (Figure 30). If a project has bid items not already shown in the spreadsheet, add them where needed. Just make sure to adjust any formulas that may be affected by this so that the spreadsheet will still calculate properly. The list of bid items and cost estimate will first need to be provided with Advance PS&E. It should be attached to an Email message and mailed to the Spec Writer along with the Special Provisions. After Advance Plans review there will likely be comments to address that may affect your quantities and estimate. An updated estimate should be sent in with the Final Special Provision package at the time that signed mylars are submitted to the Spec Writer.



**Oregon Department of Transportation
Traffic Management Section
Traffic Signing Cost Summary**

DATE:

PROJECT:

KEY NO. :

HIGHWAY:

COUNTY:

SCHEDULED LET DATE :

E.A. :

BID SCHEDULE

NO.	ITEM	ITEM CODE	UNIT	QUAN.	UNIT COST	TOTAL
1	Milepost Marker Posts	841	Each	0.00	\$65.00	\$0.00
2	Remove Existing Signs	905	Lump	1.00	\$0.00	\$0.00
3	Remove and Reinstall Existing Signs	905	Lump	1.00	\$0.00	\$0.00
4	Wood Sign Posts	910	fbm	0.00	\$7.00	\$0.00
5	Sign Support Footings	920	Lump	1.00	\$0.00	\$0.00
6	Tri. Base Breakaway Sign Supports	930	Lump	1.00	\$0.00	\$0.00
7	Multi-post Breakaway Sign Supports	930	Lump	1.00	\$0.00	\$0.00
8	Exit Number Sign Mounts	930	Lump	1.00	\$0.00	\$0.00
9	Signal Pole Mounts	930	Lump	1.00	\$0.00	\$0.00
10	Perforated Steel Square Tube Supports	930	Lump	1.00	\$0.00	\$0.00
11	Perf. Steel Sq. Tube Breakaway Supports	930	Lump	1.00	\$0.00	\$0.00
12	Secondary Sign Mounts	930	Lump	1.00	\$0.00	\$0.00
13	Vertical Sign Mounts (Existing Structures)	930	Lump	1.00	\$0.00	\$0.00
14	Type "B" Signs In Place	940	ft ²	0.00	\$25.00	\$0.00
15	Type "B2" Signs In Place	940	ft ²	0.00	\$35.00	\$0.00
16	Type "C" Signs In Place	940	ft ²	0.00	\$25.00	\$0.00
17	Type "C1" Signs in Place	940	ft ²	0.00	\$35.00	\$0.00
18	Type "F" Signs In Place	940	ft ²	0.00	\$16.00	\$0.00
19	Type "F1" Signs In Place	940	ft ²	0.00	\$22.00	\$0.00
20	Type "G" Signs In Place	940	ft ²	0.00	\$25.00	\$0.00
21	Type "G1" Signs In Place	940	ft ²	0.00	\$35.00	\$0.00
22	Type "G2" Signs in Place	940	ft ²	0.00	\$25.00	\$0.00
23	Type "R" Signs In Place	940	ft ²	0.00	\$16.00	\$0.00
24	Type "R1" Signs In Place	940	ft ²	0.00	\$18.00	\$0.00
25	Type "R2" Signs In Place	940	ft ²	0.00	\$18.00	\$0.00
26	Type "W1" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
27	Type "W2" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
28	Type "W4" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
29	Type "W5" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
30	Type "W7" Signs In Place	940	ft ²	0.00	\$22.00	\$0.00
31	Type "Y1" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
32	Type "Y2" Signs In Place	940	ft ²	0.00	\$20.00	\$0.00
33	Type "Y4" Signs In Place	940	ft ²	0.00	\$20.00	\$0.00
34	Type "Y5" Signs In Place	940	ft ²	0.00	\$30.00	\$0.00
35	Type "YG" Signs In Place	940	ft ²	0.00	\$17.00	\$0.00
ESTIMATED SIGN CONTRACT COST -----						\$0.00

ANTICIPATED ADDITIONAL ITEMS

	State supplied signs	160	Lump	1.00	\$0.00	\$0.00
--	----------------------	-----	------	------	--------	--------

ESTIMATED SIGN PROJECT COST -----						\$0.00
--	--	--	--	--	--	---------------

Figure 30 | Cost Estimating Spreadsheet

Providing Quantities

Each of the bid items used for permanent signing falls into one of three categories for payment: 1.) Per each, 2.) Per unit of measure, or 3.) Lump sum. To determine which of the three applies to a particular bid item, look in the Standard Specifications and the corresponding Special Provisions for the subsections defining measurement and payment at the end of the section that deals with that particular bid item.

There will be language specifying how the item is to be measured, to what degree of accuracy, and how it is to be paid for. Mile post marker posts, for example, are to be paid for per each post. Wood sign posts are to be paid for per foot board measure (FBM). An individual FBM is to be calculated for each wood post detailed in the plans and then the sum total of these is provided as the quantity on the cost estimate for that bid item. FBM is calculated for each post by multiplying the nominal cross-sectional dimensions in inches and dividing the resulting value by 12. Once this has been done, multiply the new resulting value by the length of the post in feet to get your number of FBM for that particular post. A 6"x6" post of 20 foot length equals 60 FBM.

Each type of sign is paid for by the square foot. The easiest way to tabulate quantities for these is to go through each Sign and Post Data Table and calculate a square footage for each new sign by multiplying together the dimensions (converted to feet). Once this has been completed, tally up a total square footage for each sign type and these amounts are entered as quantities onto the cost estimate spreadsheet.

Sign (and post) removals as well as removal and reinstallation of existing signs are lump sum bid items. Although quantities do not need to be provided for either of these items for bid purposes, it is still necessary to tally up the number of removals and reinstallations for the project so that you can estimate a lump sum dollar amount to cover this work. For removals, categorize by size of removal, number of footings involved and whether the sign is ground mounted or overhead. The cost of removal will vary considerably depending on how large it is, whether there are concrete footings to break up and remove, and whether special equipment is needed to remove signs from overhead supports. After assigning a reasonable amount of money for each type of removal or removal and reinstallation, total up the projected costs and enter them into the appropriate location on the cost estimate spreadsheet.

Sign Support Footings is another lump sum bid item, but unlike sign removals it requires that a quantity be provided in the Section 920 Special Provision for bid purposes. There are several types of steel sign supports that require concrete footings.

1. **Cantilevers and Sign Bridges** require custom design work and their footing quantities (excavation, concrete, rebar, and backfill) are to be listed individually per location, by the Bridge Designer. Each of these locations is also listed as a separate bid item for Sign Support Footings (specifying the type of footing and the location).
2. **All ground-mounted steel supports that have footings** (Triangular Base Breakaways, Multi-Post Breakaways, Perforated Steel Square Tube Sign Supports) are combined together as a single bid item called "Sign Support Footings". Although a single cost value is entered onto the cost estimate spreadsheet, the footings for these three types of supports are to be listed separately (by the Sign Designer) along with their quantities in the Section 920 Special Provision. So if you have all three types of supports on your project, you will show three separate quantities. These quantities will show the amount of concrete only (in cubic yards). There is no need to include amounts for excavation, rebar or backfill for ground-mounted supports.

By looking at your Sign and Post Data Tables you can tally up a total number of supports estimated for each type and size of support. Multiplying these numbers by the standard values shown for each corresponding size and type listed on the spreadsheet and adding the resulting numbers will give you the quantities (separately for TBBs and MPBs) that you need to show in the Special Provision. In the past there were no standard values available for the amount of concrete present in a Perforated Steel Square Tube Sign Support footing, because historically the installation methods varied widely. However, when installed according to Oregon Standard Drawing TM687 and TM688, the calculated amount of concrete (by figuring the volume of the excavated hole and subtracting out the volume occupied by the post anchor) is 0.09 cubic yards. Multiply this resulting amount by the total number of these supports shown in your data tables to get an estimated quantity for use in the Special Provision. Once you have your quantities figured for each type, add them together and multiply by an appropriate unit cost for concrete footings installed.

Except as otherwise stated in the Standard Specifications and Special Provisions (Section 930), list each type of steel support separately as its own lump sum bid item. Provide quantities of steel (in pounds) in the Special Provision for estimating purposes. A total quantity for each bid item (type of steel support) is necessary. Use the same web-site location mentioned above for calculating concrete quantities for calculating steel quantities. There are calculation sheets for each size of TBB, MPB, and for signal pole mounts.

After calculating quantities for each individual support, total by type of support and list the resulting quantities in the Special Provision. Quantities of steel for Perforated Steel Square Tube Sign Supports are a little tougher to figure, because there are a number of different cross-sectional sizes and varying wall thicknesses available. Some are designed to break away (slip bases), and some are designed to yield (anchor tubes). The perforated steel square tube manufacturers can provide information regarding the unit weight of steel (pounds per lineal foot) for each of the varying sizes and wall thicknesses they provide. Use these values multiplied by the length of each post and the corresponding sleeve(s) to calculate a total quantity of steel for each particular installation.

Add all the numbers for each “breakaway” installation to give you a total quantity of steel for all Perforated Steel Square Tube Breakaway Sign Supports. Likewise, add all the numbers for each “yielding” installation to give you a total quantity of steel for all Perforated Steel Square Tube Sign Supports. List these values in the Special Provision for estimating purposes. They are two separate bid items, so the quantities need to be shown separately.

Exit Number Sign Mounts are used in pairs. They are most commonly used in 7 foot lengths, but this may vary depending on the heights of the primary and secondary signs involved. These supports weigh roughly 5.7 pounds per lineal foot, so it is a simple calculation for figuring the weight of any single pair of ENSS. Add the weights of all such supports together and place this resulting value in the Special Provision for estimating purposes.

Structure Mounts and Bridge Rail Mounts are custom designs provided by a structural designer. That individual is responsible for providing quantities for bidding purposes on these items. Likewise for cantilevers and sign bridges, except that the quantities for these are to be listed separately and shown as separate bid items for each individual location. After estimating quantities for each steel bid item, select appropriate unit costs (per pound installed) for each type of steel in order to calculate a lump sum cost estimate for each item.

Unit Costs and Regional Factors

Historical data is available from ODOT Cost Estimating Unit on their web-site at http://www.oregon.gov/ODOT/Business/Pages/average_bid_item_prices.aspx. This site has data available with either a statewide or a regional focus. This data compiles bid prices submitted for projects dating as far back as 1998. Bid items are listed by the section number (2008 Oregon Standard Specifications for Construction) within which they fall. For example, wood sign posts are listed by the number 0910 since they are covered by Section 910.

Costs for certain bid items will vary some from region to region. Focus on the data available within your specific region of the state for the past 2-3 years. When there is not much data available within your region, look at the data available within an adjacent region. If necessary, look from the statewide listings for data. For items bid per each or per unit of measure, good cost figures should be available for putting together a cost estimate. Others bid as lump-sum items are more difficult to borrow data from, because the only historical data available are the actual lump-sum bid amounts which do not indicate the quantity of material covered by the bid mount.

If you are having trouble coming up with good cost figures for use in estimating, contact our ODOT Traffic Standards Unit at (503) 986-3599 for assistance.

Anticipated Items

When your project includes signs with unique, hard to reproduce, graphic features such as Scenic Byway signs, Tour Route signs, Historic Columbia River Highway, Lewis and Clark Trail, Oregon Trail, and State Parks Shields, you may wish to note them on the plans as “State Supplied Signs”. This is because these signs could prove difficult for some sign suppliers to accurately reproduce, and the signs are readily available through ODOT’s Sign Shop.

If you decide to call out for State Supplied Signs, then it should be noted as such on the Sign Details sheet next to the applicable sign(s) and in the “Remarks” column of the Sign and Post Data Table. In the Special Provisions (00160.30), list the items supplied, including the number and size of each type of sign.

At the bottom of the bid item/estimate spreadsheet enter a dollar amount that will cover the purchase and installation of these signs. This “Anticipated Item” amount enables the Project Manager to purchase the signs from the State Sign Shop when needed and to have them delivered to the contractor at the job site for installation. The amount provided should cover the cost of installation by the contractor as well as the purchase price of the signs. There may be occasions where anticipated items are necessary to cover items other than State Supplied Signs, but they are not very common.

When an Anticipated Item is used, justification is needed to support this decision. There is a process to follow for providing this justification in writing. The Cost Estimating Unit web-site offers a couple of letter templates that are required submittals within this process. First is the Letter of Approval for Anticipated Items. The second is the Letter of Public Interest Finding. These letter templates can be accessed through the following links:

http://www.oregon.gov/ODOT/Business/Documents/Anticipated_Item_Template.docx

http://www.oregon.gov/ODOT/Business/Documents/LPIF_Template.docx

(This page intentionally left blank.)



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 7

Design Follow-Up

7 | Design Follow-Up

Construction Support

Your part of getting the project out to bid is now completed, providing that your plans, specs, and estimate are clear enough that any of the bidders don't have questions about them. Usually, all the questions that the bidders have are directed to the Project Manager that will be overseeing the contract. If he gets a question on part of your work that he can't answer, he will contact you for an answer. Keep a copy of all the documents you submitted close to your desk until the bid is opened.

After the bid is opened, send a copy of all the Sign Drawings to the Project Manager and the Materials Inspection Section. The Sign Drawings will be used to actually build all of the non-standard signs on the project.

Sometimes unexpected things occur as part of construction. It is not unusual to get a call from the Project Manager asking for a design for a sign that has been hit by a vehicle and destroyed. Sometimes signs disappear off the project and will need replacing. These requests require immediate attention since time is very critical. The permanent signing is one of the last things to happen as part of a contract; the Contractor may be looking at liquidated damages if they run over the scheduled contract completion date.

You will also have to answer questions about the location of sign placement. There are places in the state that have very little soil cover over solid rock and the Contractor will want to move the sign placement to allow for drilling the sign footing hole. Be aware of proper sign distances when you allow signs to be moved. Do not approve moving a sign if it violates sign spacing requirements. If moving the sign is required, you may have to move the location of several signs to accommodate one installation. You can also explore placing more than one sign at a given place, but do not overload the driver with too much information on a single installation.

You may also be requested to change the type of support that a sign was designed to receive. Some of these requests make good sense and should be approved. Be careful that you have a bid item for the new support or have the Project Manager write a Contract Change Order (CCO) to accommodate the new support. Since at the time of design, you cannot be aware of what is occurring or what will occur before the sign is installed, be flexible in allowing changes. Moving a sign to a Signal Pole Mount to avoid blocking a new commercial sign would be a good example of things that occur that you cannot anticipate.

Shop Drawings / Submittals

Sign designs for typical MUTCD signs and standard Oregon signs can be found in the FHWA [Standard Highway Signs Manual](#) (See Appendix B) and the Oregon [Sign Policy & Guidelines for the State Highway System](#) (See Appendix B). Signs that appear in these books do not require shop drawings since the designs are already available.

Signs

Material submittals (shop drawings) for non-standard signs will be needed by the sign fabricator prior to fabrication. Section 940 of the 2008 Oregon Standard Specifications for Construction requires the Engineer of Record to supply these to the contractor upon request. The request will usually come from the Project Manager's office. The designer provides the Project Manager with enough copies of shop drawings for each non-standard sign to insure that all interested parties receive copies. This includes the Project Manager, Prime Contractor, Signing Sub-Contractor, and the Sign Supplier (fabricator). A single set of shop drawings also must be sent to the ODOT Materials Inspection Unit in Portland for use in inspecting and approving of the signs upon fabrication. Larger sets should be mailed, while smaller sets can be faxed to (503) 653-3085.

Shop drawings for non-standard signs are most easily produced at the same time as the Sign Detail sheets. Since the GuidSIGN sign design software is necessary to design these signs for the data tables, it only requires a few more steps to create a report for each sign. ODOT users have a custom sheet style and report form set up for shop (contract) drawings within the GuidSIGN program. It shows the following information on an 8½" x 11" print for each individual sign: Project name, sign number, dimensions, border width, corner radius, color and type of background sheeting, color and type of legend, sign type, substrate material, and number required. Each sheet also shows a to-scale likeness of that particular sign along with detailed dimensioning for all pieces of legend and the spacing in between. There is a spacing chart included which specifies positioning for each individual letter, shield or arrow based on an x-y coordinate system. The program fills in most of this information automatically, but some text may need to be modified manually. Be sure to keep a complete set of these drawings for yourself. You may need to refer to them occasionally when called by an inspector or fabricator.

Quite often things change between the project design and the project construction. Things can change during construction also. The designer must occasionally add or subtract signs from the project. The final decision on adding or subtracting signs lies with the Engineer of Record (the person who stamped and signed the plans) since they are legally responsible for the signing installed according to the plans. If a decision to add or subtract signs is made, notify the Material Inspection Unit as soon as possible. If you send out sign designs for added signs to the project, fax a copy of the design to the Material Inspection Section. Otherwise they will not know there are additions and will call you for verification before they approve the signs at the sign manufacturing location. Include changes to the plans in the As-Constructed drawings made after the project is completed.

Steel Supports

Since the lengths of all the sign supports are estimated in the design stage, a field verification of the sign supports is necessary before the sign supports are ordered. Typically field verification of the wood posts and perforated steel square tube sign supports are done at the Project Managers office and you will never see them. Occasionally, they send them in for verification. A list of verified post lengths is given to the Contractor so they can order the right size posts before showing up on the project (most permanent signing is done by a sub-contractor).

Sign supports specified for Multi-Post Breakaway (MPB) and Triangular Base Breakaway (TBB) sign supports also need to be verified by the designer prior to fabrication, based on cross-sectional information provided by the Project Manager's office. The cross-sections are taken at the actual locations specified in the Sign and Post Data Tables, and then they are sent to the designer. The designer calculates the actual post size at this time and fills out a sign post drawing for that particular size and type of support.

Use the Excel spreadsheet design programs mentioned earlier to determine the actual sizes and lengths needed for each support. Blank forms for all the standard sizes of Multi-Post Breakaways and Triangular Base Breakaways (with or without "H" frames) are available from the ODOT Traffic Standards web-site at the following link:

<http://www.oregon.gov/ODOT/Engineering/Pages/Structures.aspx>.


Other forms are available at this same location for signal pole mounts and secondary sign supports (Exit Number Sign Mounts, route marker frames, "C" channels). These other forms do not require any cross-sectional information to complete. Once you have completed all of the necessary steel shop drawings, copy enough extra sets to cover all interested parties.

Provide sets for the Project Manager, Prime Contractor, Signing Sub-Contractor, and Steel Fabricator. Send these to the Project Manager to be forwarded. It is likely that the original request for drawings will come through that office. Keep an extra set for yourself in case of phone inquiries.

The Contractor will have the posts fabricated to the information shown on these drawings. This ensures that the proper size and length of support is used for each sign installation. The contractor should not begin fabrication of any steel supports until they are provided shop drawings from the Engineer of Record.

Shop drawings are not necessary for the following types of metal sign supports: perforated steel square tube sign supports, milepost marker posts, adjustable sign mounts, and mast arm street name sign mounts.

Any shop drawings required for cantilevers, sign bridges, structure mounts or bridge rail mounts are to be provided by the structural designer responsible for their design.



ODOT Traffic Sign Design Manual

3rd Edition

Chapter 8

Special Design Considerations

8 | Special Design Considerations

Review Requirements for Interstate Signing

The uniform appearance and application of signing on the Interstate Highway System is critical. Since 2003, concerns and problems on projects designed on the Interstate have elevated the importance of taking steps to assure that there is a level of quality control implemented in the review of installations for Interstate signs. Because the cost of fixing potential mistakes is more extensive on the Interstate, and because providing guidance to designers needs to be done in a timely manner to avoid conflicts with project deadlines, a set of Interstate review requirements has been established.

Project Delivery

For all STIP or construction projects with proposed changes to permanent signing on the Interstate Highway system the following review steps are required:

DAP Review

- Sign Designers submit preliminary plans through the Region Traffic Office to the Traffic Standards Unit.
- Plans will include the locations, sign content (text & symbols), estimated sizes, and anticipated support requirements for all new or revised signs. See Appendix C for further details.
- The Traffic Standards Unit shall review and make comments on the submitted preliminary signing plans within ten business days of receipt.

Advance Plan Review

- Advance signing plans shall be submitted through the Region Traffic Office to the Traffic Standards Unit along with shop drawings prior to the Plans in Hand review for the project. See Appendix C for further details.
- Any discrepancies between designers concerns and review comments shall be resolved prior to or as part of the Plans in Hand review.
- If a design project does not have a Plans in Hand review as part of its project schedule, the Sign Designer shall submit the plans (with the sign shop drawings) 4 weeks prior to Final Plans for review and acceptance by the Traffic Standards Unit. The Traffic Standards Unit will reply with comments within ten business days.

Maintenance Sign Changes and Additions

Any modifications to non-standard signs on the Interstate as part of maintenance activities must be designed by a sign designer and approved by the Traffic Standards Unit. According to the following steps:

- Sign designers will submit plans showing sign content, location, size, support and sign shop drawings to the Traffic Standards Unit for review and approval
- The Traffic Standards Unit shall review and make comments back to the designer on the submitted designs within one week
- The Traffic Standards Unit will indicate final approval by sending an E-Mail to the sign designer that indicates the sign designs that have been approved
- Non-standard signs, for the purpose of this manual, shall be considered any sign design not detailed by a sign design included in the FHWA Standard Highways Signs Manual or the Oregon State Sign Policy and Guidelines Manual.

(This page intentionally left blank.)



ODOT Traffic Sign Design Manual

3rd Edition

Appendices

Appendix A | Signing Contacts

Before starting the design, a designer may find it beneficial to assemble a list of personal contacts involved in individual aspects of the project. The following is a list of position titles that may be useful to add to the contact list for any given project. Along with each position is some insight into how that person may be of benefit to you as a contact. The names and phone numbers that correspond with these positions can be obtained from the appropriate ODOT Region Tech Center in your area of service.

Project Leader / Consultant Project Manager

The Project Leader or Consultant Project Manager will provide you with information about project scope and plan format. They can tell you information about the design schedule and the critical project deadlines. This person will also coordinate design resources that you might need, such as a sign inventory or photos. They should be able to provide you with the names of many of the other contacts, included below, for your specific project.

Roadway Designer

The roadway designer will provide all CADD files necessary to begin your own design. They provide files for existing features, new construction, right-of-way, alignments, etc... They also provide information about project scope and plan format. The roadway designer will be responsible for preliminary plans distribution.

Specification Writer

The specification writer is responsible for assembling the Plans and Specifications from each of the project disciplines and creating a single set of contract documents. The specification writer doesn't typically get involved in the project until after the Preliminary Plans phase and just prior to the Advance Plans and Specifications phase. You submit your Plans and Specifications to the specification writer for both Advance Plans and Specifications and Final Plans and Specifications. They distribute the Plans and Specifications for review. If you need to add any unique language to the boiler-plate special provisions, the changes need review and approval by the specification writer and the technical resource for that specification.

Region Sign Designer

Each Region has a designer responsible for the sign designs created in the Region. They can answer questions about design standards and signing policy. Each Region also has either a Region Traffic Manager or a Region Traffic Engineer.

Traffic-Roadway Section Staff

The Traffic-Roadway Section staff provides technical assistance on signing issues for ODOT design staff as well as consultants and local agencies. TRS staff publishes the Traffic Sign Design Manual and the Sign Policy and Guidelines. TRS staff also maintains As-Constructed Plans, speed zone orders and no parking resolutions, and provides sign designs for specialty signs. TRS staff also provides the sheet numbers for all contract signing plans. The Traffic-Roadway Section information can be found at the website: <http://www.oregon.gov/ODOT/Engineering/Pages/Disciplines.aspx>

District Sign Supervisor/Coordinator

The district sign supervisors and district sign coordinators are responsible for maintenance of all state-owned signs and supports within their maintenance district. These Supervisor/Coordinators maintain databases of their entire sign inventory within their district. The databases provide the designer with useful information to serve as a supplement to the project sign inventory and photos. The Supervisor/Coordinators can provide information as to the age and/or condition of existing signs and supports. They can also provide comments during the plan review process.

State Parks

Oregon State Parks and Recreation has an individual contact who can be reached at (503) 986-0707. The designer should contact this individual for guidance pertaining to the design of new signing or the replacement of existing signing for State Parks facilities. This contact should also be included in the plan review process for any project that contains State Parks signing.

Oregon Travel Experience (OTE)

The Oregon Travel Experience (formerly the Travel Information Council) owns and maintains all TODS (Tourist Oriented Directional Signs) and LOGOS (Motorist Informational Signing) on our state highway system. They are to be notified about any work on our system that will in any way impact their signs. They should also be contacted about any TOD or LOGO signs that are affected by work zone staging. The designer should include them in the plans review distribution, and invite their comments as to the appropriateness of any planned activities that will affect their signs. OTE also has ownership of signing programs affecting resort areas, museums, and private golf courses. Their staff can be reached at (503) 378-4508. OTE maintains a website at: <http://ortravelexperience.com/>.

Right-of-Way

The Region right-of-way office will need detailed information from the sign designer pertaining to any right-of-way or easement needs necessary to accommodate permanent signing installations on the project. They can also provide you with accurate right-of-way CADD files if the roadway designer is not able to do so.

Sign Structures Designer

You may need to request custom design assistance from a structural designer for a number of different types of steel sign supports. Some of these are covered by standard drawings. Others such as bridge rail mounts, structure mounts, cantilevers and sign bridges will require custom designs. The sign designer will need to provide detailed information, as to the size and location of these signs, for the sign structures designer to be able to complete their design. The sign designer will also want to make reference in their signing plans to these structure designs.

Geotechnical Engineer

The sign designer should contact the geotechnical engineer for help determining foundation exploration needs for overhead supports. The geotechnical engineer can help with scheduling of any drilling and testing of soil samples.

Landscape Designer

If landscape design work is included in the project, the landscape designer should be contacted to ensure that no elements of their design will conflict with the signing plans. It is not uncommon for landscape plans to include trees at or near locations where signing is needed. Those trees will eventually grow out and block the view of nearby signs.

Other Traffic Designers

These could include signal, striping, illumination or traffic control plans designers. The sign designer may need to coordinate plans with any or all of these individuals to ensure that there are no conflicts with each other's plans, such as a sign to be installed behind a luminaire pole or a DO NOT PASS sign to be installed at a location that conflicts with the striping plans. Signing plans should often make reference to other plans, such as referring to a signal design sheet for details about signs that need to be mounted on signal poles. Communicating this information with other designers is important to them, as well. For example, the signal designer will need to know about any signs to be mounted on their signal poles so that they can design the pole to satisfy all loading requirements.

Project Manager (and Inspector)

The Project Manager or Project Inspectors may contact the sign designer at various times throughout project development and construction for clarification about plans, questions about contract change orders and price agreements, and many other issues. The sign designer provides them with technical assistance when needed. The sign designer also provides working drawings for fabrication of non-standard (custom) signs, steel sign supports, secondary supports, and route marker frames. The sign designer provides them to the Project Manager upon request. They, in turn, forward copies to the fabricators for manufacture. The Project Manager needs to provide the sign designer with cross-sectional information to assist the sign designer in calculating final steel post sizes and lengths included in the working drawings.

Bicycle & Pedestrian Program Manager

The Bicycle & Pedestrian Program Manager sets policy and standards for handling of bicycle and pedestrian issues and for matters relating to design of bicycle and pedestrian facilities. Call (503) 986-3554 with any questions about the effectiveness of existing or proposed signing as it relates to bicycle and pedestrian facilities. This could involve signing for bike lanes, bike paths, multi-use paths, etc.

Construction Materials Inspection Lab

The ODOT Construction Materials Inspection Lab is responsible for inspecting custom sign designs that have been fabricated for ODOT construction projects. Sign designers should make sure to provide copies of their shop drawings to the Construction Materials Inspection Lab.

Survey Crew

The Survey Crew inventories the existing signing as they are doing the topographical survey of the project. It is a good idea to contact survey crew members to help them understand the information that needs to be collected.

Region Mobility Liaison

The Region Mobility Liaison plays an important role in coordinating vertical clearance requirements with Region and ODOT Motor Carrier Transportation Division. Contact the Region Mobility Liaison early during the scoping process for any project that includes any new overhead sign supports or any other feature that may impact vertical clearance over the roadway.

Appendix B | Sign Design Resources

In addition to your list of contacts, you will need access to a number of different resources to aid you in the development of Plans and Specifications. The following paragraphs describe a number of these resources. Some include computer links where they can be accessed or phone contacts. This is not intended as a complete list of every resource necessary, but it includes those needed regularly for most designs.

Existing Sign Inventory & Photos

In order for a designer to produce a complete set of permanent signing plans, a sign inventory of the existing sign installations is required. The inventory can be obtained in several different ways.

The best and most complete inventory is obtained when the survey crew inventories the existing signing as they are doing the topographical survey of the project. The exact location of the signs can be determined and mapped into the project plans.

The Highway Design Manual (2012 Version, Chapter 11) explains roadside inventory needs for the various classifications of projects (1R, 3R, 4R). The web-site for this manual can be accessed at: <http://www.oregon.gov/ODOT/Engineering/Pages/Manuals.aspx>

Digital Video Log

Another option for obtaining information for the sign designer to use is the digital video log. This method requires a lot of guessing on the part of the designer because they consist of digital photos snapped every .005 mile (roughly 25 feet). Exact sizes of signs and supports are nothing more than guesses on the part of the designer. This method combined with a sign database from some District Sign Crews is the least desirable of the methods mentioned. The online version of the digital video log can be found at two locations. An intranet version is available to ODOT employees at:

<http://intranet.odot.state.or.us/cf/dvl/index.cfm>.

An internet version is also available at:

<http://www.oregon.gov/odot/data/pages/road-assets-mileage.aspx>

Manual on Uniform Traffic Control Devices (MUTCD)

State Law requires that all traffic control devices placed on highways in Oregon be in compliance with the MUTCD and Oregon Supplements to the MUTCD (OAR 734-020-0005). Signs placed on the state highway system should comply with the Sign Policy and Guidelines for the State Highway System.

Existing signs and supports need to be reviewed for compliance with the current MUTCD. Once the Oregon Transportation Commission adopts a new version of the MUTCD, all traffic control devices placed in service from that date forward must comply with the MUTCD.

A list of compliance dates for the Manual on Traffic Control Devices can be found at:

<http://mutcd.fhwa.dot.gov/kno-compliance.htm>.

The MUTCD can be accessed on-line at: http://mutcd.fhwa.dot.gov/pdfs/2009r1r2/pdf_index.htm. There are links at this site that will take you to other sites where you can order the manual or you can download the entire manual.

Standard Highway Signs Manual

This site also has a link to the “Standard Highway Signs (SHS)” book that contains sign layouts for almost all the signs shown in the MUTCD. You can also go directly to that site at:

http://mutcd.fhwa.dot.gov/ser-shs_millennium.htm

Oregon Supplements to the MUTCD

The Oregon Supplements to the MUTCD can be accessed on-line at the Traffic-Roadway Section web site at:

http://www.oregon.gov/ODOT/Engineering/Documents_TrafficStandards/MUTCD-OR-Supplement.pdf

Sign Policy & Guidelines for the State Highway System

The Sign Policy and Guidelines manual can be accessed on line at:

<http://www.oregon.gov/ODOT/Engineering/Pages/Sign-Policy.aspx>

From this site you can download individual chapters or the entire manual. This manual contains information that supplements or, in some cases, takes exception to the information in the MUTCD. The Sign Policy is an ongoing document usually updated several times a year to keep up with current changes in policy. The most recent updates are available for downloading at the site previously mentioned.

ODOT Traffic Manual

The ODOT Traffic Manual provides designers with information regarding the traffic policies, practices, and organization within ODOT. It has information on different roles and responsibilities within different Sections of ODOT as well as providing information that may be necessary when considering changes in traffic control. It also includes information on where to look up specific policies, procedures, warrants, and design consideration for traffic items. The ODOT Traffic Manual is available online at the following website:

<http://www.oregon.gov/ODOT/Engineering/Pages/Manuals.aspx>

Speed Zone Orders

You will need to obtain any existing Speed Zone Order(s) for the sections of highway included inside the limits of your project. Speed Zone Orders are official documents that set out the limits of speed zones that are different than the statutory speeds listed in state law. Over the years, they have been approved by the Oregon Transportation Commission, State Highway Engineer, State Speed Control Board, Speed Zone Review Panel and the State Traffic Engineer.

The Speed Zone Order can be obtained through the Traffic-Roadway Section by calling 503-986-3571. You will need the name of the Highway and the mile point limitations of the project to give to the person answering the phone. New Speed Zone Orders do not necessarily contain School Speed 20 information. This may have to be obtained from the road authority.

Any new speed zone sign installations shown on your plans must be consistent with the speeds and locations as spelled out in the Speed Zone Order(s). Existing installations that are located improperly or are otherwise inconsistent with the Order must be corrected. This is necessary in order to allow for proper enforcement.

Use the following website to review Speed Zone Orders online:

<http://www.oregon.gov/ODOT/Engineering/Pages/Speed-Zones.aspx>

No Parking Resolution

You will need to check for any No-Parking Resolution for the state highway. These can be obtained from the Region Traffic Unit. You will need to provide the name of the highway and the mile point limits of the project.

On City streets and County roads, the local jurisdiction controls the no-parking sections of roadway. Usually, the Public Works Department can get this information for you.

No-Parking Resolutions are similar to Speed Zone Orders in that the signing in the field must reflect the language of the Resolution in order to allow for proper enforcement. If “No Parking” signing is present in a location not covered by No-Parking Resolution, it is there illegally and should be removed.

Signing which permits on-street parking in urban areas is allowed on our highway system, but it is the responsibility of the local jurisdiction to set the limits and to install, maintain and enforce the signing.

Contract Plans Development Guide

This is a two volume document that provides the designer with all the technical information, such as standards and drafting standards, to produce plans that will be bid through a Transportation Commission Services Contract. This document can be obtained on-line at:

<http://www.oregon.gov/ODOT/Engineering/Pages/CP-Development-Guide.aspx>

There is a charge for this publication.

Standard Specifications and Special Provisions

The Oregon Standard Specifications for Construction (2018) book can be obtained on-line at:

http://www.oregon.gov/ODOT/Business/Pages/Standard_Specifications.aspx

These Standard Specifications are supplemented by our Special Provisions. The most current edition of our Special Provisions can be found on-line at:

http://www.oregon.gov/ODOT/Business/Pages/Standard_Specifications.aspx

Standard Drawings

Oregon Standard Drawings can be accessed on-line at:

<http://www.oregon.gov/ODOT/Engineering/Pages/Standards.aspx>. Standard Drawings pertaining to permanent signing are located in the TM200 drawing series. Standard Drawings pertaining to structural steel sign supports can be found in the TM600 drawing series.

As-Built Plans

ODOT Traffic-Roadway Section maintains sets of “As-Built” plans as we receive them from our construction field offices. These As-Builts have not been completed for all projects that included permanent signing, but we do keep those that we receive on file. They can prove useful at times in the absence of a good sign inventory and photos. They can also provide information such as overall sign dimensions and letter sizes used on guide signs, especially those that are overhead and otherwise hard to measure in the field. As-Built plans should not be relied on for accuracy if more than 10 years old. Anything older than 10 years have a strong possibility of those signs and/or supports may have already been replaced through normal maintenance activity. If this has happened, there is no guarantee that they were replaced with something of like size. It is always better to get actual field data on-site, whenever possible. As-Builts should be considered as a last resort for inventory purposes. Inquiries about our As-Builts should be directed to (503) 986-3599.

Oregon Bicycle and Pedestrian Plan

The Oregon Bicycle and Pedestrian Plan contains a lot of good information about design and maintenance of bicycle and pedestrian facilities. There is a section which focuses on appropriate and inappropriate signing for bicycle facilities, whether they are located on the state highway system or off the highway system. The Oregon Bicycle and Pedestrian Plan can be found on the ODOT web-site at the following location:

<http://egov.oregon.gov/ODOT/HWY/BIKEPED/planproc.shtml>

OARs and ORSs

Oregon Administrative Rules (OARs) and Oregon Revised Statutes (ORS) provide important guidance in the use of permanent signing. Enforcement of many traffic signs and the associated fines are governed by the laws that they are established under. It is important to try and use sign language defined by statute and the appropriate fines established. Oregon Administrative Rules are found online at:

<http://arcweb.sos.state.or.us/banners/rules.htm>

Oregon Revised Statutes are found online at:

https://www.oregonlegislature.gov/bills_laws/Pages/ORS.aspx

Qualified Products List

The Qualified Products List (QPL) is a comprehensive list of all finished products which have been evaluated by ODOT for use on state highways. Sign designers are frequently asked by district crews and region traffic to look into implementing new products on the State Highway System. It is important to check with the QPL to ensure that products have been approved. New products that do not show up on the list can be referred to the ODOT Materials Laboratory for possible acceptance. The list of approved products can be found online at:

<http://www.oregon.gov/ODOT/Construction/Pages/Qualified-Products.aspx>

Traffic Control Devices Handbook

The Traffic Control Devices Handbook is a publication produced by the FHWA intended to augment the information from the MUTCD. The Traffic Control Devices Handbook links the standards and warrants of the MUTCD with the activities related to complying with the standards. The most recent update to the Traffic Control Devices Handbook was completed in 2013. The document is not available online, but can be purchased through different traffic related organizations.

Interstate Highways Control Cities List

This list is an AASHTO publication formally entitled “List of Control Cities for Use in Guide Signs on Interstate Highways”. Control Cities are major destinations along an interstate route, as determined by AASHTO, with input from each of the states. These Control City legends should be used in the following situations, along a freeway, to provide for consistency and continuity in directional guide signing: 1.) Interchanges between freeways; 2.) Separation points of overlapping freeway routes; 3.) On directional signs on intersecting routes, to guide traffic entering the freeway; 4.) On Pull-Through signs; 5.) On the bottom line of post-interchange distance signs. This list can be found online at:

Appendix C | Level of Development

Design Acceptance Package

The Design Acceptance Package (previously known as Concept Plans) is not a standard part of all ODOT projects. Instances when it would be appropriate include projects with complicated geometric design such as freeway and expressway projects involving grade separation and interchange ramps. These projects will usually require the use of large overhead guide signs. For situations such as this, the earlier you can identify major signing needs the better. Installations that will require the purchase of right-of-way or that will require overhead structural support design should be identified early on so that others affected (right-of-way agents, structural designers, foundations exploration crew) can have plenty of time to complete their work within the overall project schedule. At this early stage, you would likely only need to provide Signing Plan and Sign Details sheets to show location and type for major guide signs. A rough estimate of permanent signing costs might be warranted particularly where overhead supports will be required, as these are quite expensive in comparison to typical ground-mounted sign installations.

Preliminary Plans

The usual items to be completed for the Preliminary Review would be the Signing Plan Sheets, Sign Detail Sheets, and the completed Sign and Post Data Table sheets. The Specifications, Special Provisions, and Estimate are usually completed with the Advance Plans but one or more of these items may be requested on occasion at the preliminary plans stage. If you are pressed for time, it is acceptable to send out Preliminary Plans without the Sign and Post Data Tables completed. Although it would be better to include them, the most important information to show at this time is the type of signs and supports and where they are going. This can be accomplished with the Signing Plans and Sign Details only. It is not uncommon for major changes to be made as part of the Preliminary Plans review so you may be wasting time if you prepare specs and estimate at this design stage. You will want to wait until later in the process, if possible, for specs and estimate to ensure that you have thoroughly covered all items in your plans.

The Preliminary Plans are usually submitted to the Roadway Designer for review distribution. You can request that the Road Designer send copies of the package to additional parties. The preliminary plans should be sent to the District Manager and the District Sign Crew for review. Make sure these people are included in the distribution list, as they are not always automatically listed. Remember that these are the people that will be maintaining the product. The District Sign Crew review is very important as they know what signs are in the field and what kind of condition they are in. Depending on who is impacted by the project, you may want to send plans to Oregon Travel Experience (required when logo or specific service signs are impacted), State Parks and Recreation, National Park Service, US Forest Service, etc. If you find out about an entity that needs a set of plans after the distribution is sent out-go to the Contractor Plans unit, get a set of plans and mail them to that party. The more review you can get from the plans, the better set of plans you can produce.

This would be the time to have your plans reviewed by another sign designer if you have one available.

You should start receiving comments back from people within a few days. Take the time to review all the comments to see if they apply to this situation. A note back to the person submitting the comments is sometimes in order-especially if you are choosing not to incorporate the changes requested.

Advance Plans and Specifications

After you have received the comments on your Preliminary Plans, check with the Roadway Designer on your project to see if there are any changes in the Roadway Plans. Quite often, the Roadway Designer will change alignment, stationing, or some other item and forget to tell the other designers. Incorporate any changes from the designer and any changes necessary from the comments on the Preliminary Plans into your plans. The new set will be sent out as Advance Plans.

The Special Provisions and Estimate will accompany the Advance Plans. The sign designer will submit these electronically at the same as the plan sheets. Include completed Sign and Post Data Tables with the Advance Plans if not provided earlier. It would be very difficult to put together a reasonable estimate without them.

Package together your revised plans, special provisions, and estimate and deliver this to the Specifications Writer. They will incorporate your items with the items from the other designers involved in the project and send out the Advance PS&E documents. Plans are hand-delivered or mailed. Specials should be electronically “red-lined” (using track changes) and sent to the Specifications Writer attached to an e-mail message. Estimate can be hand-delivered or sent electronically.

Once the Advance Plans are sent out, you should take the time to review the Roadway and Striping Plans to make sure that they match what you are doing with the permanent signing. If they don’t match, change your plans or send a response to the other designer letting them know that the two plans do not match. You both may need to change things so they match for the final plan.

Plans-In-Hand Meeting

Prior to the completion of the Final Plans and Specifications, the project team schedules a Plans in Hand Meeting to go over responses to comments that have been made on the project. The Plans in Hand Meeting is a final opportunity for design team members to make comments and suggestions on all of the elements in the project. Attending the Plans in Hand Meeting is a good way to resolve any concerns that have come up during the design process.

Final Plans and Specifications

After you have received the comments on your Advance Plans and Specifications, check with the Roadway Designer to see if there are any changes in the Roadway Plans. Again, the Roadway Designer will often change alignment, stationing, or some other item without telling the other designers. Last minute changes in the plans sometimes result from the review at Advance Plans stage. Incorporate changes from the Roadway Designer and any changes necessary from the comments on the Advance Plans into your plans.

Once all changes have been made, the plans sheets are printed on mylars, signed by the engineer of record and sent out as Final Plans in the bid documents. The Specifications Writer must be provided with stamped, final mylars for publication. Plans that do not have a PE stamp and signature will be returned to you. You should make any final changes to your Special Provisions and Estimate, based on comments received during Advance Plans and Specifications, and submit these electronically to the Specifications Writer at the same time that mylars are submitted. When Special Provisions from all disciplines have been assembled into a single document, the Spec Writer will send out signature sheets to be stamped and signed by each Engineer of Record.

Appendix D | Sign Sizes

Table 5 | ODOT Regulatory and Warning Sign Sizes (inches)

Sign or Plaque	Sign Designation	Conventional Road		Expressway	Freeway	Minimum	Oversized
		Single Lane	Multi-Lane				
Stop	R1-1	36 x 36	36 x 36	36 x 36		30 x 30	48 x 48
Speed Limit	R2-1	36 x 48	36 x 48	48 x 60	48 x 60	30 x 36	48 x 60
Do Not Pass	R4-1	36 x 48	36 x 48	48 x 60	48 x 60	24 x 30	48 x 60
Slower Traffic Keep Right	R4-3		36 x 48	48 x 60	48 x 60	18 x 24	48 x 60
Keep Right	R4-7, 7a, 7b	36 x 48	36 x 48	48 x 60	48 x 60	24 x 30	48 x 60
Keep Left	R4-8, 8a, 8b	36 x 48	36 x 48	48 x 60	48 x 60	24 x 30	48 x 60
Do Not Enter	R5-1	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Wrong Way	R5-1a	36 x 24	42 x 30	42 x 30	42 x 30	30 x 18	42 x 30
Emergency Parking Only	R8-4	30 x 24	30 x 24	48 x 36	48 x 36		48 x 36
No Stopping on Pavement	R8-5	36 x 48	36 x 48	48 x 60	48 x 60	18 x 24	48 x 60
No Stopping Except on Shoulder	R8-6	36 x 48	36 x 48	48 x 60	48 x 60	18 x 24	48 x 60
Horizontal Alignment	W1-1, 2, 3, 4, 5	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Chevron Alignment	W1-8	24 x 30	30 x 36	36 x 48	36 x 48	18 x 24	36 x 48
Comb. Horizontal Alignment/Intersection	W1-10, 10a, 10b, 10c, 10d, 10e	36 x 36	36 x 36	48 x 48			48 x 48
Hairpin Curve	W1-11	36 x 36	36 x 36	48 x 48	48 x 48		48 x 48
Truck Rollover	W1-13	36 x 36	36 x 36	48 x 48	48 x 48		48 x 48
270-degree Loop	W1-15	36 x 36	36 x 36	48 x 48	48 x 48		48 x 48
Intersection Warning	W2-1, 2, 3, 4, 5, 6, 7, 8	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Advanced Traffic Control	W3-1, 2, 3	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Hill	W7-1	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Hill with Grade	W7-1a	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Hill Blocks View	W7-6	36 x 36	36 x 36	48 x 48	48 x 48		48 x 48
Bump or Dip	W8-1, 2	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Soft Shoulder	W8-4	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Slippery When Wet	W8-5	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Truck Crossing	W8-6	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Loose Gravel	W8-7	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48

Sign or Plaque	Sign Designation	Conventional Road		Expressway	Freeway	Minimum	Oversized
		Single Lane	Multi-Lane				
Rough Road	W8-8	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Low Shoulder	W8-9	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Uneven Lanes	W8-11	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
No Center Line	W8-12	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Bridge Ices Before Road	W8-13	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Fallen Rocks	W8-14	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Grooved Pavement	W8-15	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Metal Bridge Deck	W8-16	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Shoulder Drop-Off	W8-17	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Road May Flood	W8-18	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Gusty Winds Area	W8-21	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Fog Area	W8-22	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
No Shoulder	W8-23	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Shoulder Ends	W8-25	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Left (Right) Lane Ends	W9-1	36 x 36	36 x 36	48 x 48	48 x 48	30 x 30	48 x 48
Bicycle	W11-1	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Pedestrian	W11-2	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Large Animals	W11-3, 4, 16, 17, 18, 19, 20, 21, 22	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Farm Vehicle	W11-5	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Snowmobile	W11-6	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Equestrian	W11-7	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Emergency Vehicle	W11-8	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Handicapped	W11-9	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Truck	W11-10	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Golf Cart	W11-11	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Horse-Drawn Vehicle	W11-14	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Bicycle/Pedestrian	W11-15	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Trail Crossing	W11-15a	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Double Arrow	W12-1	36 x 36	36 x 36	48 x 48		30 x 30	48 x 48
Advisory Speed (Plaque)	W13-1P	24 x 24	24 x 24	30 x 30	30 x 30	18 x 18	30 x 30
Advisory Exit or Ramp Speed	W13-2, 3	36 x 48	36 x 48	48 x 60	48 x 60	24 x 30	48 x 60
Dead End, No Outlet	W14-1, 2	36 x 36	36 x 36			30 x 30	48 x 48

Note: This table contains only those signs where ODOT has determined to use sizes larger than the Federal standards listed in MUTCD Table 2B-1 and Table 2C-2.

Appendix E | Mileage Control Table

Table 6 | Control Points Established as City Centers

City	Highway	M.P.	Description	County
A				
Adair Village	091(1W)	75.70	Jct. Pacific Highway West 091 & Arnold Ave.	Benton
Adams	008AA	11.90	Jct. Cayuse-Adams Front. Rd. 008AA (Old Oregon Washington Hwy) & Preston St.	Umatilla
Adrian	450	11.98	Jct. Succor Creek Hwy. 450 (1st. St.) & Main St.	Malheur
Albany	058	2.25	Jct. Albany-Junction City Hwy. 058 & Albany-Corvallis Hwy. 031 (Pacific Blvd.)	Linn
	031	11.28		
Amity	091(1W)	44.68	Jct. Pacific Highway West 091 (Trade St.) & Bellevue-Hopewell Hwy. 153 (5th St.)	Yamhill
	153	6.23		
Antelope	291	7.96	Jct. Shaniko-Fossil Hwy. 291 (Main St.) & Antelope Hwy. 293	Wasco
	293	13.52		
Arlington	002	137.59	Jct. of Columbia River Hwy. 002 & John Day Hwy. 005	Gillam
	005	0.00		
Ashland	063	19.11	Jct. Rogue Valley Hwy. 063 (Main St.) & Water St.	Jackson
Astoria	092(2W)	98.13	Jct. Lower Columbia River Hwy. 092 (Marine Dr.) & 14th St.	Clatsop
Athena	334	17.34	Jct. Athena-Holdman Hwy. 334 (Main St.) & 3rd St.	Umatilla
Aumsville			Jct. Main St. & 1st St.	Marion
Aurora	081(1E)	25.01	Jct. Pacific Highway East 081 & Main St.	Marion
B				
Baker City	071	50.96	Jct. Whitney Hwy. 071 (Main St.) & La Grande-Baker Hwy. 066 (Bridge St.) & Auburn Ave.	Baker
	066	52.04		
Bandon	009	273.94	Jct. Oregon Coast Hwy. 009 (2nd St.) & Elmira Ave.	Coos
Banks	102	82.97	Jct. Nehalem Hwy. 102 (Main St.) & Market St.	Washington
Barlow	081(1E)	22.89	Jct. Pacific Highway East 081 & Barlow Rd. (Irving St)	Clackamas
Bay City	009	59.93	Jct. Oregon Coast Hwy. 009 & C St. (Hayes Oyster Dr.)	Tillamook
Beaverton	029	3.95	Jct. Tualatin Valley Hwy. 029 (S.W. Canyon Rd.) & S.W. Broadway	Washington
Bend	017	20.99	Jct. McKenzie-Bend Hwy. 017 (E. 3rd St.) & Central Oregon Hwy. 007 (Greenwood Ave.)	Deschutes
	007	0.51		
Boardman	002	164.16	Columbia River Hwy. 002 overcrossing Boardman Conn. 002GX	Morrow
	002GX	2C164.15		
Bonanza	023	6.97	Jct. Dairy-Bonanza Hwy. 023 (Market St.) & Central St.	Klamath
Brookings	009	357.08	Jct. Oregon Coast Hwy. 009 (Chetco Ave.) & Pacific Ave.	Curry
Brownsville	212	6.23	Jct. Halsey-Sweet Home Hwy. 212 (Bishop Way) & Main St.	Linn

City	Highway	M.P.	Description	County
Burns	007	131.50	Jct. Central Oregon Hwy. 007 (Broadway Ave.) & Steens Hwy. 442 (Monroe St.)	Harney
	442	0.00		
Butte Falls			Jct. Broad St. & Fir Ave.	Jackson
C				
Canby	081(1E)	21.14	Jct. Pacific Highway East 081 (1st Ave.) & Ivy St.	Clackamas
Cannon Beach	009	29.53	Oregon Coast Hwy. 009 overcrossing Sunset Blvd.	Clatsop
Canyon City	048	1.94	Jct. John Day-Burns Hwy. 048 & Main St.	Grant
Canyonville			Jct. Main St. & 1st St.	Douglas
Carlton	029	37.99	Jct. Tualatin Valley Hwy. 029 (Main St.) & Pine St.	Yamhill
Cascade Locks			Jct. NW Wa Na Pa St. & Forest Lane	Hood River
Cave Junction	025	28.95	Jct. Redwood Hwy. 025 & Oregon Caves Hwy. 038	Josephine
	038	0.00		
Central Point			Jct. S. Front St. & Pine St.	Jackson
Chiloquin	488	4.58	Chiloquin Spur Hwy. 488 (Chocktoot St.) at east end of Williamson River Bridge	Klamath
Clatskanie	092(2W)	61.70	Jct. Lower Columbia River Hwy. 092 & Mist-Clatskanie Hwy. 110	Columbia
	110	0.00		
Coburg			Jct. Van Duyn Rd. & Pearl St.	Lane
Columbia City	092(2W)	31.02	Jct. Lower Columbia River Hwy. 092 & E St.	Columbia
Condon	005	38.07	Jct. John Day Hwy. 005 (Main St.) & Wasco-Heppner Hwy. 300 (Walnut St.)	Gilliam
	300	40.68		
Coos Bay	009	238.31	Jct. Oregon Coast Hwy. 009 (Broadway) & Anderson Ave.	Coos
Coquille	035	11.14	Jct. Coos Bay-Roseburg Hwy. 035 (Birch St.) & Main St.	Coos
Cornelius	029	16.56	Jct. Tualatin Valley Hwy. 029 (Adair St.) & 12th Ave.	Washington
Corvallis	091(1W)	83.42	Jct. Pacific Highway West 091 (4th St.) & Corvallis-Lebanon Hwy. 210 (Van Buren Ave.)	Benton
	210	-0.10		
Cottage Grove	226	14.79	Jct. Goshen-Divide Hwy. 226 (9th St.) & Main St.	Lane
Cove	342	13.52	Jct. Cove Hwy. 342 (Main St.) & French St.	Union
Creswell	226	5.78	Jct. Goshen-Divide Hwy. 226 (Front St.) & Oregon Ave.	Lane
Culver	361	8.98	Jct. Culver Hwy. 361 (1st Ave.) & C St.	Jefferson
D				
Dallas	191	3.40	Jct. Kings Valley Hwy. 191 (Main St.) & Washington St.	Polk
Damascus	174	2.60	Jct. Clackamas-Boring Hwy. 174 & SE Foster Rd.	Clackamas
Dayton	150	0.48	Jct. Salem-Dayton Hwy. 150 (3rd St.) & Amity-Dayton (Ferry St.)	Yamhill
	155	9.19		
Dayville	005	131.14	Jct. John Day Hwy. 005 & South Fork Rd.	Grant
Depoe Bay	009	127.46	Jct. Oregon Coast Hwy. 009 & Collins St.	Lincoln
Detroit	162	50.28	Jct. North Santiam Hwy. 162 & Forest Ave.	Marion
Donald			Jct. Main St. & Donald-Gervais Rd.	Marion
Drain	045	50.25	Jct. Umpqua Hwy. 045 (B St.) & Cedar St.	Douglas
Dufur	004	13.22	Jct. The Dalles-California Hwy. 004 & Boyd Loop Rd. /1st St.	Wasco

City	Highway	M.P.	Description	County
Dundee	091(1W)	26.11	Jct. Pacific Highway West 091 & S.W. 9th St.	Yamhill
Dunes City	009	195.98	Jct. Oregon Coast Hwy. 009 & Clear Lake Rd.	Lane
Durham	141	8.32	Jct. Beaverton-Tualatin Hwy. 141 (Upper Boones Ferry Rd.) & Bridgeport Rd. / Rivendell Rd.	Washington
E				
Eagle Point	022	9.42	Jct. Crater Lake Hwy. 022 & Nick Young Rd. / S. Royal Ave.	Jackson
Eastside			Jct. D St. & 6th Ave.	Coos
Echo	320	35.70	Jct. Lexington-Echo Hwy. 320 (Main St.) & Thielsen St.	Umatilla
Elgin	010	20.25	Jct. Wallowa Lake Hwy. 010 (8th Ave.) & Weston-Elgin Hwy. 330 (Division St.)	Union
	330	40.84		
Elkton	045	36.44	Jct. Umpqua Hwy. 045 (A St.) & Elkton-Sutherlin Hwy. 231	Douglas
	231	0.00		
Enterprise	010	65.02	Jct. Wallowa Lake Hwy. 010 (North St.) & Enterprise-Lewiston Hwy. 011 (1st St.)	Wallowa
	011	43.19		
Estacada	161	33.49	Jct. Woodburn-Estacada Hwy. 161 & Clackamas Hwy. 171	Clackamas
	171	23.36		
Eugene	091(1W)	123.37	Jct. Pacific Highway West 091 (7th Ave.) & Eugene-Springfield Hwy. 227 (Washington St.)	Lane
	227	0.00		
F				
Fairview	123	17.62	Jct. Northeast Portland Hwy. 123 (Sandy Blvd.) & Fairview Ave.	Multnomah
Falls City			Jct. North Main St. & Mitchell St. & 4th St.	Polk
Florence	009	190.23	Jct. Oregon Coast Hwy. 009 & Florence-Eugene Hwy. 062 (Ninth St.)	Lane
	062	0.02		
Forest Grove			Jct. Pacific Ave. & College Way	Washington
Fossil	005	58.15	Jct. John Day Hwy. 005 (7th St.) & Shaniko-Fossil Hwy. 291 (Washington St.)	Wheeler
	291	42.95		
G				
Garibaldi	009	55.56	Jct. Oregon Coast Hwy. 009 (Garibaldi Ave.) & 7th St.	Tillamook
Gaston	029	25.45	Jct. Tualatin Valley Hwy. 029 (Front St.) & Main St.	Washington
Gates	162	33.11	Jct. North Santiam Hwy. 162 & Horeb St.	Linn
Gearhart	009	18.83	Jct. Oregon Coast Hwy. 009 & Pacific Way	Clatsop
Gervais	081(1E)	36.22	Jct. Pacific Highway East 081 & Gervais Rd.	Marion
Gladstone	064	11.05	East Portland Freeway 064 overcrossing Washington St.	Clackamas
Glendale			Jct. Molly St. & Pacific Ave.	Douglas
Gold Beach	009	328.48	Jct. Oregon Coast Hwy. (Ellensburg St.) & Moore St.	Curry
Gold Hill	271	2.36	Jct. Sams Valley Hwy. 271 (2nd Ave.) and Gold Hill Spur Hwy. 486 (2nd Ave.) & Dardanelles St.	Jackson
	486	2.36		
Granite			Jct. Main St. & Center St.	Grant
Grants Pass	025	-0.79	Jct. Redwood Hwy. 025 (6th St.) & G St.	Josephine

City	Highway	M.P.	Description	County
Grass Valley	042	28.36	Jct. Sherman Hwy. 042 (Mill St.) & Sherars Bridge Hwy. 290 (Krusow St.)	Sherman
	290	28.42		
Greenhorn			Jct. Main St. & Greenhorn Rd. & Bonanza Rd.	Baker
Gresham			Jct. Powell Blvd. & Main Ave.	Multnomah
H				
Haines	066	40.69	Jct. La Grande-Baker Hwy. 066 (Front St.) & 4th St. (Anthony Lakes Hwy.)	Baker
Halfway	481	54.70	Jct. Baker-Copperfield Spur Hwy. 481 & Halfway-Cornucopia Hwy. 413 (Main St.) & Pine Creek Hwy. 414 (Record St)	Baker
	413	11.45		
	414	0.00		
Halsey	058	19.36	Jct. Albany-Junction City Hwy. 058 (2nd St.) & Halsey-Sweet Home Hwy. 212 (American Dr.)	Linn
	212	0.00		
Hammond	104	0.10	Jct. Fort Stevens Hwy. 104 (Pacific Dr.) & Lake Dr.	Clatsop
Happy Valley			Jct. King Rd. & 129th Ave.	Clackamas
Harrisburg	058	28.59	Jct. Albany-Junction City Hwy. 058 (3rd St.) & Smith St.	Linn
Helix	335	0.00	Jct. Havana-Helix Hwy. 335 (Main St.) & Columbia St.	Umatilla
Heppner	052	45.89	Jct. Heppner Hwy. 052 (May St.) & Wasco-Heppner Hwy. 300 (Main St.)	Morrow
	300	84.12		
Hermiston	054	5.46	Jct. Umatilla-Stanfield Hwy. 054 (1st St.) & Main St.	Umatilla
Hillsboro	029	13.29	Jct. Tualatin Valley Hwy. 029 (Baseline St.) & Hillsboro-Silverton Hwy. 140 (1st Ave.)	Washington
	140	0.00		
Hines	007	129.12	Jct. Central Oregon Hwy. 007 & Barnes Ave.	Harney
Hood River	002	63.92	Columbia River Hwy. 002 undercrossing Hood River Front. Rd. 002DS (2nd St.)	Hood River
	002DS	1F63.92		
Hubbard	081(1E)	29.54	Jct. Pacific Highway East 081 & J St.	Marion
Huntington	449	5.89	Jct. Huntington Hwy. 449 & Snake River Rd (E. Washington St)	Malheur
I				
Idanha	162	54.54	Jct. North Santiam Hwy. 162 & Main St.	Wallowa
Imbler	010	12.20	Jct. Wallowa Lake Hwy. 010 (Ruckman St.) & Main St.	Union
Independence	043	2.35	Jct. Monmouth-Independence Hwy. 043 (Monmouth St.) & Independence Hwy. 193 (Main St.)	Polk
	193	6.34		
Ione	052	27.88	Jct. Heppner Hwy. 052 & Green St.	Morrow
Irrigon	002	175.57	Jct. Columbia River Hwy. 002 (Main Ave.) & Division St.	Morrow
Island City	010	2.41	Jct. Wallowa Lake Hwy. 010 (B St.) & Cove Hwy. 342 (1st. St.)	Union
	342	0.00		

City	Highway	M.P.	Description	County
J				
Jacksonville	272	33.23	Jct. Jacksonville Hwy. 272 (California St.) & Oregon St.	Jackson
Jefferson	164	6.12	Jct. Jefferson Hwy. 164 & Main St.	Linn
John Day	005	162.29	Jct. John Day Hwy. 005 (Main St.) & John Day-Burns Hwy. 048 (Canyon Blvd.)	Grant
	048	0.00		
Johnson City			Jct. Roots St. & 81st. Ave.	Clackamas
Jordan Valley	456	20.44	Jct. I.O.N. Hwy. 456 (Main St.) & Bassett St.	Malheur
Joseph	010	71.42	Jct. Wallowa Lake Hwy. 010 (Main St.) & Joseph-Wallowa Lake Hwy. 351 (Main St.) & Little Sheep Creek 350 (Wallowa Ave.)	Wallowa
	350	0.00		
	351	0.00		
Junction City	091(1W)	109.47	Jct. Pacific Highway West 091 (Ivy St.) & 6th Ave.	Lane
K				
Keizer			River Rd. N. & Chemawa Rd.	Marion
King City	091(1W)	11.19	Jct. Pacific Highway West 091 & Royalty Parkway	Washington
Klamath Falls			Jct. Klamath Ave. & 5th St.	Klamath
L				
Lafayette	091(1W)	32.29	Jct. Pacific Highway West 091 (3rd St.) & Madison St.	Yamhill
LaGrande	010	0.00	Jct. Wallowa Lake Hwy. 010 (Island Ave.) & La Grande-Baker Hwy. 066 (Adams Ave.)	Union
	066	2.19		
Lake Oswego	003	6.13	Jct. Oswego Hwy. 003 (State St.) & A Ave.	Clackamas
Lakeside	009	222.73	Jct. Oregon Coast Hwy. 009 & Airport Way	Coos
Lakeview	019	143.03	Jct. Fremont Hwy. 019 (G St.) & Klamath Falls-Lakeview Hwy. 020 (4th St.)	Lake
	020	96.37		
Lebanon	016	13.32	Jct. Santiam Hwy. 016 (Main St.) & Grant St.	Linn
Lexington	052	36.45	Jct. Heppner Hwy. 052 (Main St.) & Lexington-Echo Hwy. 320 (E St.)	Morrow
	320	0.00		
Lincoln City	009	114.88	Jct. Oregon Coast Hwy. 009 & D River.	Lincoln
Lonerock			Main St. & Robinson Ave	Gilliam
Long Creek	028	90.26	Jct. Pendleton-John Day Hwy. 028 & Kimberly-Long Creek Hwy. 402 (Main St.)	Grant
	402	34.88		
Lostine	010	54.89	Jct. Wallowa Lake Hwy. 010 (State St.) & Wallowa St.	Wallowa
Lowell			Jct. Pengra Rd. & Moss St.	Lane
Lyons	211	24.41	Jct. Albany-Lyons Hwy. 211 (6th St.) & Main St.	Linn
M				
Madras	004	92.46	Jct. The Dalles-California Hwy. 004 (4th St.) & Culver Hwy. 361 (D St.)	Jefferson
	361	0.05		
Malin	050	24.25	Jct. Klamath Falls-Malin Hwy. 050 (Broadway St.) & Rosicky Ave.	Klamath
Manzanita	009	43.18	Jct. Oregon Coast Hwy. 009 & Laneda Ave.	Tillamook
Maupin	004	45.20	Jct. The Dalles-California Hwy. 004 (Deschutes Ave.) & 4th St.	Wasco
Maywood Park	064	23.25	Jct. East Portland Freeway 064 & Prescott St.	Multnomah

City	Highway	M.P.	Description	County
McMinnville	091(1W)	37.72	Jct. Pacific Highway West 091 (Adams St.) & 3rd St.	Yamhill
Medford			Jct. Central Ave. & 8th St.	Jackson
Merrill	050	13.99	Jct. Klamath Falls-Malin Hwy. 050 (Front St.) & Main St.	Klamath
Metolius	361	4.27	Jct. Culver Hwy. 361 (Jefferson Ave.) & 6th St.	Jefferson
Mill City			Jct. Broadway St. & 1st. Ave.	Marion
Millersburg	001NH	7C235.64	Jct. Murder Creek Conn. 001NH & Murder Creek Conn. 001NF (Old Santiam Rd.)	Linn
	001NF	5C235.90		
Milton-Freewater	008	30.62	Jct. Oregon-Washington Hwy. 008 (Main St. & Columbia St.)	Umatilla
Milwaukie	081(1E)	5.46	Jct. Pacific Highway East (McLoughlin Blvd.) & Clackamas Hwy. 171	Clackamas
	171	0.11		
Mitchell	041	65.94	Jct. Ochoco Hwy. 041 & Service Creek-Mitchell Hwy. 390	Wheeler
	390	24.32		
Molalla	161	12.76	Jct. Woodburn-Estacada Hwy. 161 (Main St.) & Molalla Ave.	Clackamas
Monmouth	091(1W)	63.42	Jct. Pacific Highway West 091 (Pacific Ave.) & Monmouth Hwy. 194 (Main St.)	Polk
	194	7.56		
Monroe	091(1W)	101.15	Jct. Pacific Highway West 091 (5th St.) & Territorial Hwy. 200	Benton
	200	-0.03		
Monument	402	13.74	Jct. Kimberly-Long Creek Hwy. & 2nd St.	Grant
Moro	042	18.19	Jct. Sherman Hwy. 042 (Main St.) & 1st St.	Sherman
Mosier	002	69.79	Columbia River Hwy. 002 undercrossing Mosier Interchange Conn. 002IC	Wasco
	002IC	4C69.65		
Mt. Angel	140	46.13	Jct. Hillsboro-Silverton Hwy. 140 & Main St.	Marion
Mt. Vernon	005	154.03	Jct. John Day Hwy. 005 (Main St.) & Pendleton-John Day Hwy. 028 (Mountain Blvd.)	Grant
	028	120.51		
Myrtle Creek			Jct. Main St. & 2nd Ave.	Douglas
Myrtle Point	035	20.58	Jct. Coos Bay-Roseburg Hwy. 035 (8th St.) & Spruce St.	Coos
N				
Nehalem	009	44.98	Jct. Oregon Coast Hwy. 009 (H St.) & 7th St.	Tillamook
Newberg	091(1W)	23.45	Jct. Pacific Highway West 091 (Hancock St.) & Hillsboro-Silverton Hwy. 140 (College St.)	Yamhill
	140	20.15		
Newport	009	140.36	Jct. Oregon Coast Hwy. 009 & Corvallis-Newport Hwy. 033 (Olive St.)	Lincoln
	033	0.00		
North Bend	009	235.41	Jct. Oregon Coast Hwy. 009 (Sherman Ave.) & Cape Arago Hwy. 240 (Virginia Ave.)	Coos
	240	0.00		
North Plains	047	57.16	Jct. Sunset Hwy. 047 & N. Plains Conn. 047AK (Glencoe Rd.\1st St.)	Washington
	047AK	2C57.22		
North Powder	006	285.68	Old Oregon Trail Hwy. 006 overcrossing La Grande-Baker Hwy. 066	Union
	066	32.29		
Nyssa	007	265.97	Jct. Central Oregon Hwy. 007 (Main St.) & Succor Creek Hwy. 450 (Adrian Blvd.)	Malheur
	450	0.02		

City	Highway	M.P.	Description	County
O				
Oakland			Jct. 1st St. & Locust St.	Douglas
Oakridge	018	35.48	Jct. Willamette Hwy. 018 & Crestview St.	Lane
Ontario			Jct. Oregon St. & Idaho St.	Malheur
Oregon City	081(1E)	12.56	Jct. Main St. & Pacific Highway East 081 (5th St.)	Clackamas
P				
Paisley	019	98.36	Jct. Fremont Hwy. 019 (Main St.) & Mill St.	Lake
Pendleton	067	3.39	Jct. Pendleton Hwy. 067 (Dorion Ave.) & Main St.	Umatilla
Philomath	033	50.63	Jct. Corvallis-Newport Hwy. 033 (Main St.) & 13th St.	Benton
Phoenix	063	11.49	Jct. Rogue Valley Hwy. 063 (Main St.) & 4th St.	Jackson
Pilot Rock	028	15.58	Jct. Pendleton-John Day Hwy. 028 (Birch St. & Birch Pl.)	Umatilla
Portland			Jct. Burnside & Front St. (Naito Parkway)	Multnomah
Port Orford	009	300.99	Jct. Oregon Coast Hwy. 009 (Oregon St.) & Port Orford Hwy. 251 (9th St.)	Curry
	251	0.76		
Powers	242	18.50	Jct. Powers Hwy. 242 (1st Ave.) & Poplar St.	Coos
Prairie City	005	175.26	Jct. John Day Hwy. 005 (Front St.) & Main St.	Grant
Prescott			Jct. Graham Rd. & Blakely St.	Columbia
Prineville	041	18.75	Jct. Ochoco Hwy. 041 (3rd St.) & Crooked River Hwy. 014 (Main St.)	Crook
	014	0.00		
R				
Rainier	092(2W)	46.97	Jct. Lower Columbia River Hwy. 092 (B St.) & 1st St.	Columbia
Redmond	480	121.29	Jct. Redmond Spur Hwy. (6th St.) & Evergreen Ave.	Deschutes
Reedsport	009	211.58	Jct. Oregon Coast Hwy. 009 & Umpqua Hwy. 045	Douglas
	045	0.00		
Richland	012	42.15	Jct. Baker-Copperfield Hwy. 012 (Main St.) & 1st St.	Baker
Riddle			Jct. Main St. & 5th Ave.	Douglas
Rivergrove			Jct. Childs Rd. & Pilkington Rd.	Clackamas
Rockaway Beach	009	50.82	Jct. Oregon Coast Hwy. 009 & 1st Ave.	Tillamook
Rogue River	001	48.82	Pacific Hwy. 001 overcrossing Depot St. Conn. 060AF (Depot St.)	Jackson
	060AF	1C8.96		
Roseburg	001	124.14	Pacific Hwy. 001 overcrossing North Umpqua Hwy. 138 (Harvard Ave.)	Douglas
	138	-0.89		
Rufus	002	109.95	Jct. Columbia River Hwy. 002 overcrossing Rufus Conn. 002FK (John Day Dam Rd.)	Sherman
	002FK	2C109.95		

City	Highway	M.P.	Description	County
S				
St. Helens	092(2W)	28.56	Jct. Lower Columbia River Hwy 092 & Columbia Blvd.	Columbia
St. Paul	140	28.11	Jct. Hillsboro-Silverton Hwy. 140 (Main St.) & Church Ave.	Marion
Salem	030	26.14	Jct. Willamina-Salem Hwy. 030 (Center St.) & Willamina-Salem Hwy. Conn. 072AC (Commercial St.)	Marion
	072AC	1C4.96		
Sandy	026	24.40	Jct. Mt. Hood Hwy. 026 (Pioneer Blvd.) & Eagle Creek-Sandy Hwy 172 (Meinig Rd.)	Clackamas
	172	5.88		
Scappoose	092(2W)	20.91	Jct. Lower Columbia River Hwy. 092 & Columbia Ave.	Columbia
Scio	211	9.80	Jct. Albany-Lyons Hwy. 211 (1st Ave.) & Main St.	Linn
Scotts Mills			Jct. 3rd St. & Grandview Ave.	Marion
Seaside	009	21.05	Jct. Oregon Coast Hwy. 009 (Roosevelt Dr.) & Broadway	Clatsop
Seneca	048	25.26	Jct. John Day-Burns Hwy. 048 (Barnes Ave.) & 1st St.	Grant
Shady Cove	022	20.09	Jct. Crater Lake Hwy. 022 & Rogue River Dr.	Jackson
Shaniko	291	0.04	Jct. Shaniko-Fossil Hwy. 291 & D St.	Wasco
Sheridan	157	7.13	Jct. Willamina-Sheridan Hwy. 157 (Main St.) & Bridge St.	Yamhill
Sherwood			Jct. Pine & Oregon St. (1st St.)	Washington
Siletz	181	23.81	Jct. Siletz Hwy. 181 (Gaither St.) & Buford Ave.	Lincoln
Silverton	140	(2)50.50	Jct. Hillsboro-Silverton Hwy. 140 (1st St.) & Cascade Hwy. South 160 (Oak St.)	Marion
	160	29.65		
Sisters	015	92.50	Jct. McKenzie Hwy. 015 (Cascade St.) & Elm St.	Deschutes
Sodaville			Jct. Main St. & Ash St.	Linn
Spray	005	92.57	Jct. John Day Hwy. 005 (Main St.) & Willow St.	Wheeler
Springfield	015	1.57	Jct. McKenzie Hwy. 015 (South A St.) & Springfield Hwy. 228 (2nd St.)	Lane
	228	1.40		
Stanfield	054	11.03	Jct. Umatilla-Stanfield Hwy. 054 (Main St.) & Coe Ave.	Umatilla
Stayton			Jct. Washington St. & 1st Ave.	Marion
Sublimity			Jct. Starr St. & Center St.	Marion
Summerville			Jct. Main St. & 4th St.	Union
Sumpter	410	0.50	Jct. Sumpter Hwy. 410 (Mill St.) & Granite St.	Baker
Sutherlin	231	25.39	Jct. Elkton-Sutherland Hwy. 231 (Central Ave.) & Calapooia St.	Douglas
Sweet Home	016	27.07	Jct. Santiam Hwy. 016 (Main St.) & Halsey-Sweet Home Hwy. 212	Linn
	212	21.40		

City	Highway	M.P.	Description	County
T				
Talent	063	14.20	Jct. Rogue Valley Hwy. 063 & W. Valley View Rd.	Jackson
Tangent	058	8.81	Jct. Albany-Junction City Hwy. 058 & Birdfoot Dr.	Linn
The Dalles			Jct. 3rd St. & Union St.	Wasco
Tigard	091(1W)	8.65	Jct. Pacific Hwy. West 091 & Beaverton-Tigard Hwy. 144	Washington
	144	5.90		
Tillamook	009	65.74	Jct. Oregon Coast Hwy. 009 (Main Ave.) & Wilson River Hwy. 037 (3rd St.) & Netarts Hwy. 131 (3rd St.)	Tillamook
	037	0.00		
	131	9.08		
Timberline	173	0.12	Beg. Of Timberline Hwy. 173	Clackamas
Toledo			Jct. Main St. & 3rd St.	Lincoln
Troutdale			Jct. Historic Columbia River Hwy. (Columbia Blvd). & SW 257th. Ave (NW Graham Rd)	Multnomah
Tualatin	001	289.50	Jct. Pacific Hwy. 001 undercrossing Nyberg Rd.	Washington
Turner			Jct. 3rd St. & Chicago St.	Marion
U				
Ukiah	341	1.24	Jct. Main St. & Camas St.	Umatilla
Umatilla	002	182.96	Jct. 6th St. & G St.	Umatilla
Union	066	16.51	Jct. La Grande-Baker Hwy. 066 (Main St.) & Beakman St.	Union
	340	0.00		
Unity	005	212.45	Jct. John Day Hwy. 005 (Main St./1st Ave.) & South Burnt River Ln. (S. Fork Rd.)	Baker
V				
Vale	005	278.21	Jct. John Day Hwy. 005 (Glenn St.) & Central Oregon Hwy. (A St.)	Malheur
	007	246.39		
Veneta	062	46.92	Jct. Florence-Eugene Hwy. 062 and Territorial Hwy. 200	Lane
	200	19.49		
Vernonia	102	62.09	Jct. Nehalem Hwy. 102 (Bridge St.) & State Ave.	Columbia
W				
Waldport	009	155.90	Jct. Oregon Coast Hwy. 009 & Alsea Hwy. 027 (Hemlock St.)	Lincoln
	027	0.00		
Wallowa	010	47.31	Jct. Wallowa Lake Hwy. 010 (1st St.) & Ellen St. & Whiskey Creek Rd.	Wallowa
Warrenton	104	3.32	Jct. Ft. Stevens Hwy. 104 (Main Ave.) & Warrenton-Astoria Hwy. 105 (Harbor St.)	Clatsop
	105	0.00		
Wasco	300	-0.09	Jct. Wasco-Heppner Hwy. 300 (Clark St.) & Celilo-Wasco Hwy. 301 (1st. St.)	Sherman
	301	15.57		
Waterloo			Jct. Gross St. & 4th St.	Linn
West Linn	064	8.82	E. Portland Freeway Hwy 064 overcrossing Oswego Hwy. 003 (Willamette Dr.)	Clackamas
	003	11.17		
Weston			Jct. Water St. & Main St.	Umatilla

City	Highway	M.P.	Description	County
Wheeler	009	47.39	Jct. Oregon Coast Hwy. 009 (Nehalem Blvd.) & Gregory St.	Tillamook
Willamina	157	2.28	Jct. Willamina-Sheridan Hwy. 157 (S. Main St.) & NW Main St.	Yamhill
Wilsonville	001	283.88	Jct. Pacific Hwy. 001 overcrossing Wilsonville Conn. 001RD (Wilsonville Rd.)	Washington
	001RD	2C283.88		
Winston	035	73.37	Jct. Coos Bay-Roseburg Hwy. 035 (Douglas Blvd.) & Main St.	Douglas
Woodburn	140	37.87	Jct. Hillsboro-Silverton Hwy. 140 & Boones Ferry Rd./Settlemier Ave.	Marion
Wood Village	002	15.96	Jct. Columbia River Hwy. 002 undercrossing NE 238th Ave. Conn. 002IO (238th Dr.)	Multnomah
	002IO	5C15.99		
Y				
Yachats	009	164.46	Jct. Oregon Coast Hwy. 009 & Yachats River Rd.	Lincoln
Yamhill	029	34.47	Jct. Tualatin Valley Hwy. 029 (Maple St.) & Yamhill-Newberg Hwy. 151 (Main St.)	Yamhill
	151	0.00		
Yoncalla			Jct. Eagle Valley Rd. (Front St.) & Applegate Ave.	Douglas

Note: Table last updated June 2015 by ODOT Road Inventory and Classification Services

Appendix F | Abbreviations

Table 7 | Common Oregon Abbreviations

Word	Abbreviation
Canyon	Cyn
College	Coll
Creek	Cr
Lake	Lk
Loop	Lp
Mount	Mt
Park	Pk
Peak	Pk
River	Riv
State	St
Springs	Spgs
University	Univ

Note: This is not intended to be a comprehensive list of abbreviations, but merely a list of those most common to Oregon and not covered in MUTCD Table 1A-1.