

CABLE DRUM SIZES AND WEIGHTS


A wide range of drums with various sizes and weights is used to store and transport our cables. The most common types of drums and their sizes and weights are shown in this table.

Flang diameter (F) mm	Core diameter (K) mm	Central hole diameter (A) mm	Largest width (B) mm	Winding width (W) mm	Empty weight Kg	Volume m³
*600	250	80	468	400	7,5	0,17
*800	400	100	480	400	14	0,31
800	500	100	500	485	43	0,31
*1000	500	100	605	485	28	0,31
1000	500	100	609	485	74	0,61
1200	600	100	724	600	108	1,04
1500	800	100	946	750	160	2,13
1600	800	100	1030	834	240	2,64
1800	900	100	1030	834	400	3,34
2100	900	100	1148	950	450	5,06
2250	1400	100	1122	830	600	5,68
2500	1450	100	1220	930	700	7,63
2500	1450	100	1458	1150	800	9,11
2650	1450	100	1488	1175	850	10,45
2800	1700	100	1520	1157	1050	11,92
3000	1600	100	1600	1235	1150	14,40

*Plastic drum

Empty drum return

To get your empty drums in the Netherlands collected quickly, please send your request to our shipping department via the website (www.tkf.eu) or by e-mail to haspels@tkf.nl. If drums have to be collected outside the Netherlands, please contact our sales staff.



- F** = Diameter flange
- K** = Diameter core
- A** = Diameter axle-hole
- B** = Largest width
- W** = Winding width